



# PRICELIST 2024

Quickcouplers and Attachments  
for **KOMATSU** excavators  
valid as of January 2024



# Table of Contents



 <p><b>3.05</b> 0,5-0,9t</p> <p>4 4</p> <p><b>PC09</b></p>	 <p><b>3.10</b> 1,4-2t</p> <p>5 7</p> <p><b>PC16-PC20</b></p>	 <p><b>3.20</b> 2-2,5t</p> <p>11 14</p> <p><b>PC24</b></p>	 <p><b>3.30</b> 2,5-4t</p> <p>18 21</p> <p><b>PC26/PC30/PC33E/PC35</b></p>
 <p><b>3.40</b> 4,5-5t</p> <p>25 28</p> <p><b>PC45</b></p>	 <p><b>3.50</b> 5-6t</p> <p>32 35</p> <p><b>PC55/PC58</b></p>	 <p><b>3.60</b> 7-8t</p> <p>40 44</p> <p><b>PC80</b></p>	 <p><b>3.70</b> 8-11t</p> <p>48 52</p> <p><b>PC88/PW98</b></p>
 <p><b>3.75</b> 8-9t</p> <p>56</p> <p><b>WB93-97</b></p>	 <p><b>3.80</b> 10-13t</p> <p>57 64</p> <p><b>PW138</b></p>	 <p><b>3.90</b> 13-16t</p> <p>67 74</p> <p><b>PC138/PW148</b></p>	 <p><b>4.00</b> 15-20t</p> <p>79 88</p> <p><b>PW158/160/168/180/198/PC170</b></p>
 <p><b>4.10</b> 19-24t</p> <p>93 102</p> <p><b>PC210/PC228</b></p>	 <p><b>4.20</b> 23-28t</p> <p>107 116</p> <p><b>PC230/PC240</b></p>	 <p><b>4.30</b> 29-38t</p> <p>121 130</p> <p><b>PC290/PC390-PC490 HRD</b></p>	 <p><b>4.35</b> 29-38t</p> <p>135 141</p> <p><b>PC360/HB365</b></p>
 <p><b>4.40</b> 39-49t</p> <p>145 148</p> <p><b>PC490LC</b></p>	 <p><b>4.50</b> 50-70t</p> <p>152 155</p> <p><b>PC700</b></p>	 <p><b>4.70</b> 90-110t</p> <p>158 159</p> <p><b>PC950</b></p>	 <p><b>4.80</b> 110-130t</p> <p>161 162</p> <p><b>PC1250</b></p>

Date of this Pricelist: January 1st 2024

With the publication of this pricelist, all previous pricelists lose their validity with immediate effect.

All prices are non-binding gross prices!

Our terms of payment and delivery apply.  
(Lehnhoff GTC: <https://www.lehnhoff.com/gtc.html>)

Printing errors, mistakes and changes reserved. Pictures may vary.  
Weights can only be given approximately due to specific deviating equipment of the excavators.

As standard  
all buckets are painted in



RAL  
7021

all quickcouplers in



RAL  
3000

All products in this pricelist can be ordered through Komatsu CPQ.  
Alternatively, please send orders directly to [komatsu.sales@lehnhoff.de](mailto:komatsu.sales@lehnhoff.de).

## Lehnhoff Hartstahl GmbH

Tel. +49 (0)72 23 / 966 - 0 Rungsstraße 10-15  
Fax +49 (0)72 23 / 966 - 109 D-76534 Baden-Baden  
E-Mail [info@lehnhoff.de](mailto:info@lehnhoff.de) Postfach 11 01 65  
[www.lehnhoff.de](http://www.lehnhoff.de) D-76487 Baden-Baden



### MS 01 Quickcoupler mechanical

for PC09

Quickcoupler with mechanical locking, incl. socket wrench  
**MS 01-2 with locking by 180° turn**



Type	Excavator	Option	Weight [kg]	PN	Price [€]
MS 01-2	PC09	-	15	LH270848	<b>1.028,00</b>

### MTL 09 Mini backhoe bucket premium

with Lehmatic adapter SW 01

Mini backhoe bucket, cutting edge 110x12mm, teeth 404F.



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
240	Lehnhoff	404F	2	0,013	22	LH236330	<b>444,00</b>
400	Lehnhoff	404F	3	0,020	28	LH236334	<b>514,00</b>

### MG 09 SY rigid Ditch bucket, rigid version

with Symlock adapter SY 01, for backhoe and front shovel application, cutting edge 110x12mm out of 500 HB steel and side edges out of 400 HB steel



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
800			-	0,040	38	LH270027	<b>826,00</b>

### MRR 1 Clearing rake

With Symlock adapter SY 01, for clearing bushes, shrubs and undergrowth, collecting tree cuttings, loosening soil and sorting work in the recycling sector. 3 segments with wear protection made of HB450 steel, cutting edge (500HB) between the segments.



Tooth-radius [mm]	Width [mm]	Teeth	Weight [kg]	PN	Price [€]
500	500	3	150	LH282591	<b>1.786,00</b>



Attachments for PC16/PC17/PC18/PC20



**MS 01 Quickcoupler mechanical**

**for PC16-PC20**

Quickcoupler with mechanical locking, incl. socket wrench, optionally with 1t load hook.

**MS 01-2 with locking by 180° turn**

Type	Excavator	Option	Weight [kg]	PN	Price [€]
MS 01-2	PC16-PC20	-	15	LH270846	<b>1.028,00</b>
MS 01-2	PC16-PC20	Load hook 1t	17	LH270767	<b>1.195,00</b>



**HS 01 DL Quickcoupler hydraulic**

**for PC16-PC20**

Quickcoupler with hydraulic locking, optionally with 1t load hook.

**With Safety locking mechanism Double Lock**

Type	Excavator	Option	Weight [kg]	PN	Price [€]
HS 01 DL	PC16-PC20	-	15	LH280189	<b>1.431,00</b>
HS 01 DL	PC16-PC20	Load hook 1t	17	LH280190	<b>1.598,00</b>



**MS 01 - Tilt Quickcoupler Tilt**

**for PC16-PC20**

Mechanical quickcoupler with Powertilt motor (PT), with direct suspension. Including 1t load hook. Excl. optional switch valve, excl. installation on excavator.

**MS 01-2 with locking by 180° turn**

Type	Excavator	Option	Tilt-Angle	Weight [kg]	PN	Price [€]
MS 01-2 - PT 4.5	PC16-PC18	Load hook 1t	2 x 87	45-49	LH268392	<b>4.227,00</b>
MS 01-2 - PT 030	PC20	Load Hook 1t	2 x 87	45-55	LH286754	<b>6.523,00</b>
Tilt switch valve		12 V			LH205585	<b>976,00</b>



## HS 01 DL - Tilt Quickcoupler Tilt

### for PC16-PC20

Hydraulic quickcoupler with Powertilt motor (PT), with direct suspension. Including 1t load hook. Excl. optional switch valve, excl. installation on excavator.






**With safety locking mechanism Double Lock**



Type	Excavator	Option	Tilt-Angle	Weight [kg]	PN	Price [€]
HS 01 DL - PT 4.5	PC16-PC18	Load hook 1t	2 x 87°	47-51	LH276405	<b>4.527,00</b>
HS 01 DL - PT 030	PC20	Load Hook 1t	2 x 87	55-59	LH286675	<b>6.994,00</b>
Tilt switch valve		12 V			LH205585	<b>976,00</b>

## SW 01 Adapter

Adapters SW 01 for bucket modification and for welding on other attachments.

Description	Weight [kg]	PN	Price [€]
 <b>Adapter frame SW 01</b> for bucket modification	6	114526	<b>98,80</b>
 <b>Symlock adapter SW 01</b> for backhoe and front shovel application, with bucket safety clip	7	221538	<b>186,00</b>
 <b>Weld-on adapter SW 01</b> for hammers, shears etc. Base plate: 325x230x20mm	20	200968	<b>312,00</b>
 <b>Screwed adapter SW 01</b> for hammers, shears etc.	15	700502	<b>571,00</b>
 <b>Grab adapter SW 01</b> for hydraulic grabs, with cross bar	21		<b>930,00</b>



## Attachments for PC16/PC17/PC18/PC20

**MTL 1 SY Mini backhoe bucket premium****with Symlock adapter SY 01**

for backhoe and front shovel application

**premium quality:** cutting edge 110x12mm (400 HB), extended base and side edge out of 400 HB steel, Lehnhoff teeth 404F, with bucket safety clip

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
220	Lehnhoff	404F	2	0,023	30	LH221770	<b>688,00</b>
250	Lehnhoff	404F	3	0,026	35	LH221771	<b>727,00</b>
300	Lehnhoff	404F	3	0,030	38	LH221772	<b>745,00</b>
400	Lehnhoff	404F	3	0,040	41	LH221734	<b>811,00</b>
500	Lehnhoff	404F	4	0,050	46	LH221551	<b>829,00</b>
600	Lehnhoff	404F	4	0,060	52	LH221773	<b>875,00</b>

**MTL 1 S SY Mini backhoe bucket premium without teeth**

**with Symlock adapter SY 01** - for backhoe and front shovel application, with elongated bucket base,

**premium quality:** cutting edge 110x12mm (400HB), extended base with protected weld seam and side edges of 400 HB steel, with bucket safety clip

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
220	no teeth		-	0,025	29	LH261859	<b>653,00</b>
250	no teeth		-	0,029	31	LH261860	<b>690,00</b>
300	no teeth		-	0,033	34	LH261861	<b>705,00</b>
400	no teeth		-	0,044	40	LH261862	<b>769,00</b>
500	no teeth		-	0,055	46	LH261863	<b>786,00</b>
600	no teeth		-	0,066	51	LH261864	<b>829,00</b>



### MBL 1 SY Mini backhoe bucket basic

with Symlock adapter SY 01

for backhoe and front shovel application

with basic quality features: cutting edge 110x12mm (400 HB), base out of S355 steel, two-strap teeth GW12, with bucket safety clip



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
250	Lehnhoff	GW12	3	0,026	34	LH244207	<b>515,00</b>
300	Lehnhoff	GW12	3	0,030	39	LH244208	<b>527,00</b>
400	Lehnhoff	GW12	3	0,040	48	LH244210	<b>566,00</b>
500	Lehnhoff	GW12	4	0,050	53	LH244211	<b>604,00</b>
600	Lehnhoff	GW12	4	0,060	62	LH244213	<b>643,00</b>

### MBL 1 S SY Mini backhoe bucket basic without teeth

with Symlock adapter SY 01 - for backhoe and front shovel application, with elongated bucket base

Standard quality: cutting edge 110x12mm made of 400 HB steel, base made of S355 steel, with bucket safety clip



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
250	no teeth		-	0,029	33	LH261873	<b>459,00</b>
300	no teeth		-	0,033	36	LH261874	<b>471,00</b>
400	no teeth		-	0,044	43	LH261875	<b>505,00</b>
500	no teeth		-	0,055	49	LH261876	<b>538,00</b>
600	no teeth		-	0,066	55	LH261877	<b>574,00</b>

### MG 1 R Ditch bucket, rigid version

with Symlock adapter SY 01

for backhoe and front shovel application, cutting edge 150x16mm out of 500 HB steel and side edges out of 400 HB steel



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
850			-	0,073	72	LH269764	<b>1.149,00</b>
1000			-	0,086	82	LH270028	<b>1.196,00</b>
1200			-	0,106	95	LH270030	<b>1.265,00</b>





## Attachments for PC16/PC17/PC18/PC20

**MG 1 G Ditch bucket, rigid version**

for tilt application with straight side cutting edge, for high and low ladle application, blade 150x16mm and side blades made of 500 HB steel, lateral water drainage holes, with Symlock adapter SY 01

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
850			-	0,077	70	LH211798	<b>1.122,00</b>
1000			-	0,092	80	LH221545	<b>1.164,00</b>
1200			-	0,117	101	LH220503	<b>1.198,00</b>

**MG 1 RH Tilting ditch bucket**

with Lehmatic adapter SW 01

2 x 45° tilting range, 1 hydraulic cylinder, counter-balance valve, hydraulic connections on tilting head, cutting edge 150x16mm out of 500 HB steel and side edges out of 400 HB steel, lateral water drain bores

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
850			-	0,073	111	LH270017	<b>2.373,00</b>
1000			-	0,086	126	LH269222	<b>2.489,00</b>
1200			-	0,106	143	LH270018	<b>2.627,00</b>

**MSL 1 SY Sorting bucket with plasma base**

with Symlock adapter SY 01, blade 110x12mm (400 HB), plasma-cut base of 400 HB steel, hole/bar width 40mm, teeth 404 F.

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
600			4	0,060	58	LH280379	



### MRR 1 Clearing rake

With Symlock adapter SY 01, for clearing bushes, shrubs and undergrowth, collecting tree cuttings, loosening soil and sorting work in the recycling sector. 3 segments with wear protection made of HB450 steel, cutting edge (500HB) between the segments.

Tooth-radius [mm]	Width [mm]	Teeth	Weight [kg]	PN	Price [€]
500	500	3	150	LH282591	1.786,00



### MKL 1 SY

for cable construction - with cutting edge 200x20 (500 HB), water drainage holes in the side walls, Symlock adapter SY01

Width [mm]	Digging Depth [mm]	Teeth	Weight [kg]	PN	Price [€]
130	750	-	58	LH290871	1.100,00



## Attachments for PC24

**MS 03 Quickcoupler mechanical****for PC24**

Quickcoupler with mechanical locking, incl. socket wrench, optionally with 2t load hook

Type	Excavator	Option	Weight [kg]	PN	Price [€]
MS 03	PC24	-	30	LH280446	<b>1.334,00</b>
MS 03	PC24	Load hook 2t	32	LH278184	<b>1.547,00</b>

**HS 03 DL Quickcoupler hydraulic****for PC24**

Quickcoupler with hydraulic locking, optionally with 2t load hook.

**With Safety locking mechanism Double Lock**

**NEW: With exchangeable HD wear protection on the claws**

Type	Excavator	Option	Weight [kg]	PN	Price [€]
HS 03 DL	PC24	-	30	LH280262	<b>2.026,00</b>
HS 03 DL	PC24	Load hook 2t	32	LH276996	<b>2.239,00</b>

**HS 03V DL Quickcoupler fully hydraulic****for PC24**

Fully hydraulic Quickcoupler with 2 valves KV1, 3 valves KV0.8, one load hooks as standard, valve block's internal depressurization circuit (BiD)

**NEW: Double-Lock version, with exchangeable HD wear protection on the claws**

Type	Excavator	Option	Weight [kg]	PN	Price [€]
HS 03V LSC	PC24	1x Hook 3t	50	LH286722	<b>6.535,00</b>



### MS 03 - Tilt Quickcoupler Tilt

#### for PC24

Mechanical quickcoupler with Powertilt motor (PT), with direct suspension. Including 2t load hook.

Excl. optional switch valve, excl. installation on excavator.



Type	Excavator	Option	Tilt-Angle	Weight [kg]	PN	Price [€]
MS 03 - PT 030	PC24	Load hook 2t	2 x 90°	62-68	LH280447	<b>6.875,00</b>
Tilt switch valve		12 V			LH205585	<b>976,00</b>

### HS 03 DL - Tilt Quickcoupler Tilt


#### for PC24

Hydraulic quickcoupler with Powertilt motor (PT), with direct suspension. Including 2t load hook.

Excl. optional switch valve, excl. installation on excavator.

**With safety locking mechanism Double Lock**

**NEW: With exchangeable HD wear protection on the claws.**



Type	Excavator	Option	Tilt-Angle	Weight [kg]	PN	Price [€]
HS 03 DL - PT 030	PC24	Load hook 2t	2 x 90°	66-72	LH279743	<b>7.653,00</b>
Tilt switch valve		12 V			LH205585	<b>976,00</b>

### HS 03V DL - Tilt Quickcoupler Tilt

#### for PC24

Fully hydraulic Quickcoupler with tilt motor, with Powertilt (PT). With direct suspension on excavator side. 1 load hook as standard. Incl. Lehmatic Safety Control (LSC), excl. optional switch valve, excl. installation on excavator.

**NEW: Double-Lock version, with exchangeable HD wear protection on the claws**








Type	Excavator	Option	Weight [kg]	PN	Price [€]
HS 03V DL - PT 030	PC24	1x Hook 3t	90-96	LH286723	<b>13.436,00</b>
Tilt switch valve		12 V		LH205585	<b>976,00</b>



Attachments for PC24






**SW 03 Adapter**

	Description	Weight [kg]	PN	Price [€]
	<b>Adapter frame SW 03</b> for bucket modification	12	104091	<b>144,00</b>
	<b>Symlock adapter SW 03</b> for backhoe and front shovel application, with bucket safety clip	14	219035	<b>234,00</b>
	<b>Weld-on adapter SW 03</b> for hammers, shears etc. Base plate: 400x250x20mm	30	106072	<b>486,00</b>
	<b>Screwed adapter SW 03</b> for hammers, shears etc. please specify exact type!	30	700509	<b>667,00</b>
	<b>Grab adapter SW 03</b> for suspended grabs, with cross bar please specify exact type!	27	700512	<b>1.154,00</b>

**SW 03V DL Adapter**

Screw adapter with valve configuration for various attachments.

**NEW: For Double-Lock-Version HS03V DL!**

	Description	Weight [kg]	PN	Price [€]
	<b>Screwed adapter SW 03V</b> for hydraulic hammers, valves: 2x KV1, plus installation and hoses	ca. 40		<b>1.735,00</b>
	<b>Screwed adapter SW 03V</b> for cutting units/compactors, valves: 2x KV1, 1x KV0.8, plus installation and hoses	ca. 40		<b>1.904,00</b>
	<b>Screwed adapter SW 03V</b> for sorting grabs/shears, valves: 2x KV1, 2x KV0.8, plus installation and hoses	ca. 40		<b>2.077,00</b>
	<b>Screwed adapter SW 03V</b> for rotating compactors, valves: 2x KV1, 3x KV0.8, plus installation and hoses	ca. 40		<b>2.248,00</b>
	<b>Grab adapter SW 03V</b> for suspended grabs, with cross bar, valves: 4x KV1, plus installation and hoses	ca. 65		<b>2.596,00</b>



### MTL 2 SY Mini backhoe bucket premium

with Symlock adapter SY 03

for backhoe and front shovel application

**premium quality:** cutting edge 110x12mm (400 HB), extended base and side edge out of 400 HB steel, Lehnhoff teeth 404F, with bucket safety clip.

Surcharge for HS 03V dirt protection: 20,00 EUR



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
300	Lehnhoff	404F	3	0,040	50	LH221774	<b>780,00</b>
400	Lehnhoff	404F	3	0,060	60	LH221542	<b>846,00</b>
500	Lehnhoff	404F	4	0,080	65	LH221775	<b>870,00</b>
600	Lehnhoff	404F	4	0,097	73	LH221776	<b>908,00</b>
700	Lehnhoff	404F	5	0,117	80	LH221777	<b>972,00</b>

### MTL 2 S SY Mini backhoe bucket premium without teeth

with Symlock adapter SY 03 - for backhoe and front shovel application, with elongated bucket base,

**premium quality:** cutting edge 110x12mm (400HB), extended base with protected weld seam and side edges of 400 HB steel, with bucket safety clip.

Surcharge for HS 03V dirt protection: 20,00 EUR



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
300	no teeth		-	0,044	48	LH261888	<b>739,00</b>
400	no teeth		-	0,066	56	LH261889	<b>801,00</b>
500	no teeth		-	0,088	63	LH261890	<b>825,00</b>
600	no teeth		-	0,107	70	LH261891	<b>860,00</b>

### MBL 2 SY Mini backhoe bucket basic

with Symlock adapter SY 03

for backhoe and front shovel application

**with basic quality features:** cutting edge 110x12mm out of 400 HB steel, base out of S355 steel, two-strap teeth GW12, with bucket safety clip

Surcharge for HS 03V dirt protection: 20,00 EUR



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
300	Lehnhoff	GW12	3	0,040	49	LH244214	<b>626,00</b>
400	Lehnhoff	GW12	3	0,060	57	LH244216	<b>672,00</b>
500	Lehnhoff	GW12	4	0,080	65	LH244217	<b>729,00</b>
600	Lehnhoff	GW12	4	0,097	72	LH244218	<b>773,00</b>
700	Lehnhoff	GW12	5	0,120	85	LH244220	<b>910,00</b>



## Attachments for PC24

**MBL 2 S SY Mini backhoe bucket basic**

with Symlock adapter SY 03 - for backhoe and front shovel application, with elongated bucket base

Standard quality: cutting edge 110x12mm made of 400 HB steel, base made of S355 steel, with bucket safety clip  
Surcharge for HS 03V dirt protection: 20,00 EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
300	no teeth		-	0,044	50	LH261893	<b>558,00</b>
400	no teeth		-	0,066	57	LH261894	<b>598,00</b>
500	no teeth		-	0,088	65	LH261895	<b>649,00</b>
600	no teeth		-	0,107	72	LH261896	<b>691,00</b>

**MG 2 R Ditch bucket, rigid version**

with Symlock adapter SY 03

rigid version, for backhoe and front shovel application, cutting edge 150x16mm out of 500 HB steel and side edges out of 400 HB steel  
Surcharge for HS 03V dirtprotection: 20,00 EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1000			-	0,086	85	LH270029	<b>1.289,00</b>
1200			-	0,106	99	LH270032	<b>1.311,00</b>

**MG 2G Ditch bucket, rigid version**

for tilt application with straight side cutting edge, for high and low ladle application, blade 150x16mm and side blades made of 500 HB steel, lateral water drainage holes, with Symlock adapter SY 03  
Surcharge for HS 03V dirtprotection: 20,00 EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
850			-	0,077	75	LH211804	<b>1.169,00</b>
1000			-	0,092	87	LH222003	<b>1.210,00</b>
1200			-	0,117	103	LH221736	<b>1.244,00</b>



### MG 2 RH Tilting ditch bucket

#### with Lehmatic adapter SW 03

2 x 45° tilting range, 1 hydraulic cylinder, counter-balance valve, hydraulic connections on tilting head, cutting edge 150x16mm out of 500 HB steel and side edges out of 400 HB steel, lateral water drain bores

Surcharge for HS 03V adapter: 1.143,- EUR.



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1000			-	0,092	137	LH270019	<b>2.878,00</b>
1200			-	0,117	154	LH270020	<b>2.954,00</b>

### MSL 2 SY Sorting bucket with plasma base

with Symlock adapter SY 03, cutting edge 110x12mm (400 HB), plasma-cut base made of 400 HB steel, hole/bar width 60mm, teeth 404 F.



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
600		404F	4	0,100	65	LH277868	<b>995,00</b>

### MSL 2 SY Sorting bucket round bars

#### with Symlock adapter SY 03,

cutting edge 110x12mm (500 HB), Base made of round bars D15, hole width 40mm, teeth 404F.



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
600		404F	4	0,100	70	292793	





Attachments for PC24



**MKL 6 SY**

for cable construction - with cutting edge 200x20 (500 HB), water drainage holes in the side walls, Symlock adapter SY03

Width [mm]	Digging Depth [mm]	Teeth	Weight [kg]	PN	Price [€]
130	750	-	66	LH290872	1.243,00



**MRR 6 Clearing rake**

With Symlock adapter SY 03, for clearing bushes, shrubs and undergrowth, collecting prunings, soil loosening as well as sorting work in the recycling sector. 4 segments with wear protection made of HB450 steel, cutting edge (500HB) between the segments.

Tooth-radius [mm]	Width [mm]	Teeth	Weight [kg]	PN	Price [€]
700	770	4	175	LH282590	2.120,00



**MRZ 3 bionic Ripper tooth**

for demolition and rock use - with Lehmatic adapter SW 03

Option	Tooth point	Angle	Tooth-radius [mm]	Weight [kg]	PN	Price [€]
SW 03	6262	35	550	60	LH225517	1.243,00



### MS 03 Quickcoupler mechanical

#### for PC26-PC35

Quickcoupler with mechanical locking, incl. socket wrench, optionally with 2t/3t load hook



Type	Excavator	Option	Weight [kg]	PN	Price [€]
MS 03	PC26	-	30	LH104646	<b>1.334,00</b>
MS 03	PC30-PC35	-	32	LH104647	<b>1.334,00</b>
MS 03	PC26	Load hook 2t	32	LH201106	<b>1.547,00</b>
MS 03	PC30-PC35	Load hook 3t	32	LH201799	<b>1.559,00</b>

### HS 03 DL Quickcoupler hydraulic

#### for PC26-PC35

Quickcoupler with hydraulic locking, optionally with 2t/3t load hook.

**With safety locking mechanism Double Lock**

**NEW: With exchangeable HD wear protection on the claws**



Type	Excavator	Option	Weight [kg]	PN	Price [€]
HS 03 DL	PC26	-	30	LH280192	<b>2.026,00</b>
HS 03 DL	PC30-PC35	-	32	LH280195	<b>2.026,00</b>
HS 03 DL	PC26	Load hook 2t	32	LH276486	<b>2.239,00</b>
HS 03 DL	PC30-PC35	Load hook 3t	32	LH276628	<b>2.251,00</b>
Install. kit HS01-03 12V		QC valve etc.		LH204735	<b>558,00</b>

### HS 03V DL Quickcoupler fully hydraulic

#### for PC26-PC35

Fully hydraulic Quickcoupler with 2 valves KV1, 3 valves KV0.8, one load hook as standard, valve block's internal depressurizing circuit (BiD)

**NEW: Double-Lock version, with exchangeable HD wear protection on the claws**

plus hydr. installation kit and installation.



Type	Excavator	Option	Weight [kg]	PN	Price [€]
HS 03V DL	PC26	1x Hook 3t	50	LH295247	<b>6.535,00</b>
HS 03V DL	PC30-PC35	1x Hook 3t	50	LH295249	<b>6.535,00</b>
Install. kit hydr. HS-V 12V		incl. QC valve		LH279829	<b>967,00</b>



## Attachments for PC26/PC30/PC33E/PC35

**MS 03 - Tilt Quickcoupler Tilt****for PC26-PC35**

Mechanical quickcoupler with Powertilt motor (PT), with direct suspension. Including 2t/3t load hook.  
Excl. optional switch valve, excl. installation on excavator.

Type	Excavator	Option	Tilt-Angle	Weight [kg]	PN	Price [€]
MS 03 - PT 030	PC26	Load hook 2t	2 x 90°	62-68	LH256896	<b>6.875,00</b>
MS 03 - PT 050	PC30-PC35	Load hook 3t	2 x 90°	80-90	LH256917	<b>7.285,00</b>
Tilt switch valve		12 V			LH205585	<b>976,00</b>

**HS 03 DL - Tilt Quickcoupler Tilt****for PC26-PC35**


Hydraulic quickcoupler with Powertilt motor (PT), with direct suspension. Including 2t/3t load hook.

Excl. optional switch valve, excl. installation on excavator.

**With safety locking mechanism Double Lock**

**NEW: With exchangeable HD wear protection on the claws.**

Type	Excavator	Option	Tilt-Angle	Weight [kg]	PN	Price [€]
HS 03 DL - PT 030	PC26	Load hook 2t	2 x 90°	66-72	LH276429	<b>7.653,00</b>
HS 03 DL - PT 050	PC30-PC35	Load hook 3t	2 x 90°	84-90	LH276490	<b>8.150,00</b>
Install. kit HS01-03 12V		QC valve etc.			LH204735	<b>558,00</b>
Tilt switch valve		12 V			LH205585	<b>976,00</b>

**HS 03V DL - Tilt Quickcoupler Tilt****for PC26-PC35**






Fully hydraulic Quickcoupler with tilt motor, with Powertilt (PT). With direct suspension on excavator side. 1 load hook as standard, excl. optional switch valve and installation on excavator.

**NEW: Double-Lock version, with exchangeable HD wear protection on the claws**

Type	Excavator	Option	Weight [kg]	PN	Price [€]
HS 03V DL - PT 030	PC26	1x Hook 3t	90-96	LH295248	<b>13.462,00</b>
HS 03V DL - PT 050	PC30-PC35	1x Hook 3t	105-115	LH295250	<b>13.896,00</b>
Tilt switch valve		12 V		LH205585	<b>976,00</b>
Install. kit hydr. HS-V 12V		incl. QC valve		LH279829	<b>967,00</b>













### SW 03 Adapter

Description	Weight [kg]	PN	Price [€]
 <b>Adapter frame SW 03</b> for bucket modification	12	104091	<b>144,00</b>
 <b>Symlock adapter SW 03</b> for backhoe and front shovel application, with bucket safety clip	14	219035	<b>234,00</b>
 <b>Weld-on adapter SW 03</b> for hammers, shears etc. Base plate: 400x250x20mm	30	106072	<b>486,00</b>
 <b>Screwed adapter SW 03</b> for hammers, shears etc. please specify exact type!	30	700509	<b>667,00</b>
 <b>Grab adapter SW 03</b> for suspended grabs, with cross bar please specify exact type!	27	700512	<b>1.154,00</b>

### SW 03V DL Adapter

Screw adapter with valve configuration for various attachments.

**NEW: For Double-Lock-Version HS03V DL!**

Description	Weight [kg]	PN	Price [€]
  <b>Screwed adapter SW 03V</b> for hydraulic hammers, valves: 2x KV1, plus installation and hoses	ca. 40		<b>1.735,00</b>
  <b>Screwed adapter SW 03V</b> for cutting units/compactors, valves: 2x KV1, 1x KV0.8, plus installation and hoses	ca. 40		<b>1.904,00</b>
  <b>Screwed adapter SW 03V</b> for sorting grabs/shears, valves: 2x KV1, 2x KV0.8, plus installation and hoses	ca. 40		<b>2.077,00</b>
  <b>Screwed adapter SW 03V</b> for rotating compactors, valves: 2x KV1, 3x KV0.8, plus installation and hoses	ca. 40		<b>2.248,00</b>
  <b>Grab adapter SW 03V</b> for suspended grabs, with cross bar, valves: 4x KV1, plus installation and hoses	ca. 65		<b>2.596,00</b>



## Attachments for PC26/PC30/PC33E/PC35

**MTL 3 SY Mini backhoe bucket premium****with Symlock adapter SY 03**

for backhoe and front shovel application

**premium quality:** cutting edge 150x16mm (500 HB), extended base and side edge out of 400 HB steel, teeth 400F , with bucket safety clip.

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
300	Kprime	P004SC	3	0,056	68	LH281772	<b>870,00</b>
400	Kprime	P004SC	3	0,075	78	LH281773	<b>908,00</b>
500	Kprime	P004SC	4	0,100	90	LH281774	<b>998,00</b>
600	Kprime	P004SC	4	0,127	97	LH281775	<b>1.062,00</b>
800	Kprime	P004SC	5	0,180	116	LH281776	<b>1.217,00</b>

**MTL 3 S SY Mini backhoe bucket premium without teeth****with Symlock adapter SY 03** - for backhoe and front shovel application, with elongated bucket base,**premium quality:** cutting edge 150x16mm (500HB), extended base with protected weld seam and side edges of 400 HB steel, with bucket safety clip.

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
300	no teeth		-	0,062	63	LH261919	<b>825,00</b>
400	no teeth		-	0,083	72	LH261920	<b>860,00</b>
500	no teeth		-	0,110	81	LH261921	<b>945,00</b>
600	no teeth		-	0,140	91	LH261922	<b>1.007,00</b>
800	no teeth		-	0,198	109	LH261924	<b>1.187,00</b>

**MBL 3 SY Mini backhoe bucket basic****with Symlock adapter SY 03**

for backhoe and front shovel application

**with basic quality features:** cutting edge 150x16mm out of 400 HB steel, base out of S355 steel, two-strap teeth GW16, with bucket safety clip

Surcharge for HS 03V protection: 20,00 EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
300	Lehnhoff	GW16	3	0,060	74	LH244223	<b>748,00</b>
400	Lehnhoff	GW16	3	0,070	84	LH244224	<b>812,00</b>
500	Lehnhoff	GW16	4	0,100	95	LH244225	<b>916,00</b>
600	Lehnhoff	GW16	4	0,130	108	LH244226	<b>972,00</b>
800	Lehnhoff	GW16	5	0,180	129	LH244228	<b>1.121,00</b>



### MBL 3 S SY Mini backhoe bucket basic without teeth

with Symlock adapter SY 03 - for backhoe and front shovel application, with elongated bucket base

Standard quality: cutting edge 150x16mm made of 400 HB steel, base made of S355 steel, with bucket safety clip  
Surcharge for HS 03V dirt protection: 20,00 EUR



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
300	no teeth		-	0,062	71	LH261925	<b>668,00</b>
400	no teeth		-	0,083	82	LH261926	<b>725,00</b>
500	no teeth		-	0,110	94	LH261927	<b>816,00</b>
600	no teeth		-	0,140	106	LH261928	<b>868,00</b>
800	no teeth		-	0,198	130	LH261930	<b>999,00</b>

### MG 4 R Ditch bucket, rigid version

with Symlock adapter SY 03

for backhoe and front shovel application, cutting edge 150x16mm out of 500 HB steel and side edges out of 400 HB steel. Surcharge for HS 03V dirt protection: 20,00 EUR



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1000			-	0,185	113	LH270033	<b>1.361,00</b>
1200			-	0,230	130	LH270035	<b>1.426,00</b>
1400			-	0,270	149	LH270036	<b>1.490,00</b>
1500			-	0,290	155	LH270037	<b>1.542,00</b>

### MG 4 G Ditch bucket, rigid version

for tilt application with straight side cutting edge, for backhoe and front shovel application, cutting edge 150x16mm and side cutting edge out of 500 HB steel, lateral water drain bores, with Symlock adapter SY 03.

Surcharge for HS 03V dirt protection: 20,00 EUR



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1000			-	0,150	106	LH211810	<b>1.223,00</b>
1200			-	0,180	143	LH221506	<b>1.395,00</b>
1400			-	0,208	158	LH221815	<b>1.454,00</b>
1500			-	0,220	169	LH214845	<b>1.500,00</b>



## Attachments for PC26/PC30/PC33E/PC35

**MG 4 RH Tilting ditch bucket****with Lehmatic adapter SW 03**

2 x 45° tilting range, 1 hydraulic cylinder, counter-balance valve, hydraulic connections on tilting head, cutting edge 150x16mm out of 500 HB steel and side edges out of 400 HB steel, lateral water drain bores.

Surcharge for HS 03V adapter: 1.143,- EUR.

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1000			-	0,185	172	LH270021	<b>3.074,00</b>
1200			-	0,230	192	LH269219	<b>3.174,00</b>
1400			-	0,270	214	LH267962	<b>3.359,00</b>
1500			-	0,290	222	LH270022	<b>3.491,00</b>

**MSL 3 Sorting bucket with plasma base**

**with Lehmatic adapter SW 03**, cutting edge 150x16mm (500 HB), plasma-cut base made of 400 HB steel, hole/bar width 50mm, teeth Kprime P004SC.

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
600	Kprime	P004SC	4	0,127	90	LH282486	<b>1.167,00</b>

**MSL 3 SY Sorting bucket round bars**

**with Symlock adapter SY 03**, cutting edge 150x16mm (500 HB), Base made of round bars D20, hole width 40mm, teeth Kprime P004SC.

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
600	Kprime	P004SC	4	0,127	90		<b>1.459,00</b>



### MKL 6 SY

for cable construction - with cutting edge 200x20 (500 HB), water drainage holes in the side walls, Symlock adapter SY03

Width [mm]	Digging Depth [mm]	Teeth	Weight [kg]	PN	Price [€]
130	750	-	66	LH290872	1.243,00



### MRR 6 Clearing rake

With Symlock adapter SY 03, for clearing bushes, shrubs and undergrowth, collecting prunings, soil loosening as well as sorting work in the recycling sector. 4 segments with wear protection made of HB450 steel, cutting edge (500HB) between the segments.

Tooth-radius [mm]	Width [mm]	Teeth	Weight [kg]	PN	Price [€]
700	770	4	175	LH282590	2.120,00



### MRZ 3 bionic Ripper tooth

for demolition and rock use - with Lehmatic adapter SW 03

Option	Tooth point	Angle	Tooth-radius [mm]	Weight [kg]	PN	Price [€]
SW 03	6262	35	550	60	LH225517	1.243,00



### MSG 4 Demolition and sorting grab

compact design, grab shells out of Hardox 400, interchangeable cutting edges out of Hardox 500, incl. counter-balance valve, rotating angle 360° endless, incl. screwed Lehmatic adapter SW 03. Grab shells closed or with rectangular bars on demand. Surcharge for HS 03V adapter: 1532,- EUR

Opening clearance [mm]	Width [mm]	Capacity SAE [m³]	Grab force [kN]	Weight [kg]	PN	Price [€]
1137	500	0,100	12	240	LH264708	12.138,00





## Attachments for PC45

**MS 03 Quickcoupler mechanical****for PC45-PC58**

Quickcoupler with mechanical locking, incl. socket wrench, optionally with 3t load hook

Type	Excavator	Option	Weight [kg]	PN	Price [€]
MS 03	PC45-PC58	-	32	LH204227	<b>1.334,00</b>
MS 03	PC45-PC58	Load hook 3t	34	LH204556	<b>1.559,00</b>

**HS 03H DL Quickcoupler hydraulic****for PC45-PC58**

Quickcoupler with hydraulic locking, optionally with 3t load hook.

**With safety locking mechanism Double Lock**

**NEW: With exchangeable HD wear protection on the claws.**



Type	Excavator	Option	Weight [kg]	PN	Price [€]
HS 03 H DL	PC45-PC58	-	32	LH275745	<b>2.539,00</b>
HS 03 H DL	PC45-PC58	Load hook 3t	34	LH276574	<b>2.764,00</b>

**HS 03V DL Quickcoupler fully hydraulic****For PC45-PC58**

Fully hydraulic Quickcoupler with 2 valves KV1, 3 valves KV0.8, one load hook as standard, valve block's internal depressurizing circuit (BiD), excl. hydr. installation kit and installation.

**NEW: Double-Lock version, with exchangeable HD wear protection on the claws**



Type	Excavator	Option	Weight [kg]	PN	Price [€]
HS 03V DL	PC45-PC58	1x Hook 3t	50	LH286845	<b>6.535,00</b>



### MS 03 - Tilt Quickcoupler Tilt

#### for PC45

Mechanical quickcoupler with Powertilt motor (PT), with direct suspension. Including 3t load hook.

Excl. optional switch valve and installation on excavator.



Type	Excavator	Option	Tilt-Angle	Weight [kg]	PN	Price [€]
MS 03 - PT 050	PC45	Load hook 3t	2 x 90°	80-90	LH256933	<b>7.285,00</b>
Tilt switch valve		12 V			LH205585	<b>976,00</b>

### HS 03H DL - Tilt Quickcoupler Tilt

#### für PC45

Hydraulic quickcoupler with Powertilt motor (PT), with direct suspension. Including 3t load hook. Excl. optional switch valve, excl. installation on excavator.

**With safety locking mechanism Double Lock**

**NEW: With exchangeable HD wear protection on the claws.**



Type	Excavator	Option	Tilt-Angle	Weight [kg]	PN	Price [€]
HS 03H DL - PT 050	PC45	Load hook 3t	2 x 90°	80-90	LH277874	<b>8.691,00</b>
Tilt switch valve		12 V			LH205585	<b>976,00</b>
Install. kit HS01-03 12V		QC valve etc.			LH204735	<b>558,00</b>

### HS 03V DL - Tilt Quickcoupler Tilt

#### for PC45

Fully hydraulic Quickcoupler with tilt motor, with Powertilt (PT). With direct suspension on excavator side. One load hook as standard, excl. optional switch valve, excl. installation on excavator.

**NEW: Double-Lock version, with exchangeable HD wear protection on the claws**








Type	Excavator	Option	Weight [kg]	PN	Price [€]
HS 03V DL - PT 050	PC45	1x Hook 3t	105-115	LH286846	<b>13.869,00</b>
Tilt switch valve		12 V		LH205585	<b>976,00</b>








Attachments for PC45

**SW 03 Adapter**

	Description	Weight [kg]	PN	Price [€]
	<b>Adapter frame SW 03</b> for bucket modification	12	104091	<b>144,00</b>
	<b>Symlock adapter SW 03</b> for backhoe and front shovel application, with bucket safety clip	14	219035	<b>234,00</b>
	<b>Weld-on adapter SW 03</b> for hammers, shears etc. Base plate: 400x250x20mm	30	106072	<b>486,00</b>
	<b>Screwed adapter SW 03</b> for hammers, shears etc. please specify exact type!	30	700509	<b>667,00</b>
	<b>Grab adapter SW 03</b> for suspended grabs, with cross bar please specify exact type!	27	700512	<b>1.154,00</b>

**SW 03V DL Adapter**

Screw adapter with valve configuration for various attachments.  
**NEW: For Double-Lock-Version HS03V DL!**

	Description	Weight [kg]	PN	Price [€]
	<b>Screwed adapter SW 03V</b> for hydraulic hammers, valves: 2x KV1, plus installation and hoses	ca. 40		<b>1.735,00</b>
	<b>Screwed adapter SW 03V</b> for cutting units/compactors, valves: 2x KV1, 1x KV0.8, plus installation and hoses	ca. 40		<b>1.904,00</b>
	<b>Screwed adapter SW 03V</b> for sorting grabs/shears, valves: 2x KV1, 2x KV0.8, plus installation and hoses	ca. 40		<b>2.077,00</b>
	<b>Screwed adapter SW 03V</b> for rotating compactors, valves: 2x KV1, 3x KV0.8, plus installation and hoses	ca. 40		<b>2.248,00</b>
	<b>Grab adapter SW 03V</b> for suspended grabs, with cross bar, valves: 4x KV1, plus installation and hoses	ca. 65		<b>2.596,00</b>



### MTL 4 SY Mini backhoe bucket premium

#### with Symlock adapter SY 03

backhoe and front shovel application

**premium quality:** cutting edge 150x16mm (500 HB), extended base and side edge out of 400 HB steel, teeth Kprime P004SC, with bucket safety clip.

Surcharge for HS 03V dirt protection: 20,00 EUR



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
300	Kprime	P004SC	3	0,066	74	LH281783	<b>921,00</b>
400	Kprime	P004SC	3	0,096	80	LH281784	<b>967,00</b>
500	Kprime	P004SC	4	0,130	92	LH281785	<b>1.077,00</b>
600	Kprime	P004SC	4	0,162	100	LH281786	<b>1.128,00</b>
800	Kprime	P004SC	5	0,230	124	LH281787	<b>1.322,00</b>

### MTL 4 S SY Mini backhoe bucket premium without teeth

with Symlock adapter SY 03 - for backhoe and front shovel application, with elongated bucket base,

**premium quality:** cutting edge 150x16mm (500HB), extended base with protected weld seam and side edges of 400 HB steel, with bucket safety clip.

Surcharge for HS 03V dirt protection: 20,00 EUR



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
300	no teeth		-	0,073	73	LH261931	<b>874,00</b>
400	no teeth		-	0,106	84	LH261932	<b>915,00</b>
500	no teeth		-	0,143	95	LH261933	<b>1.021,00</b>
600	no teeth		-	0,178	105	LH261934	<b>1.069,00</b>
800	no teeth		-	0,253	127	LH261936	<b>1.251,00</b>

### MBL 4 SY Mini backhoe bucket basic

#### with Symlock adapter SY 03

backhoe and front shovel application

**with basic quality features:** cutting edge 150x16mm out of 400 HB steel, base out of S355 steel, two-strap teeth GW16, with bucket safety clip

Surcharge for HS 03V protection: 20,00 EUR



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
300	Lehnhoff	GW16	3	0,060	80	LH244229	<b>795,00</b>
400	Lehnhoff	GW16	3	0,100	90	LH244230	<b>865,00</b>
500	Lehnhoff	GW16	4	0,130	104	LH244231	<b>935,00</b>
600	Lehnhoff	GW16	4	0,160	114	LH244232	<b>1.005,00</b>
800	Lehnhoff	GW16	5	0,230	139	LH244234	<b>1.167,00</b>



Attachments for PC45



**MBL 4 S SY Mini backhoe bucket basic without teeth**

with Symlock adapter SY 03 - for backhoe and front shovel application, with elongated bucket base.

with basic quality features: cutting edge 150x16mm out of 400 HB steel, base out of S355 steel, with bucket safety clip

Surcharge for HS 03V dirt protection: 20,00 EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
300	no teeth		-	0,073	78	LH261945	<b>707,00</b>
400	no teeth		-	0,106	91	LH261946	<b>770,00</b>
500	no teeth		-	0,143	104	LH261947	<b>834,00</b>
600	no teeth		-	0,178	117	LH261948	<b>896,00</b>
800	no teeth		-	0,253	143	LH261950	<b>1.040,00</b>



**MG 4 R Ditch bucket, rigid version**

with Symlock adapter SY 03

for backhoe and front shovel application, cutting edge 150x16mm out of 500 HB steel and side edges out of 400 HB steel.

Surcharge for HS 03V dirt protection: 20,00 EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1000			-	0,185	113	LH270033	<b>1.361,00</b>
1200			-	0,230	130	LH270035	<b>1.426,00</b>
1400			-	0,270	149	LH270036	<b>1.490,00</b>
1500			-	0,290	155	LH270037	<b>1.542,00</b>



**MG 4 G Ditch bucket, rigid version**

for tilt application with straight side cutting edge, for backhoe and front shovel application, cutting edge 150x16mm and side cutting edge out of 500 HB steel, lateral water drain bores, with Symlock adapter SY 03.

Surcharge for HS 03V dirt protection: 20,00 EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1000			-	0,150	106	LH211810	<b>1.223,00</b>
1200			-	0,180	143	LH221506	<b>1.395,00</b>
1400			-	0,208	158	LH221815	<b>1.454,00</b>
1500			-	0,220	169	LH214845	<b>1.500,00</b>



### MG 4 RH Tilting ditch bucket

with Lehmatic adapter SW 03

2 x 45° tilting range, 1 hydraulic cylinder, counter-balance valve, hydraulic connections on tilting head, cutting edge 150x16mm out of 500 HB steel and side edges out of 400 HB steel, lateral water drain bores.

Surcharge for HS 03V adapter: 1.143,- EUR.



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1000			-	0,185	172	LH270021	<b>3.074,00</b>
1200			-	0,230	192	LH269219	<b>3.174,00</b>
1400			-	0,270	214	LH267962	<b>3.359,00</b>
1500			-	0,290	222	LH270022	<b>3.491,00</b>

### MSL 4 Sorting bucket with plasma base

with Lehmatic adapter SW 03, cutting edge 150x16mm (500 HB), plasma-cutted bottom made of 400 HB steel, hole/bar width 50mm, teeth Kprime P004SC.



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
600	Kprime	P004SC	4	0,162	100	LH282487	<b>1.229,00</b>
800	Kprime	P004SC	5	0,230	120	LH282488	<b>1.394,00</b>

### MSL 4 SY Sorting bucket round bars

with Symlock adapter SY 03,

cutting edge 150x16mm (500 HB), Base made of round bars D20, hole width 50mm, teeth Kprime P004SC.



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
600		P004SC	4	0,160	132		<b>1.561,00</b>
800		P004SC	5	0,230	132		<b>1.742,00</b>



Attachments for PC45



**MKL 6 SY**

for cable construction - with cutting edge 200x20 (500 HB), water drainage holes in the side walls, Symlock adapter SY03

Width [mm]	Digging Depth [mm]	Teeth	Weight [kg]	PN	Price [€]
130	750	-	66	LH290872	1.243,00



**MRR 6 Clearing rake**

With Symlock adapter SY 03, for clearing bushes, shrubs and undergrowth, collecting prunings, soil loosening as well as sorting work in the recycling sector. 4 segments with wear protection made of HB450 steel, cutting edge (500HB) between the segments.

Tooth-radius [mm]	Width [mm]	Teeth	Weight [kg]	PN	Price [€]
700	770	4	175	LH282590	2.120,00



**MRZ 6 bionic Ripper tooth**

for demolition and rock use - with Lehmatic adapter SW 03

Option	Tooth point	Angle	Tooth-radius [mm]	Weight [kg]	PN	Price [€]
SW 03	6262	35	650	63	LH225506	1.412,00



**MSG 4 Demolition and sorting grab**

compact design, grab shells out of Hardox 400, interchangeable cutting edges out of Hardox 500, incl. counter-balance valve, rotating angle 360° endless, incl. screwed Lehmatic adapter SW 03. Grab shells closed or with rectangular bars on demand. Surcharge for HS 03V adapter: 1532,- EUR

Opening clearance [mm]	Width [mm]	Capacity SAE [m³]	Grab force [kN]	Weight [kg]	PN	Price [€]
1137	500	0,100	12	240	LH264708	12.138,00



### MS 03 Quickcoupler mechanical

#### for PC45-PC58

Quickcoupler with mechanical locking, incl. socket wrench, optionally with 3t load hook



Type	Excavator	Option	Weight [kg]	PN	Price [€]
MS 03	PC45-PC58	-	32	LH204227	<b>1.334,00</b>
MS 03	PC45-PC58	Load hook 3t	34	LH204556	<b>1.559,00</b>

### HS 03H DL Quickcoupler hydraulic

#### for PC45-PC58

Quickcoupler with hydraulic locking, optionally with 3t load hook.

**With safety locking mechanism Double Lock**

**NEW: With exchangeable HD wear protection on the claws.**



Type	Excavator	Option	Weight [kg]	PN	Price [€]
HS 03 H DL	PC45-PC58	-	32	LH275745	<b>2.539,00</b>
HS 03 H DL	PC45-PC58	Load hook 3t	34	LH276574	<b>2.764,00</b>

### HS 03V DL Quickcoupler fully hydraulic

#### For PC45-PC58

Fully hydraulic Quickcoupler with 2 valves KV1, 3 valves KV0.8, one load hook as standard, valve block's internal depressurizing circuit (BiD), excl. hydr. installation kit and installation.

**NEW: Double-Lock version, with exchangeable HD wear protection on the claws**



Type	Excavator	Option	Weight [kg]	PN	Price [€]
HS 03V DL	PC45-PC58	1x Hook 3t	50	LH286845	<b>6.535,00</b>





## Attachments for PC55/PC58

**MS 03 - Tilt Quickcoupler Tilt****for PC55/PC58**

Mechanical quickcoupler with Powertilt motor (PT), with direct suspension. Including 3t load hook.


Excl. optional switch valve, excl. installation on excavator.

Type	Excavator	Option	Tilt-Angle	Weight [kg]	PN	Price [€]
MS 03 - PT 070	PC55/PC58	Load hook 3t	2 x 90°	120-140	LH256948	<b>9.483,00</b>
Tilt switch valve		12 V			LH205585	<b>976,00</b>

**HS 03H DL - Tilt Quickcoupler Tilt****for PC55/PC58**

Hydraulic quickcoupler with Powertilt motor (PT), with direct suspension. Including 3t load hook. Excl. optional switch valve, excl. installation on excavator. **With safety locking mechanism Double Lock**

Type	Excavator	Option	Tilt-Angle	Weight [kg]	PN	Price [€]
HS 03H DL - PT 070	PC55/PC58	Load hook 3t	2 x 90°	115-125	LH276611	<b>10.594,00</b>
Tilt switch valve		12 V			LH205585	<b>976,00</b>






**HS 03V DL - Tilt Quickcoupler Tilt****for PC55/PC58**

Fully hydraulic Quickcoupler with tilt motor, with Powertilt (PT). With direct suspension on excavator side. 1 load hook as standard, excl. optional switch valve, excl. installation on excavator.

**NEW: Double-Lock version, with exchangeable HD wear protection on the claws**

Type	Excavator	Option	Weight [kg]	PN	Price [€]
HS 03V DL - PT 070	PC55/PC58	1x Hook 3t	148 - 168	LH286850	<b>15.692,00</b>
Tilt switch valve		12 V		LH205585	<b>976,00</b>






## SW 03 Adapter

Description	Weight [kg]	PN	Price [€]
 <b>Adapter frame SW 03</b> for bucket modification	12	104091	<b>144,00</b>
 <b>Symlock adapter SW 03</b> for backhoe and front shovel application, with bucket safety clip	14	219035	<b>234,00</b>
 <b>Weld-on adapter SW 03</b> for hammers, shears etc. Base plate: 400x250x20mm	30	106072	<b>486,00</b>
 <b>Screwed adapter SW 03</b> for hammers, shears etc. please specify exact type!	30	700509	<b>667,00</b>
 <b>Grab adapter SW 03</b> for suspended grabs, with cross bar please specify exact type!	27	700512	<b>1.154,00</b>

## SW 03V DL Adapter

Screw adapter with valve configuration for various attachments.

**NEW: For Double-Lock-Version HS03V DL!**

Description	Weight [kg]	PN	Price [€]
 <b>Screwed adapter SW 03V</b> for hydraulic hammers, valves: 2x KV1, plus installation and hoses	ca. 40		<b>1.735,00</b>
 <b>Screwed adapter SW 03V</b> for cutting units/compactors, valves: 2x KV1, 1x KV0.8, plus installation and hoses	ca. 40		<b>1.904,00</b>
 <b>Screwed adapter SW 03V</b> for sorting grabs/shears, valves: 2x KV1, 2x KV0.8, plus installation and hoses	ca. 40		<b>2.077,00</b>
 <b>Screwed adapter SW 03V</b> for rotating compactors, valves: 2x KV1, 3x KV0.8, plus installation and hoses	ca. 40		<b>2.248,00</b>
 <b>Grab adapter SW 03V</b> for suspended grabs, with cross bar, valves: 4x KV1, plus installation and hoses	ca. 65		<b>2.596,00</b>



## Attachments for PC55/PC58

**MTL 6 SY Mini backhoe bucket premium****with Symlock adapter SY 03**

backhoe and front shovel application

**premium quality:** cutting edge 150x16mm (500 HB), extended base and side edge out of 400 HB steel, teeth Kprime P004SC, with bucket safety clip.

Surcharge for HS 03V dirt protection: 20,00 EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
300	Kprime	P004SC	3	0,080	78	LH281788	<b>1.091,00</b>
400	Kprime	P004SC	3	0,120	87	LH281789	<b>1.144,00</b>
500	Kprime	P004SC	4	0,140	105	LH281790	<b>1.273,00</b>
600	Kprime	P004SC	4	0,180	109	LH281791	<b>1.334,00</b>
800	Kprime	P004SC	5	0,250	131	LH281792	<b>1.563,00</b>
1000	Kprime	P004SC	5	0,320	150	LH280395	<b>1.759,00</b>

**MTL 6 S SY Mini backhoe bucket premium without teeth**

**with Symlock adapter SY 03** - for backhoe and front shovel application, with elongated bucket base,

**premium quality:** cutting edge 150x16mm (500HB), extended base with protected weld seam and side edges of 400 HB steel, with bucket safety clip.

Surcharge for HS 03V dirt protection: 20,00 EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
300	no teeth		-	0,088	79	LH261951	<b>1.034,00</b>
400	no teeth		-	0,132	91	LH261952	<b>1.086,00</b>
500	no teeth		-	0,154	102	LH261953	<b>1.205,00</b>
600	no teeth		-	0,198	113	LH261954	<b>1.265,00</b>
800	no teeth		-	0,275	135	LH261955	<b>1.481,00</b>
1000	no teeth		-	0,352	157	LH261956	<b>1.669,00</b>



### MBL 6 SY Mini backhoe bucket basic

#### with Symlock adapter SY 03

backhoe and front shovel application

**with basic quality features:** cutting edge 150x16mm out of 400 HB steel, base out of S355 steel, two-strap teeth GW16, with bucket safety clip

Surcharge for HS 03V protection: 20,00 EUR



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
300			3	0,080	83	LH244235	<b>865,00</b>
400			3	0,120	89	LH244236	<b>929,00</b>
500			4	0,140	106	LH244237	<b>1.024,00</b>
600			4	0,180	118	LH244238	<b>1.101,00</b>
800			5	0,250	144	LH244239	<b>1.218,00</b>
1000			5	0,320	170	LH244240	<b>1.347,00</b>

### MBL 6 S SY Mini backhoe bucket basic without teeth

with Symlock adapter SY 03 - for backhoe and front shovel application, with elongated bucket base.

**with basic quality features:** cutting edge 150x16mm out of 400 HB steel, base out of S355 steel, with bucket safety clip

Surcharge for HS 03V dirt protection: 20,00 EUR



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
300	no teeth		-	0,088	84	LH261957	<b>770,00</b>
400	no teeth		-	0,132	97	LH261958	<b>828,00</b>
500	no teeth		-	0,154	110	LH261959	<b>913,00</b>
600	no teeth		-	0,198	123	LH261960	<b>984,00</b>
800	no teeth		-	0,275	149	LH261961	<b>1.085,00</b>
1000	no teeth		-	0,352	175	LH261962	<b>1.201,00</b>



## Attachments for PC55/PC58

**MG 6 R Ditch bucket, rigid version****with Symlock adapter SY 03**

for backhoe and front shovel application, cutting edge 150x16mm out of 500 HB steel & side edges out of 400 HB steel, lateral water drain bores. Surcharge for HS 03V protection: 20,00 EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1200			-	0,255	136	LH270038	<b>1.641,00</b>
1400			-	0,300	154	LH270039	<b>1.797,00</b>
1600			-	0,345	173	LH270040	<b>1.895,00</b>

**MG 6 G Ditch bucket, rigid version**

for tilt application with straight side cutting edge, cutting edge 150x16mm and side cutting edge out of 500 HB steel, lateral water drain bores, with Symlock Adapter SY 03  
Surcharge for HS 03V dirtprotection: 20,00 EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1200			-	0,190	124	LH247127	<b>1.608,00</b>
1400			-	0,240	140	LH247130	<b>1.683,00</b>
1500			-	0,260	147	LH247121	<b>1.725,00</b>

**MG 6 RH Tilting ditch bucket****with Lehmatic adapter SW 03**

2 x 45° tilting range, 2 hydraulic cylinders, counter-balance valve, hydraulic connections on tilting head, cutting edge 150x16mm out of 500 HB steel and side edges out of 400 HB steel, lateral water drain bores.

Surcharge for HS-V adapter: 1.143,- EUR.

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1200			-	0,255	210	LH270024	<b>3.551,00</b>
1400			-	0,300	231	LH271302	<b>3.629,00</b>
1600			-	0,345	251	LH270026	<b>3.793,00</b>



### MSL 6 Sorting bucket with plasma base

with **Lehmatic adapter SW 03**, cutting edge 150x16mm (500 HB), plasma-cut base made of 400 HB steel, hole/bar width 60mm, teeth Kprime P004SC.



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
800	Kprime	P004SC	5	0,250	125	LH282489	<b>1.638,00</b>
1000	Kprime	P004SC	5	0,320	143	LH282490	<b>1.793,00</b>

### MSL 6 SY Sorting bucket round bars

with **Symlock adapter SY 03**, cutting edge 150x16mm (500 HB), Base made of round bars D25, hole width 50mm, teeth Kprime P004SC.



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1000		P004SC	5	0,320	143		<b>2.341,00</b>

### MKL 6 SY

**for cable construction** - with cutting edge 200x20 (500 HB), water drainage holes in the side walls, Symlock adapter SY03



Width [mm]	Digging Depth [mm]	Teeth	Weight [kg]	PN	Price [€]
130	750	-	66	LH290872	<b>1.243,00</b>



Attachments for PC45-PC58



**MRR 6 Clearing rake**

With **Symlock adapter SY 03**, for clearing bushes, shrubs and undergrowth, collecting prunings, soil loosening as well as sorting work in the recycling sector. 4 segments with wear protection made of HB450 steel, cutting edge (500HB) between the segments.

Tooth-radius [mm]	Width [mm]	Teeth	Weight [kg]	PN	Price [€]
700	770	4	175	LH282590	2.120,00



**MRZ 6 bionic Ripper tooth**

for demolition and rock use - with Lehmatic adapter SW 03

Option	Tooth point	Angle	Tooth-radius [mm]	Weight [kg]	PN	Price [€]
SW 03	6262	35	650	63	LH225506	1.412,00



**MPG 5 Pallet fork**

**Load handling** for all popular pallets, with adjustable forks, with Lehmatic adapter SW 03.

Width [mm]	Weight [kg/m]	Load capacity [t]	Weight [kg]	PN	Price [€]
1100	1200x100x45	1,8	251	LH225617	2.403,00



**MSG 6 Demolition and sorting grab**

compact design, grab shells out of Hardox 400, interchangeable cutting edges out of Hardox 500, incl. counter-balance valve, rotating angle 360° endless, incl. screwed Lehmatic adapter SW 03. Grab shells closed or with rectangular bars on demand. Surcharge for HS 03V adapter: 1532,- EUR

Opening clearance [mm]	Width [mm]	Capacity SAE [m³]	Grab force [kN]	Weight [kg]	PN	Price [€]
1350	650	0,140	26	455	LH264709	12.138,00



### MS 08 Quickcoupler mechanical

#### for PC80

Quickcoupler with mechanical locking, incl. socket wrench, optionally with 5t load hook

Type	Excavator	Option	Weight [kg]	PN	Price [€]
MS 08	PC80	-	75	LH219841	<b>2.950,00</b>
MS 08	PC80	Hook 5t	77	LH219378	<b>3.262,00</b>



### HS 08 DL Quickcoupler hydraulic

#### for PC80

Quickcoupler with hydraulic locking, optionally with 5t load hook.

**With safety locking mechanism Double Lock**

**NEW: With exchangeable HD wear protection on the claws**

Type	Excavator	Option	Weight [kg]	PN	Price [€]
HS 08 DL	PC80	-	80	LH280201	<b>3.978,00</b>
HS 08 DL	PC80	Hook 5t	82	LH276739	<b>4.290,00</b>



### HS 08V DL Quickcoupler fully hydraulic

#### for PC80

Fully hydraulic Quickcoupler with 3 valves KV1 and 2 valves KV2, one 5 t load hook, valve block's internal depressurizing circuit (BiD) incl., excl. hydr. installation kit and installation.

**With safety locking mechanism Double Lock**

**NEW: With exchangeable HD wear protection on the claws**

Type	Excavator	Option	Weight [kg]	PN	Price [€]
HS 08V DL	PC80	Hook 5t	90	LH286705	<b>7.487,00</b>





## Attachments for PC80

**MS 08 - Tilt Quickcoupler Tilt****for PC80**

Mechanical quickcoupler with Powertilt motor (PT), with direct suspension. Including 5t load hook.

Excl. optional switch valve and installation on excavator.



Type	Excavator	Option	Tilt-Angle	Weight [kg]	PN	Price [€]
MS 08 - PT 100	PC80	Hook 5t	2 x 90°	180-210	LH256975	<b>12.878,00</b>
Tilt switch valve		12 V			LH205585	<b>976,00</b>

**HS 08 DL - Tilt Quickcoupler Tilt****for PC80**

Hydraulic quickcoupler with Powertilt motor (PT), with direct suspension. Including 5t load hook.

Excl. optional switch valve and installation on excavator.

**With safety locking mechanism Double Lock**

**New: With exchangeable HD wear protection on the claws**



Type	Excavator	Option	Tilt-Angle	Weight [kg]	PN	Price [€]
HS 08 DL - PT 100	PC80	Hook 5t	2 x 90°	197-226	LH276675	<b>14.267,00</b>
Tilt switch valve		12 V			LH205585	<b>976,00</b>

**HS 08V DL - Tilt Quickcoupler Tilt****for PC80**

Fully hydraulic Quickcoupler with tilt motor, with Powertilt (PT). With direct suspension on excavator side. One load hook as standard. Excl. optional switch valve and installation on excavator.

**With safety locking mechanism Double Lock**








**NEW: With exchangeable HD wear protection on the claws**



Type	Excavator	Option	Tilt-Angle	Weight [kg]	PN	Price [€]
HS 08V DL - PT 100	PC80	Hook 5t	2 x 90°	230-250	LH286853	<b>19.269,00</b>
Tilt switch valve		12 V			LH205585	<b>976,00</b>

### SW 08 Adapter

For bucket modification and for welding or screwing on other attachments.

	Description	Weight [kg]	PN	Price [€]
	<b>Adapter frame SW 08</b> for bucket modification	30	100591	<b>365,00</b>
	<b>Symlock adapter SW 08</b> for backhoe and front shovel application, with bucket safety clip	30	285822	<b>421,00</b>
	<b>Weld-on adapter SW 08</b> for hammers, shears etc. Base plate: 400x350x30mm	50	105757	<b>705,00</b>
	<b>Screwed adapter SW 08</b> for hammers, shears etc. please specify exact type!	50	700515	<b>1.083,00</b>
	<b>Grab adapter SW 08</b> for suspended grabs, with cross bar please specify exact type!	70	700518	<b>1.237,00</b>
	<b>Universal adapter SW 08</b> <b>W=350mm</b> for individual drilling patterns, Base plate 350x475x30mm.	70	276473	<b>745,00</b>
	<b>Universal adapter SW 08</b> <b>W=600mm</b> for individual drilling patterns, Base plate 600x600x30mm.	115	276489	<b>773,00</b>



## Attachments for PC80

**SW 08V Adapter**

Screw-adapter SW 08V with valve configuration for various attachments (Please specify attachment type)

	Description	Weight [kg]	Price [€]
	<b>Screwed adapter SW 08V</b> for hydraulic hammers, valves: 2x KV2, plus installation and hoses	ca. 75	<b>2.248,00</b>
	<b>Screwed adapter SW 08V</b> for cutting units/compactors, valves: 2x KV2, 1x KV1, plus installation and hoses	ca. 75	<b>2.376,00</b>
	<b>Screwed adapter SW 08V</b> for sorting grabs/shears, valves: 2x KV2, 2x KV1, plus installation and hoses	ca. 75	<b>2.506,00</b>
	<b>Screwed adapter SW 08V</b> for rotating compactors, valves: 2x KV2, 3x KV1, plus installation and hoses	ca. 75	<b>2.634,00</b>
	<b>Grab adapter SW 08V</b> for suspended grabs, with cross bar, valves: 2x KV1, 2x KV2, plus installation and hoses		<b>2.947,00</b>
	<b>Universal adapter SW 08V W=362mm for Hammer</b> for individual drilling patterns, Base plate 362x475x30mm, Bottom side machined and planned. Valves: 2xKV2	135	<b>2.260,00</b>
	<b>Universal adapter SW 08V W=600mm for Hammer</b> for individual drilling patterns, Base plate 600x600x30mm, Bottom side machined and planned. Valves: 2xKV2	135	<b>2.295,00</b>
	<b>Universal adapter SW 08V W=362mm for Demolition and Sorting Grab/Shear</b> for individual drilling patterns, Base plate 362x475x30mm, Bottom side machined and planned. Valves: 2xKV2 and 2xKV1	135	<b>2.389,00</b>
	<b>Universal adapter SW 08V W=600mm for Demolition and Sorting Grab/Shear</b> for individual drilling patterns, Base plate 600x600x30mm, Bottom side machined and planned. Valves: 2xKV2 and 2xKV1	135	<b>2.423,00</b>



### CTL 5 SY Compact backhoe bucket

#### with Symlock adapter SY 08

for backhoe and front shovel application, cutting edge 200x20mm (500 HB), base out of 400 HB steel, bucket safety clip incl. With teeth P010SC. Surcharge for HS 08V dirt protection: 41,29 EUR



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
400	Kprime	P010SC	2	0,130	146	LH281714	<b>1.822,00</b>
500	Kprime	P010SC	3	0,170	152	LH281715	<b>1.994,00</b>
600	Kprime	P010SC	3	0,210	175	LH281716	<b>2.051,00</b>
800	Kprime	P010SC	4	0,300	210	LH281717	<b>2.291,00</b>
900	Kprime	P010SC	4	0,340	233	LH281718	<b>2.419,00</b>
1000	Kprime	P010SC	5	0,380	243	LH281719	<b>2.533,00</b>

### CTL 5 SY Compact backhoe bucket without teeth

#### with Symlock adapter SY 08 without teeth

- for backhoe and front shovel application, cutting edge 200x20mm (500 HB), base of 400 HB steel, with Symlock adapter SY 08, bucket safety clip incl.

Surcharge for HS 08V dirt protection: 41,29 EUR



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
400	no teeth		-	0,142	135	LH221102	<b>1.577,00</b>
500	no teeth		-	0,185	150	LH264024	<b>1.994,00</b>
600	no teeth		-	0,230	165	LH264012	<b>2.051,00</b>
800	no teeth		-	0,325	200	LH263984	<b>2.291,00</b>
900	no teeth		-	0,370	215	LH221136	<b>2.419,00</b>
1000	no teeth		-	0,415	230	LH241764	<b>2.533,00</b>

### CSL 5 Sorting bucket with rectangular bars

with Symlock adapter SY 08, bottom made of solid rectangular bars 30x20mm, 60mm bar spacing, cutting edge 200x25mm (500 HB), teeth Kprime P010SC.

Surcharge for HS 08V dirt protection: 41,29 EUR



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
800	Kprime	P010SC	4	0,300	245	LH282491	<b>3.338,00</b>



## Attachments for PC80

**CSL 5 Sorting bucket round bars**

with Symlock adapter SY 08,

Base made of round bars D25, 60mm hole width, cutting edge 200x25mm (500 HB), teeth Kprime P010SC.

Surcharge for HS 08V dirt protection: 41,29 EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
800		P010SC	4	0,300	245		<b>3.338,00</b>

**CG 5 SY rigid Ditch bucket, rigid version**

with Symlock adapter SY 08

cutting edge 200x20mm and side edges out of 500 HB steel, base out of 400 HB steel, 1800mm width with 2 stiffening ribs, lateral water drain bores. Surcharge for HS 08V dirt protection: 41,29 EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1500			-	0,280	230	LH221962	<b>1.965,00</b>
1800			-	0,340	268	LH221834	<b>2.325,00</b>

**CG 5 Tilting ditch bucket**

with Lehmatic adapter SW 08

1 hydraulic cylinder, 2 x 45° tilting range, counter-balance valve, hydraulic connections on tilting head, cutting edge 200x20mm and side edges out of 500 HB steel, base out of 400 HB steel, 1800mm width with 2 stiffening ribs, lateral water drain bores.

Surcharge for HS 08V adapter: 1.326,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1500				0,280	328	LH209530	<b>4.469,00</b>
1800				0,340	372	LH210014	<b>4.653,00</b>

**CP 5 Grading bucket**

especially for use with rotators/tilt-rotators, 45° conical side walls, cutting edge 200x20mm out of 500 HB steel, base out of 400 HB steel.

Surcharge for HS 08V dirt protection: 41,29 EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1200			-	0,300	209	LH294405	<b>2.758,00</b>



### CU 5 G rigid Universal bucket

with Symlock adapter SY 08, rigid with backhoe bucket shape, cutting edge 200x20mm and side edges out of 500 HB steel, base out of 400 HB steel.

Surcharge for HS 08V dirt protection: 41,29 EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1200			-	0,267	241	LH279233	<b>1.954,00</b>
1400			-	0,318	273	LH279234	<b>2.146,00</b>



### CU 5 GH Universal tilting bucket

with Lehmatic adapter SW 08, backhoe bucket shape

1 hydraulic cylinder, 2 x 45° tilting range, counter-balance valve, hydraulic connections on tilting head, cutting edge 200x20mm and side edges out of 500 HB steel, base of 400 HB steel.

Surcharge for HS 08V adapter: 1.326,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1200				0,267	343	LH279235	<b>4.171,00</b>
1400				0,318	398	LH279236	<b>4.396,00</b>



### CKL 10 SY

for cable construction - with cutting edge 200x20 (500 HB), water drainage holes in the side walls, Symlock adapter SY08.

Width [mm]	Digging Depth [mm]	Teeth	Weight [kg]	PN	Price [€]
250	1000	-	134	LH290873	<b>2.070,00</b>



### CRR 8 Clearing rake

With Symlock adapter SY08, for clearing bushes, shrubs and undergrowth, collecting prunings, loosening soil and sorting work in the recycling sector. 4 segments with wear protection made of HB450 steel, cutting edge (500HB) between the segments.

Tooth-radius [mm]	Width [mm]	Teeth	Weight [kg]	PN	Price [€]
850	770	4		LH282589	<b>2.823,00</b>



Attachments for PC80



**CRZ 8 bionic Ripper tooth**

for demolition and rock use - with Lehmatic adapter SW 08

Option	Tooth point	Angle	Tooth-radius [mm]	Weight [kg]	PN	Price [€]
SW 08	308080	35	750	124	LH225533	1.898,00



**CPG 10 Pallet fork**

Load handling for all popular pallets, due to adjustable forks, with Lehmatic adapter SW 08.

Width [mm]	Weight [kg/m]	Load capacity [t]	Weight [kg]	PN	Price [€]
1100	1200x100x45	2,4	255	LH218504	2.688,00



**CSG 10 Demolition and sorting grab**

compact design, grab shells out of Hardox 400, interchangeable cutting edges out of Hardox 500, incl. counter-balance valve, rotating angle 360° endless, incl. screwed Lehmatic adapter SW 08. Grab shells closed or with rectangular bars on demand. Surcharge for HS 08V adapter: 1.570,- EUR

Opening clearance [mm]	Width [mm]	Capacity SAE [m³]	Grab force [kN]	Weight [kg]	PN	Price [€]
1350	650	0,140	26	475	LH264711	15.690,00



**CSG 10V Demolition and sorting grab**

With integrated SW 08V adapter, ready for use, approx. 10% weight saving and lower overall height. With integrated HS xxV adapter, ready for use, approx. 10% weight saving and lower overall height. Grab shells out of Hardox 400, interchangeable cutting edges out of Hardox 500, incl. counter-balance valve, rotating angle 360° endless, Grab shells closed or with rectangular bars on demand.

Opening clearance [mm]	Width [mm]	Capacity SAE [m³]	Grab force [kN]	Weight [kg]	PN	Price [€]
1350	650	0,140	26	475	LH282374	17.583,00



### MS 08 Quickcoupler mechanical

#### for PC88/PW98

Quickcoupler with mechanical locking, incl. socket wrench, optionally with 5t load hook



Type	Excavator	Option	Weight [kg]	PN	Price [€]
MS 08	PC88/PW98	-	75	LH203918	<b>2.950,00</b>
MS 08	PC88/PW98	Hook 5t	77	LH213604	<b>3.262,00</b>

### HS 08 DL Quickcoupler hydraulic

#### for PC88/PW98

Quickcoupler with hydraulic locking, optionally with 5t load hook.

**With safety locking mechanism Double Lock**

**New: With exchangeable HD wear protection on the claws**



Type	Excavator	Option	Weight [kg]	PN	Price [€]
HS 08 DL	PC88/PW98	-	80	LH280203	<b>3.978,00</b>
HS 08 DL	PC88/PW98	Hook 5t	82	LH276751	<b>4.290,00</b>

### HS 08V DL Quickcoupler fully hydraulic

#### for PC88/PW98

Fully hydraulic Quickcoupler with 3 valves KV1 and 2 valves KV2, one 5 t load hook, valve block's internal depressurizing circuit (BiD) incl., plus hydr. installation kit and installation.

**With safety locking mechanism Double Lock.**

**NEW: With exchangeable HD wear protection on the claws**



Type	Excavator	Option	Weight [kg]	PN	Price [€]
HS 08V DL	PC88/PW98	Hook 5t	90	LH286857	<b>7.487,00</b>





## Attachments for PC88/PW98

**MS 08 - Tilt Quickcoupler Tilt****for PC88/PW98**

Mechanical quickcoupler with Powertilt motor (PT), with direct suspension. Including 5t load hook.

Excl. optional switch valve, excl. installation on excavator.



Type	Excavator	Option	Tilt-Angle	Weight [kg]	PN	Price [€]
MS 08 - PT 100	PC88/PW98	Hook 5t	2 x 90°	180-210	LH256979	<b>12.878,00</b>
Tilt switch valve		12 V			LH205585	<b>976,00</b>


**HS 08 DL - Tilt Quickcoupler hydraulic****for PC88/PW98**

Hydraulic quickcoupler with Powertilt motor (PT), with direct suspension. Including 5t load hook.

Excl. optional switch valve and installation on excavator.

**With safety locking mechanism Double Lock**

**New: With exchangeable HD wear protection on the claws**



Type	Excavator	Option	Tilt-Angle	Weight [kg]	PN	Price [€]
HS 08 DL - PT 100	PC88/PW98	Hook 5t	2 x 90°	197-226	LH276745	<b>14.267,00</b>
Tilt switch valve		12 V			LH205585	<b>976,00</b>

**HS 08V DL - Tilt Quickcoupler Tilt****for PC88/PW98**

Fully hydraulic Quickcoupler with tilt motor, with Powertilt (PT). With direct suspension on excavator side. one load hook as standard. Excl. optional switch valve and installation on excavator.

**With safety locking mechanism Double Lock**

**NEW: With exchangeable HD wear protection on the claws**










Type	Excavator	Option	Tilt-Angle	Weight [kg]	PN	Price [€]
HS 08V DL - PT 100	PC88/PW98	Hook 5t	2 x 90°	230-250	LH286859	<b>19.269,00</b>
Tilt switch valve		12 V			LH205585	<b>976,00</b>



## SW 08 Adapter

For bucket modification and for welding or screwing on other attachments.

	Description	Weight [kg]	PN	Price [€]
	<b>Adapter frame SW 08</b> for bucket modification	30	100591	<b>365,00</b>
	<b>Symlock adapter SW 08</b> for backhoe and front shovel application, with bucket safety clip	30	285822	<b>421,00</b>
	<b>Weld-on adapter SW 08</b> for hammers, shears etc. Base plate: 400x350x30mm	50	105757	<b>705,00</b>
	<b>Screwed adapter SW 08</b> for hammers, shears etc. please specify exact type!	50	700515	<b>1.083,00</b>
	<b>Grab adapter SW 08</b> for suspended grabs, with cross bar please specify exact type!	70	700518	<b>1.237,00</b>
	<b>Universal adapter SW 08</b> <b>W=350mm</b> for individual drilling patterns, Base plate 350x475x30mm.	70	276473	<b>745,00</b>
	<b>Universal adapter SW 08</b> <b>W=600mm</b> for individual drilling patterns, Base plate 600x600x30mm.	115	276489	<b>773,00</b>



Attachments for PC88/PW98

**SW 08V Adapter**

Screw-adapter SW 08V with valve configuration for various attachments (Please specify attachment type)

	Description	Weight [kg]	Price [€]
	<b>Screwed adapter SW 08V</b> for hydraulic hammers, valves: 2x KV2, plus installation and hoses	ca. 75	<b>2.248,00</b>
	<b>Screwed adapter SW 08V</b> for cutting units/compactors, valves: 2x KV2, 1x KV1, plus installation and hoses	ca. 75	<b>2.376,00</b>
	<b>Screwed adapter SW 08V</b> for sorting grabs/shears, valves: 2x KV2, 2x KV1, plus installation and hoses	ca. 75	<b>2.506,00</b>
	<b>Screwed adapter SW 08V</b> for rotating compactors, valves: 2x KV2, 3x KV1, plus installation and hoses	ca. 75	<b>2.634,00</b>
	<b>Grab adapter SW 08V</b> for suspended grabs, with cross bar, valves: 2x KV1, 2x KV2, plus installation and hoses		<b>2.947,00</b>
	<b>Universal adapter SW 08V W=362mm for Hammer</b> for individual drilling patterns, Base plate 362x475x30mm, Bottom side machined and planned. Valves: 2xKV2	135	<b>2.260,00</b>
	<b>Universal adapter SW 08V W=600mm for Hammer</b> for individual drilling patterns, Base plate 600x600x30mm, Bottom side machined and planned. Valves: 2xKV2	135	<b>2.295,00</b>
	<b>Universal adapter SW 08V W=362mm for Demolition and Sorting Grab/Shear</b> for individual drilling patterns, Base plate 362x475x30mm, Bottom side machined and planned. Valves: 2xKV2 and 2xKV1	135	<b>2.389,00</b>
	<b>Universal adapter SW 08V W=600mm for Demolition and Sorting Grab/Shear</b> for individual drilling patterns, Base plate 600x600x30mm, Bottom side machined and planned. Valves: 2xKV2 and 2xKV1	135	<b>2.423,00</b>



### CTL 10 SY Compact backhoe bucket

#### with Symlock adapter SY 08

for backhoe and front shovel application, cutting edge 200x25mm (500 HB), base out of 400 HB steel, bucket safety clip incl. With tooth system Kprime P010SC. Surcharge for HS 08V dirt protection: 41,29 EUR



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
400	Kprime	P010SC	2	0,155	163	LH281720	<b>2.366,00</b>
500	Kprime	P010SC	3	0,200	178	LH281721	<b>2.563,00</b>
600	Kprime	P010SC	3	0,255	200	LH281722	<b>2.747,00</b>
800	Kprime	P010SC	4	0,360	236	LH281723	<b>2.952,00</b>
900	Kprime	P010SC	4	0,410	255	LH281724	<b>3.171,00</b>
1000	Kprime	P010SC	5	0,460	285	LH281725	<b>3.385,00</b>

### CTL 10 S SY Compact backhoe bucket without teeth

#### with Symlock adapter SY 08 without teeth

- for backhoe and front shovel application, cutting edge 200x25mm (500 HB), base of 400 HB steel, with Symlock adapter SY 08, bucket safety clip incl.

Surcharge for HS 08V dirt protection: 41,29 EUR



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
400	no teeth	-	-	0,175	150	LH227885	<b>2.248,00</b>
500	no teeth	-	-	0,220	165	LH239867	<b>2.435,00</b>
600	no teeth	-	-	0,280	185	LH218174	<b>2.610,00</b>
800	no teeth	-	-	0,400	220	LH218182	<b>2.811,00</b>
1000	no teeth	-	-	0,510	245	LH230527	<b>3.216,00</b>

### CSL 10 Sorting bucket with rectangular bars

#### with Symlock adapter SY 08

Base made of solid rectangular bars 30x20mm, 60mm bar spacing, cutting edge 200x25mm (500 HB), with teeth Kprime P010SC.



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1000	Kprime	P010SC	5	0,460	295	LH282492	<b>3.688,00</b>



## Attachments for PC88/PW98

**CSL 10** Sorting bucket round bars

with Symlock adapter SY 08,

Base made of round bars D30, 50mm hole width, cutting edge 200x25mm (500 HB), with teeth Kprime P010SC.

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1000		P010SC	5	0,460	295		<b>3.688,00</b>

**CP 10** Grading bucket

especially for use with rotators/tilt-rotators, 45° conical side walls, cutting edge 200x20mm out of 500 HB steel, base out of 400 HB steel, wear resistant plates out of 400 HB. Surcharge for HS 08V dirt protection: 41,29 EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1300			-	0,390	239	LH293082	<b>3.158,00</b>

**CG 10 SY rigid** Ditch bucket, rigid version

with Symlock adapter SY 08

cutting edge 200x20mm and side edges out of 500 HB steel, base out of 400 HB, 1800mm width with 2 stiffening ribs, lateral water drain bores. Surcharge for HS 08V dirt protection: 41,29 EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1500			-	0,350	233	LH211819	<b>2.429,00</b>
1800			-	0,420	281	LH211820	<b>2.731,00</b>

**CG 10** Tilting ditch bucket

with Lehmatic adapter SW 08

1 hydraulic cylinder, 2 x 45° tilting range, counter-balance valve, hydraulic connections on tilting head, cutting edge 200x20mm and side edges out of 500 HB steel, lateral water drain bores. Surcharge for HS 08V adapter: 1.326,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1500				0,350	334	LH210027	<b>4.837,00</b>
1800				0,420	390	LH210040	<b>5.093,00</b>



### CU 10 G rigid Universal bucket

with Symlock adapter SY 08, rigid with backhoe bucket shape, cutting edge 200x20mm and side edges out of 500 HB steel, base out of 400 HB steel.

Surcharge for HS 08V dirt protection: 41,29 EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1200			-	0,420	295	LH279239	<b>2.250,00</b>
1400			-	0,500	330	LH279240	<b>2.499,00</b>



### CU 10 GH Universal tilting bucket

with Lehmatic adapter SW 08, backhoe bucket shape

1 hydraulic cylinder, 2 x 45° tilting range, counter-balance valve, hydraulic connections on tilting head, cutting edge 200x20mm and side edges out of 500 HB steel, base of 400 HB steel.

Surcharge for HS 08V adapter: 1.326,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1200				0,420	397	LH279241	<b>4.595,00</b>
1400			-	0,500	455	LH279242	<b>4.876,00</b>



### CKL 10 SY

for cable construction - with cutting edge 200x20 (500 HB), water drainage holes in the side walls, Symlock adapter SY08.

Width [mm]	Digging Depth [mm]	Teeth	Weight [kg]	PN	Price [€]
250	1000	-	134	LH290873	<b>2.070,00</b>



### CRR 8 Clearing rake

With Symlock adapter SY08, for clearing bushes, shrubs and undergrowth, collecting prunings, loosening soil and sorting work in the recycling sector. 4 segments with wear protection made of HB450 steel, cutting edge (500HB) between the segments.

Tooth-radius [mm]	Width [mm]	Teeth	Weight [kg]	PN	Price [€]
850	770	4	54	LH282589	<b>2.823,00</b>



Attachments for PC88/PW98



**CRZ 8 bionic Ripper tooth**

for demolition and rock use - with Lehmatic adapter SW 08

Option	Tooth point	Angle	Tooth-radius [mm]	Weight [kg]	PN	Price [€]
SW 08	308080	35	750	124	LH225533	1.898,00



**CPG 10 Pallet fork**

Load handling for all popular pallets, due to adjustable forks, with Lehmatic adapter SW 08.

Width [mm]	Weight [kg/m]	Load capacity [t]	Weight [kg]	PN	Price [€]
1100	1200x100x45	2,4	255	LH218504	2.688,00



**CSG 10 Demolition and sorting grab**

compact design, grab shells out of Hardox 400, interchangeable cutting edges out of Hardox 500, incl. counter-balance valve, rotating angle 360° endless, incl. screwed Lehmatic adapter SW 08. Grab shells closed or with rectangular bars on demand. Surcharge for HS 08V adapter: 1.570,- EUR

Opening clearance [mm]	Width [mm]	Capacity SAE [m³]	Grab force [kN]	Weight [kg]	PN	Price [€]
1350	650	0,140	26	475	LH264711	15.690,00



**CSG 10V Demolition and sorting grab**

With integrated SW 08V adapter, ready for use, approx. 10% weight saving and lower overall height. With integrated HS xxV adapter, ready for use, approx. 10% weight saving and lower overall height. Grab shells out of Hardox 400, interchangeable cutting edges out of Hardox 500, incl. counter-balance valve, rotating angle 360° endless, Grab shells closed or with rectangular bars on demand.

Opening clearance [mm]	Width [mm]	Capacity SAE [m³]	Grab force [kN]	Weight [kg]	PN	Price [€]
1350	650	0,140	26	475	LH282374	17.583,00



### MS 08 Quickcoupler mechanical

#### for WB93/WB97

Quickcoupler with mechanical locking, incl. socket wrench, optionally with 5t load hook

Type	Excavator	Option	Weight [kg]	PN	Price [€]
MS 08	WB93/WB97	-	75	LH212005	<b>2.950,00</b>
MS 08	WB93/WB97	Hook 5t	77	LH255580	<b>3.262,00</b>



### HS 08 DL Quickcoupler hydraulic

#### for WB93/WB97

Quickcoupler with hydraulic locking, optionally with 5t load hook.

**With safety locking mechanism Double Lock**

**New: With exchangeable HD wear protection on the claws**

Type	Excavator	Option	Weight [kg]	PN	Price [€]
HS 08 DL	WB93/WB97		80	LH283186	<b>3.978,00</b>
HS 08 DL	WB93/WB97	Hook 5t	82	LH280207	<b>4.290,00</b>
Install. kit HS 08 12V		QC valve, switch etc.		LH232307	





Attachments for PW138



**MS 08 Quickcoupler mechanical**

**for PW138**

Quickcoupler with mechanical locking, incl. socket wrench, optionally with 5t load hook

Type	Excavator	Option	Weight [kg]	PN	Price [€]
MS 08	PW138	-	75	LH292124	<b>2.950,00</b>
MS 08	PW138	Hook 5t	77	LH292125	<b>3.262,00</b>



**HS 08 DL Quickcoupler hydraulic**

**for PW138**

Quickcoupler with hydraulic locking, optionally with 5t load hook.

**With safety locking mechanism Double Lock**

**New: With exchangeable HD wear protection on the claws**

Type	Excavator	Option	Weight [kg]	PN	Price [€]
HS 08 DL	PW138	-	80	LH292127	<b>3.978,00</b>
HS 08 DL	PW138	Hook 5t	82	LH287874	<b>4.290,00</b>



**HS 08V DL Quickcoupler fully hydraulic**

**for PW138**

Fully hydraulic Quickcoupler with 3 valves KV1 and 2 valves KV2, one 5 t load hook, valve block's internal depressurizing circuit (BiD) incl., excl. hydr. installation kit and installation.

**With safety locking mechanism Double Lock**

**New: With exchangeable HD wear protection on the claws**

Type	Excavator	Option	Weight [kg]	PN	Price [€]
HS 08V DL	PW138	Hook 5t	90	LH285083	<b>7.487,00</b>



### MS 08 - Tilt Quickcoupler Tilt

#### for PW138

Mechanical quickcoupler with Powertilt motor (PT), with direct suspension. Including 5t load hook.

Excl. optional switch valve, excl. installation on excavator.



Type	Excavator	Option	Tilt-Angle	Weight [kg]	PN	Price [€]
MS 08 - PT 180	PW138	Hook 5t	2 x 90°	280-300	LH292126	<b>13.667,00</b>
Tilt switch valve		12 V			LH205585	<b>976,00</b>

### HS 08 DL - Tilt Quickcoupler hydraulic


#### for PW138

Hydraulic quickcoupler with Powertilt motor (PT), with direct suspension. Including 5t load hook.

Excl. optional switch valve, excl. installation on excavator.

**With safety locking mechanism Double Lock**

**New: With exchangeable HD wear protection on the claws**



Type	Excavator	Option	Tilt-Angle	Weight [kg]	PN	Price [€]
HS 08 DL - PT 180	PW138	Hook 5t	2 x 90°	290-310	LH287893	<b>15.056,00</b>
Tilt switch valve		12 V			LH205585	<b>976,00</b>

### HS 08V DL - Tilt Quickcoupler Tilt

#### for PW138

Fully hydraulic Quickcoupler with tilt motor, with Powertilt (PT). With direct suspension on excavator side. One load hook as standard. Excl. optional switch valve, excl. installation on excavator.

**With safety locking mechanism Double Lock**

**New: With exchangeable HD wear protection on the claws**




Type	Excavator	Option	Tilt-Angle	Weight [kg]	PN	Price [€]
HS 08V DL - PT 180	PW138	Hook 5t	2 x 90°	300-320	LH292128	<b>20.074,00</b>
Tilt switch valve		12 V			LH205585	<b>976,00</b>



## SW 08 Adapter

For bucket modification and for welding or screwing on other attachments.

	Description	Weight [kg]	PN	Price [€]
	<b>Adapter frame SW 08</b> for bucket modification	30	100591	<b>365,00</b>
	<b>Symlock adapter SW 08</b> for backhoe and front shovel application, with bucket safety clip	30	285822	<b>421,00</b>
	<b>Weld-on adapter SW 08</b> for hammers, shears etc. Base plate: 400x350x30mm	50	105757	<b>705,00</b>
	<b>Screwed adapter SW 08</b> for hammers, shears etc. please specify exact type!	50	700515	<b>1.083,00</b>
	<b>Grab adapter SW 08</b> for suspended grabs, with cross bar please specify exact type!	70	700518	<b>1.237,00</b>
	<b>Universal adapter SW 08</b> <b>W=350mm</b> for individual drilling patterns, Base plate 350x475x30mm.	70	276473	<b>745,00</b>
	<b>Universal adapter SW 08</b> <b>W=600mm</b> for individual drilling patterns, Base plate 600x600x30mm.	115	276489	<b>773,00</b>



## SW 08V Adapter

Screw-adapter SW 08V with valve configuration for various attachments (Please specify attachment type)

Description		Weight [kg]	Price [€]
		<b>Screw-adapter SW 08V</b> for hydraulic hammers, valves: 2x KV2, plus installation and hoses	ca. 75 <b>2.248,00</b>
		<b>Screw-adapter SW 08V</b> for cutting units/compactors, valves: 2x KV2, 1x KV1, plus installation and hoses	ca. 75 <b>2.376,00</b>
		<b>Screw-adapter SW 08V</b> for sorting grabs/shears, valves: 2x KV2, 2x KV1, plus installation and hoses	ca. 75 <b>2.506,00</b>
		<b>Screw-adapter SW 08V</b> for rotating compactors, valves: 2x KV2, 3x KV1, plus installation and hoses	ca. 75 <b>2.634,00</b>
		<b>Grab adapter SW 08V</b> for suspended grabs, with cross bar, valves: 2x KV1, 2x KV2, plus installation and hoses	<b>2.947,00</b>
		<b>Universal adapter SW 08V W=362mm for Hammer</b> for individual drilling patterns, Base plate 362x475x30mm, Bottom side machined and planned. Valves: 2xKV2	135 <b>2.260,00</b>
		<b>Universal adapter SW 08V W=600mm for Hammer</b> for individual drilling patterns, Base plate 600x600x30mm, Bottom side machined and planned. Valves: 2xKV2	135 <b>2.295,00</b>
		<b>Universal adapter SW 08V W=362mm for Demolition and Sorting Grab/Shear</b> for individual drilling patterns, Base plate 362x475x30mm, Bottom side machined and planned. Valves: 2xKV2 and 2xKV1	135 <b>2.389,00</b>
		<b>Universal adapter SW 08V W=600mm for Demolition and Sorting Grab/Shear</b> for individual drilling patterns, Base plate 600x600x30mm, Bottom side machined and planned. Valves: 2xKV2 and 2xKV1	135 <b>2.423,00</b>



## Attachments for PW138



### SQ 60H LSC Quickcoupler hydraulic, symmetrical for PW138

Hydraulic symmetrical quickcoupler, based on S-standard, with LSC safety assistance system as standard, One 8 t load hook. Installation kit and installation not included.

Type	Excavator	Option	Weight [kg]	PN	Price [€]
SQ 60H LSC	PW138	Hook 5t		LH287193	<b>6.282,00</b>
LSC install. kit electr.				LH249489	<b>1.069,00</b>



### SQ 60V LSC Quickcoupler fully hydraulic, symmetrical for PW138

Fully hydraulic symmetrical quickcoupler, based on S standard, with LSC safety assistance system as standard. 2 valves KV3 and 3 valves KV1, one 5t load hook, incl. valve block's internal depressurization unit (BiD), installation kit and installation not included.

Type	Excavator	Option	Weight [kg]	PN	Price [€]
SQ 60V LSC	PW138	1x Hook 5t	170	LH282667	<b>11.230,00</b>
SQ 60V LSC	PW138	2x Hook 5t	175	LH282668	<b>11.568,00</b>
LSC install. kit electr.				LH249489	<b>1.069,00</b>








### SQ 60V LSC Quickcoupler Tilt for PW138

Fully hydraulic symmetrical quickcoupler with Powertilt motor, based on S standard, with LSC safety assistance system as standard. 2 valves KV3 and 3 valves KV1, one 5 t load hook, incl. valve block's internal depressurization unit (BiD), installation kit and installation not included. Also available as hydraulic version.

Type	Excavator	Option	Tilt-Angle	Weight [kg]	PN	Price [€]
<b>SQ 60V LSC - PT180</b>	PW138	1x Hook 5t	2 x 60°	350		<b>22.259,00</b>
LSC install. kit electr.					LH249489	<b>1.069,00</b>






## SQ 60 Adapter

	Description	Weight [kg]	PN	Price [€]
	<b>Adapter Frame SQ 60 for bucket modification</b> for use with SQH60	46	LH283682	<b>802,00</b>
	<b>Adapter Frame SQ 60 for bucket modification</b> incl. SQ valve dirt protection and tacking device, for use with SQH60 & SQ60	49	LH279824	<b>932,00</b>
	<b>Weld-on adapter SQ 60</b> for use with SQH60 for welding on various attachm.	105	LH283676	<b>1.285,00</b>
	<b>Screwed adapter SQ 60</b> for use with SQH60 for hammers, grabs, compactors etc. exact type required!	115		<b>1.745,00</b>
	<b>Universal adapter SQ 60</b> for use with SQH60 for individual drilling patterns, Base plate 445x545x30mm machined and planned.	105	LH283670	<b>1.321,00</b>



### SQ 60V Adapter

Screw-adapter SQ 60 with valve configuration for various attachments (Please specify attachment type)

	Description	Weight [kg]	Price [€]
	<b>Screwed adapter SQ 60V</b> for hydraulic hammers valves: 2x KV3, plus installation and hoses	135	<b>3.478,00</b>
	<b>Screwed adapter SQ 60V</b> for cutting units/compactors valves: 2x KV3, 1x KV1, plus installation and hoses	135	<b>3.725,00</b>
	<b>Screwed adapter SQ 60V</b> for sorting grabs/shears valves: 2x KV3, 2x KV1, plus installation and hoses	135	<b>4.078,00</b>
	<b>Screwed adapter SQ 60V</b> for rotating compactors valves: 2x KV3, 3x KV1, plus installation and hoses	135	<b>3.929,00</b>
	<b>Grab adapter SQ 60V</b> for suspended grabs with cross bar, valves: 2x KV1, 2x KV3, plus installation and hoses	145	<b>4.539,00</b>



### CTL 12 SY Compact backhoe bucket

#### with Symlock adapter SY 08

for backhoe and front shovel application, cutting edge 200x25mm (500 HB), base out of 400 HB steel, bucket safety clip incl. With tooth system Kprime P010SC.

Surcharge for HS 08V dirt protection: 41,29 EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
400	Kprime	P010SC	2	0,170	170	LH281727	<b>2.419,00</b>
500	Kprime	P010SC	3	0,225	184	LH281728	<b>2.676,00</b>
600	Kprime	P010SC	3	0,280	220	LH281729	<b>2.860,00</b>
800	Kprime	P010SC	4	0,395	245	LH281730	<b>3.142,00</b>
1000	Kprime	P010SC	5	0,510	310	LH281732	<b>3.485,00</b>
1200	Kprime	P010SC	6	0,620	370	LH281733	<b>4.205,00</b>



### CSL 12 Sorting bucket with rectangular bars

with Symlock adapter SY 08, bottom made of solid rectangular bars 30x20mm, 60mm bar spacing, cutting edge 200x25mm (500 HB), with teeth Kprime P010SC.

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1200	Kprime	P010SC	6	0,620	355	LH282493	<b>5.128,00</b>



### CSL 12 Sorting bucket round bars

with Symlock adapter SY 08,

Base with round bars D30, 60mm hole width, cutting edge 200x25mm (500 HB), with teeth Kprime P010SC.

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1200		P010SC	6	0,620	355		<b>5.128,00</b>





Attachments for PW138



**HG 15 S SY Ditch bucket, rigid version**

with **Symlock adapter SY 08, rigid version**, round design, base out of 400 HB steel, cutting edge 200x20mm and side edges out of Lehborit 5000 (500 HB), lateral water drain bores.

Surcharge for HS 08V dirt protection: 41,29 EUR

Surcharge for SQ60 Adapter incl. dirt protection: 352,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1600			-	0,440	320	LH245045	<b>3.209,00</b>
1800			-	0,500	352	LH212051	<b>3.265,00</b>



**HG 15 SH Tilting ditch bucket, compact round design**

with **Lehmatic adapter SW 08**

**2 x 45° tilting angle**, 2 hydraulic cylinders with protected piston rods, with counter-balance valve, base out of 400 HB steel, cutting edge 200x20mm out of Lehborit 5000 (500 HB), lateral water drain bores, with hydraulic hoses up to tilting head.

Surcharge for HS 08V adapter: 1.420,- EUR

Surcharge for SQ60 adapter: 2.302,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1600		-	-	0,440	576	LH242873	<b>7.998,00</b>
1800		-	-	0,500	610	LH232148	<b>8.278,00</b>



**CU 12 G rigid Universal bucket**

with **Symlock adapter SY 08, rigid with backhoe bucket shape**, cutting edge 200x20mm and side edges out of 500 HB steel, base out of 400 HB steel.

Surcharge for HS 08V dirt protection: 41,29 EUR

Surcharge for SQ60 adapter incl. dirt protection: 352,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1400			-	0,560	357	LH279247	<b>2.250,00</b>



**CU 12 GH Universal tilting bucket**

with **Lehmatic adapter SW 08, backhoe bucket shape**

1 hydraulic cylinder, 2 x 45° tilting range, counter-balance valve, hydraulic connections on tilting head, cutting edge 200x20mm and side edges out of 500 HB steel, base of 400 HB steel

Surcharge for HS 08V adapter: 1.420,- EUR

Surcharge for SQ60 adapter: 2.302,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1400			-	0,560	500	LH279249	<b>5.456,00</b>



### CRR 8 Clearing rake

With **Symlock adapter SY08**, for clearing bushes, shrubs and undergrowth, collecting prunings, loosening soil and sorting work in the recycling sector. 4 segments with wear protection made of HB450 steel, cutting edge (500HB) between the segments.

Tooth-radius [mm]	Width [mm]	Teeth	Weight [kg]	PN	Price [€]
850	770	4	265	LH282589	<b>2.823,00</b>



### CRZ 8 bionic Ripper tooth

for demolition and rock use - with Lehmatic adapter SW 08

Option	Tooth point	Angle	Tooth-radius [mm]	Weight [kg]	PN	Price [€]
SW 08	308080	35	750	124	LH225533	<b>1.898,00</b>



### CPG 10 Pallet fork

**Load handling** for all popular pallets, due to adjustable forks, with Lehmatic adapter SW 08.

Width [mm]	Weight [kg/m]	Load capacity [t]	Weight [kg]	PN	Price [€]
1100	1200x100x45	2,4	255	LH218504	<b>2.688,00</b>



### CSG 12 Demolition and sorting grab

Compact height, shells made of Hardox 400, exchangeable turning knives made of Hardox 500, incl. load holding valve, angle of rotation 360° endless, incl. screw adapter SW 08. Gripper shells closed or with grid bars available on request.

Surcharge for HS 08V adapter: 1.570,- EUR

Surcharge for SQ60 adapter: 2.302,- EUR

Opening clearance [mm]	Width [mm]	Capacity SAE [m <sup>3</sup> ]	Grab force [kN]	Weight [kg]	PN	Price [€]
1750	800	0,325	41	920	LH264712	<b>21.772,00</b>



## Attachments for PC138/PW148

**MS 10 Quickcoupler mechanical****for PC138/PW148**

Quickcoupler with mechanical locking, incl. socket wrench, optionally with 8t load hook

Type	Excavator	Option	Weight [kg]	PN	Price [€]
MS 10	PC138/PW148	-	170	LH104566	<b>4.618,00</b>
MS 10	PC138/PW148	Load hook 8t	182	LH107029	<b>4.956,00</b>

**HS 10 DL Quickcoupler hydraulic****for PC138/PW148**

Quickcoupler with hydraulic locking, optionally with 8t load hook.

**With safety locking mechanism Double Lock**

Type	Excavator	Option	Weight [kg]	PN	Price [€]
HS 10 DL	PC138/PW148	-	183	LH278358	<b>6.745,00</b>
HS 10 DL	PC138/PW148	Load hook 8t	201	LH278607	<b>7.083,00</b>

**HS 10V DL Quickcoupler fully hydraulic****for PC138/PW148**

Fully hydraulic Quickcoupler with 2 valves KV3 and 3 valves KV1, two 8 t load hooks and two bolts, valve block's internal depressurizing circuit (BiD) incl., excl. installation kit and installation.

**With safety locking mechanism Double Lock**

Type	Excavator	Option	Weight [kg]	PN	Price [€]
HS 10V DL	PC138/PW148	2x Hook 8t	220	LH278360	<b>15.051,00</b>



### MS 10 - Tilt Quickcoupler Tilt

#### for PC138/PW148

Mechanical quickcoupler with Powertilt motor (PT), with direct suspension. Including 8t load hook.

Excl. optional switch valve, excl. installation on excavator.



Type	Excavator	Option	Tilt-Angle	Weight [kg]	PN	Price [€]
MS 10 - PT 180	PC138/PW148	Hook 8t	2 x 60°	380-400	LH256824	<b>15.700,00</b>
Tilt switch valve		24 V			LH207711	<b>976,00</b>

### HS 10 DL - Tilt Quickcoupler Tilt

#### for PC138/PW148

Hydraulic quickcoupler with Powertilt motor (PT), with direct suspension. Including 8t load hook.

Excl. optional switch valve, excl. installation on excavator.

**With safety locking mechanism Double Lock**



Type	Excavator	Option	Tilt-Angle	Weight [kg]	PN	Price [€]
HS 10 DL - PT 180	PC138/PW148	Hook 8t	2 x 60	410-430	LH282648	<b>18.001,00</b>
Tilt switch valve		24 V			LH207711	<b>976,00</b>

### HS 10V DL - Tilt Quickcoupler Tilt

#### for PC138/PW148

Fully hydraulic quickcoupler with Powertilt motor (PT), with direct suspension. Including 8t load hook.

Excl. optional switch valve, excl. installation on excavator.

**With safety locking mechanism Double Lock**










Type	Excavator	Option	Tilt-Angle	Weight [kg]	PN	Price [€]
HS 10V DL - PT 180	PC138/PW148	2x Hook 8t	2 x 60°	510-550	LH282651	<b>25.102,00</b>
Tilt switch valve		24 V			LH207711	<b>976,00</b>



## Attachments for PC138/PW148











**SW 10 Adapter**

Adapters SW 10 for bucket modification and for welding or screwing on other attachments.

	Description	Weight [kg]	PN	Price [€]
	<b>Adapter plate SW 10</b> for bucket modification	95	LH100526	<b>1.249,00</b>
	<b>Weld-on adapter SW 10</b> for hammers, shears etc. Base plate: 700x545x30mm	200	LH243074	<b>2.052,00</b>
	<b>Screwed adapter SW 10</b> for hammers, shears etc. please specify exact type!	200		<b>2.706,00</b>
	<b>Grab adapter SW 10</b> for hydraulic grabs, with cross bar, please specify exact type!	210		<b>3.196,00</b>
	<b>Universal adapter SW 10</b> <b>W=545mm</b> for individual drilling patterns or welding Base plate 545x715x30mm.	172	LH279156	<b>2.087,00</b>
	<b>Universal adapter SW 10</b> <b>W=605mm</b> for individual drilling patterns or welding Base plate 605x715x30mm.	185	LH269765	<b>2.116,00</b>
	<b>Universal adapter SW 10</b> <b>W=650mm</b> for individual drilling patterns or welding Base plate 650x715x30mm.	190	LH269774	<b>2.174,00</b>

## SW 10V Adapter

Screw-adapter SW 10V with valve configuration (please specify attachment type)

	Description	Weight [kg]	Price [€]
 	<b>Screwed adapter SW 10V</b> for hydraulic hammers valves: 2x KV3, plus installation and hoses	200	<b>4.102,00</b>
 	<b>Screwed adapter SW 10V</b> for cutting units/compactors, valves: 2x KV3, 1x KV1, plus installation and hoses	200	<b>4.425,00</b>
 	<b>Screwed adapter SW 10V</b> for sorting grabs/shears, valves: 2x KV3, 2x KV1, plus installation and hoses	200	<b>4.515,00</b>
 	<b>Screwed adapter SW 10V</b> for rotating compactors, valves: 2x KV3, 3x KV1, plus installation and hoses	200	<b>4.725,00</b>
 	<b>Grab adapter SW 10V</b> for suspended grabs, with cross bar, valves: 2x KV1, 2x KV3, plus installation and hoses	225	<b>4.965,00</b>



## Attachments for PC138/PW148



### SQ 60H LSC Quickcoupler hydraulic, symmetrical for PC138/PW148

Hydraulic symmetrical quickcoupler, based on S-standard, with LSC safety assistance system as standard, One 8 t load hook. Installation kit and installation not included.

Type	Excavator	Option	Weight [kg]	PN	Price [€]
SQ 60H LSC	PC138/PW148	1x Hook 8t		LH283336	<b>6.282,00</b>
LSC install. kit electr.				LH249489	<b>1.069,00</b>



### SQ 60V LSC Quickcoupler fully hydraulic, symmetrical for PC138/PW148

Fully hydraulic symmetrical quickcoupler, based on S standard, with LSC safety assistance system as standard. 2 valves KV3 and 3 valves KV1, one 8 t load hook, incl. valve block's internal depressurization unit (BiD), installation kit and installation not included. Also available as hydraulic version.

Type	Excavator	Option	Weight [kg]	PN	Price [€]
SQ 60V LSC	PC138/PW148	1x Hook 8t	172	LH282666	<b>11.230,00</b>
SQ 60V LSC	PC138/PW148	2x Hook 8t	178	LH282665	<b>11.568,00</b>
LSC install. kit electr.				LH249489	<b>1.069,00</b>








### SQ 60V LSC Quickcoupler Tilt for PC138/PW148

Fully hydraulic symmetrical quickcoupler with Powertilt motor, based on S standard, with LSC safety assistance system as standard. 2 valves KV3 and 3 valves KV1, one 8 t load hook, incl. valve block's internal depressurization unit (BiD), installation kit and installation not included. Also available as hydraulic version.

Type	Excavator	Option	Tilt-Angle	Weight [kg]	PN	Price [€]
<b>SQ 60V LSC - PT180</b>	PC138/PW148	1x Hook 8t	2 x 60	350		<b>22.259,00</b>
LSC install. kit electr.					LH249489	<b>1.069,00</b>

## SQ 60 Adapter






	Description	Weight [kg]	PN	Price [€]
	<b>Adapter Frame SQ 60 for bucket modification</b> for use with SQH60	46	LH283682	<b>802,00</b>
	<b>Adapter Frame SQ 60 for bucket modification</b> incl. SQ valve dirt protection and tacking device, for use with SQH60 & SQ60	49	LH279824	<b>932,00</b>
	<b>Weld-on adapter SQ 60</b> for use with SQH60 for welding on various attachm.	105	LH283676	<b>1.285,00</b>
	<b>Screwed adapter SQ 60</b> for use with SQH60 for hammers, grabs, compactors etc. exact type required!	115		<b>1.745,00</b>
	<b>Universal adapter SQ 60</b> for use with SQH60 for individual drilling patterns, Base plate 445x545x30mm machined and planned.	105	LH283670	<b>1.321,00</b>



## Attachments for PC138/PW148

**SQ 60V Adapter**

Screw-adapter SQ 60 with valve configuration for various attachments (Please specify attachment type)

	Description	Weight [kg]	Price [€]
	<b>Screwed adapter SQ 60V</b> for hydraulic hammers valves: 2x KV3, plus installation and hoses	135	<b>3.478,00</b>
	<b>Screwed adapter SQ 60V</b> for cutting units/compactors valves: 2x KV3, 1x KV1, plus installation and hoses	135	<b>3.725,00</b>
	<b>Screwed adapter SQ 60V</b> for sorting grabs/shears valves: 2x KV3, 2x KV1, plus installation and hoses	135	<b>4.078,00</b>
	<b>Screwed adapter SQ 60V</b> for rotating compactors valves: 2x KV3, 3x KV1, plus installation and hoses	135	<b>3.929,00</b>
	<b>Grab adapter SQ 60V</b> for suspended grabs with cross bar, valves: 2x KV1, 2x KV3, plus installation and hoses	145	<b>4.539,00</b>



### HTL 15 GP General purpose bucket

with direct suspension for PC138/PW148

Cutting edge 250x25mm (500 HB), sandwich constructed base out of 400 HB steel, with tooth system Kprime P015SC.



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
400	Kprime	P015SC	2	0,18	315	LH280789	<b>3.557,00</b>
500	Kprime	P015SC	2	0,25	325	LH280791	<b>3.597,00</b>
600	Kprime	P015SC	3	0,33	367	LH280792	<b>3.662,00</b>
700	Kprime	P015SC	3	0,40	390	LH280793	<b>3.822,00</b>
800	Kprime	P015SC	4	0,48	452	LH280794	<b>4.073,00</b>
900	Kprime	P015SC	4	0,56	475	LH280795	<b>4.245,00</b>
1000	Kprime	P015SC	4	0,64	520	LH280796	<b>4.471,00</b>
1100	Kprime	P015SC	5	0,72	565	LH280797	<b>4.747,00</b>
1200	Kprime	P015SC	5	0,80	610	LH280798	<b>4.998,00</b>
1300	Kprime	P015SC	6	0,89	635	LH280799	<b>5.253,00</b>
1400	Kprime	P015SC	6	0,98	660	LH280800	<b>5.516,00</b>

### HTL 15 GP QC General purpose bucket

with Lehmatic adapter SW 10

Cutting edge 250x25mm (500 HB), sandwich constructed base out of 400 HB steel, with tooth System Kprime P015SC.

Surcharge for HS 10V dirt protection: 241,- EUR

Surcharge for SQ60 adapter incl. dirt protection: 0,- EUR



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
400	Kprime	P015SC	2	0,18	315	LH280801	<b>3.557,00</b>
500	Kprime	P015SC	2	0,25	325	LH280802	<b>3.597,00</b>
600	Kprime	P015SC	3	0,33	367	LH280803	<b>3.662,00</b>
700	Kprime	P015SC	3	0,40	390	LH280804	<b>3.822,00</b>
800	Kprime	P015SC	4	0,48	452	LH280805	<b>4.073,00</b>
900	Kprime	P015SC	4	0,56	475	LH280806	<b>4.245,00</b>
1000	Kprime	P015SC	4	0,64	520	LH280807	<b>4.471,00</b>
1100	Kprime	P015SC	5	0,72	565	LH280808	<b>4.747,00</b>
1200	Kprime	P015SC	5	0,80	610	LH280809	<b>4.747,00</b>
1300	Kprime	P015SC	5	0,89	635	LH280810	<b>4.998,00</b>
1400	Kprime	P015SC	5	0,98	660	LH280811	<b>5.253,00</b>



Attachments for PC138/PW148



**HG 15 S Ditch bucket, rigid version**

optionally with direct suspension for PC138/PW148

or quickcoupler suspension SW 10. Round bucket shape, base out of 400 HB steel, cutting edge 200x20mm out of Lehbortit 5000 (500 HB), with lateral water drain bores and rear cutting edge.

Surcharge for HS 10V dirt protection: 241,- EUR

Surcharge for SQ60 adapter incl. dirt protection: 0,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1800	Direct Susp.	-	-	0,50	320	LH253748	<b>3.896,00</b>
1800	SW 10	-	-	0,50	320	LH253747	<b>3.896,00</b>
2000	Direct Susp.	-	-	0,56	490	LH253749	<b>4.030,00</b>
2000	SW 10	-	-	0,56	490	LH245440	<b>4.030,00</b>



**HG 15 SH Tilting ditch bucket, compact round design**

optionally with direct suspension for PC138/PW148

or quickcoupler suspension SW 10. 2 x 45° tilting angle, 2 hydraulic cylinders with protected piston rods, with counter-balance valve, base out of 400 HB steel, cutting edge 200x20mm out of 500 HB steel, with lateral water drain bores and rear cutting edge, with hydraulic hoses up to tilting head.

Surcharge for HS10V adapter: 2.667,- EUR

Surcharge for SQ60V adapter: 1.982,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1800	Direct Susp.	-	-	0,50	655	LH230455	<b>8.757,00</b>
1800	SW 10	-	-	0,50	655	LH228489	<b>8.757,00</b>
2000	Direct Susp.	-	-	0,56	720	LH253750	<b>9.076,00</b>
2000	SW 10	-	-	0,56	720	LH227119	<b>9.076,00</b>



**HP 15 Grading bucket**

especially for use with rotators/tilt-rotators, with Lehmatic adapter SW10

45° conical side walls, cutting edge 200x25mm out of 500 HB steel, base out of 400 HB steel, wear resistant plates out of 400 HB

Surcharge for HS 10V dirt protection: 241,- EUR

Surcharge for SQ60 adapter incl. dirt protection: 0,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1400			-	0,620	437	on demand	<b>0,00</b>



### HU 15 R Universal bucket

**backhoe bucket shape with round side part with quickcoupler suspension SW 10**

base out of 400 HB steel, cutting edge 200x25mm out of 500 HB steel

Surcharge for HS 10V dirt protection: 241,- EUR

Surcharge for SQ60 adapter incl. dirt protection: 0,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1400			-	0,680	445	LH232655	<b>4.227,00</b>
1500			-	0,730	480	LH215541	<b>4.403,00</b>



### HU 15 RH Universal tilting bucket

**backhoe bucket shape with round side part with quickcoupler suspension SW 10**

2 x 45° tilting range, 2 hydraulic cylinders with protected piston rods and pressurizing valve, base of 400 HB steel, cutting edge 200x25mm of Lehbort 5000 (500 HB), with hydraulic hoses up to tilting head

Surcharge for HS10V adapter: 2.667,- EUR

Surcharge for SQ60V adapter: 1.982,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1400	SW 10	-	-	0,680	680	LH232144	<b>8.877,00</b>
1500	SW 10	-	-	0,730	697	LH232146	<b>9.124,00</b>



### HU 15 RM Universal tilting bucket

**backhoe bucket shape with round side part with quickcoupler suspension SW 10**

2 x 45° tilting range, with hydraulic tilt motor, base out of 400 HB steel, cutting edge 200x25mm out of Lehbort 5000 (500 HB).

Surcharge for HS10V adapter: 2.667,- EUR

Surcharge for SQ60V adapter: 1.982,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1400	SW 10	-	-	0,680	660	LH237435	<b>11.684,00</b>
1500	SW 10	-	-	0,730	720	LH242512	<b>11.932,00</b>



Attachments for PC138/PW148



**HSL 15 Sorting bucket with rectangular bars with Lehmatic adapter SW 10**

Base made of solid rectangular bars 40x25mm, 60mm spacing, cutting edge 250x30mm (500 HB), side edges (400 HB), with teeth Kprime P015SC.

Surcharge for HS 10V dirt protection: 241,- EUR

Surcharge for SQ60 adapter incl. dirt protection: 0,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1200	Kprime	P015SC	5	0,800	646	LH282494	<b>7.176,00</b>



**HSL 15 Sorting bucket round bars**

**with Symlock adapter SW 10**

Base with round bars D30 made of 400HB steel, 60mm hole width, cutting edge 250x30mm (500 HB), side edges (400 HB), with teeth Kprime P015SC.

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1200		P015SC	5	0,800	646		



**HRZ 18 bionic Ripper tooth**

for demolition and rock use - with Lehmatic adapter SW 10

Option	Tooth point	Angle	Tooth-radius [mm]	Weight [kg]	PN	Price [€]
SW 10	K030RC	35	950	274	LH227750	<b>4.457,00</b>



**HSG 15 Demolition and sorting grab**

compact design, grab shells out of Hardox 400, interchangeable cutting edges out of Hardox 500, incl. counter-balance valve, rotating angle 360° endless, incl. screwed Lehmatic adapter SW 10. Grab shells closed or with rectangular bars on demand.

Surcharge for HS10V adapter: 1.810,- EUR

Surcharge for SQ60V adapter: 1.244,- EUR

Opening clearance [mm]	Width [mm]	Capacity SAE [m <sup>3</sup> ]	Grab force [kN]	Weight [kg]	PN	Price [€]
1750	800	0,325	41	1070	LH264713	<b>23.353,00</b>



### HSG 15V Demolition and sorting grab

With integrated SW 10V adapter, ready for use, approx. 10% weight saving and lower overall height, grab shells out of Hardox 400, interchangeable cutting edges out of Hardox 500, incl. counter-balance valve, rotating angle 360° endless, grab shells closed or with rectangular bars on demand.



Opening clearance [mm]	Width [mm]	Capacity SAE [m³]	Grab force [kN]	Weight [kg]	PN	Price [€]
1750	800	0,325	41	1070	LH271764	<b>25.774,00</b>



## Attachments for PW158/PW160/PW168/PC170/PW180/PW198

**MS 10 Quickcoupler mechanical****for PW158-PW198**

Quickcoupler with mechanical locking, incl. socket wrench, optionally with 8t load hook

Type	Excavator	Option	Weight [kg]	PN	Price [€]
MS 10	PW158-PW168	-	170	LH104566	<b>4.618,00</b>
MS 10	PW158-PW168	Load hook 8t	182	LH107029	<b>4.956,00</b>
MS 10	PC170-PW198	-	170	LH104623	<b>4.618,00</b>
MS 10	PC170-PW198	Load hook 8t	182	LH116809	<b>4.956,00</b>

**HS 10 DL Quickcoupler hydraulic****for PW158-PW198**

Quickcoupler with hydraulic locking, optionally with 8t load hook.  
With safety locking mechanism **Double Lock**

Type	Excavator	Option	Weight [kg]	PN	Price [€]
HS 10 DL	PW158-PW168	-	183	LH278358	<b>6.745,00</b>
HS 10 DL	PW158-PW168	Load hook 8t	201	LH278607	<b>7.083,00</b>
HS 10 DL	PC170-PW198	-	170	LH282652	<b>6.745,00</b>
HS 10 DL	PC170-PW198	Load hook 8t	170	LH278635	<b>7.083,00</b>

**HS 10V DL Quickcoupler fully hydraulic****for PW158-PW198**

Fully hydraulic Quickcoupler with 2 valves KV3 and 3 valves KV1, two 8 t load hooks and two bolts, valve block's internal depressurizing circuit (BiD) incl., excl. installation kit and installation.

With safety locking mechanism **Double Lock**

Type	Excavator	Option	Weight [kg]	PN	Price [€]
HS 10V DL	PW158-PW168	2x Hook 8t	220	LH278360	<b>15.051,00</b>
HS 10V DL	PC170-PW198	2x Hook 8t	220	LH278684	<b>15.051,00</b>



### MS 10 - Tilt Quickcoupler Tilt

#### for PW158-PC198

Mechanical quickcoupler with Powertilt motor (PT), with direct suspension. Including 8t load hook.

Excl. optional switch valve, excl. installation on excavator.



Type	Excavator	Option	Tilt-Angle	Weight [kg]	PN	Price [€]
MS 10 - PT 180	PW158-PW168	Hook 8t	2 x 60°	380-400	LH256824	<b>15.700,00</b>
MS 10 - PT 180	PC170-PW198	Hook 8t	2 x 60°	380-400	LH268182	<b>15.700,00</b>
Tilt switch valve		24 V			LH207711	<b>976,00</b>

### HS 10 DL - Tilt Quickcoupler Tilt

#### for PW158-PW198

Hydraulic quickcoupler with Powertilt motor (PT) with direct suspension. Including 8t load hook.

Excl. optional switch valve, excl. installation on excavator.

**NEW: With safety locking mechanism Double Lock**



Type	Excavator	Option	Tilt-Angle	Weight [kg]	PN	Price [€]
HS 10 DL - PT 180	PW158-PW168	Hook 8t	2 x 60°	410-430	LH282648	<b>18.001,00</b>
HS 10 DL - PT 180	PC170-PW198	Hook 8t	2 x 60°	410-430	LH282653	<b>18.001,00</b>
Tilt switch valve		24 V			LH207711	<b>976,00</b>


### HS 10V DL - Tilt Quickcoupler Tilt

#### for PW158-PW198

Fully hydraulic quickcoupler with Powertilt motor (PT), with direct suspension. Including 8t load hook.

Excl. optional switch valve, excl. installation on excavator.

**With safety locking mechanism Double Lock**










Type	Excavator	Option	Tilt-Angle	Weight [kg]	PN	Price [€]
HS 10V DL - PT 180	PW158-PW168	2x Hook 8t	2 x 60°	510-550	LH282651	<b>25.102,00</b>
HS 10V DL - PT 180	PC170-PW198	2x Hook 8t	2 x 60°	510-550	LH282656	<b>25.102,00</b>
Tilt switch valve		24 V			LH207711	<b>976,00</b>





## SW 10 Adapter






Adapters SW 10 for bucket modification and for welding or screwing on other attachments.

	Description	Weight [kg]	PN	Price [€]
	<b>Adapter plate SW 10</b> for bucket modification	95	LH100526	<b>1.249,00</b>
	<b>Weld-on adapter SW 10</b> for hammers, shears etc. Base plate: 700x545x30mm	200	LH243074	<b>2.052,00</b>
	<b>Screwed adapter SW 10</b> for hammers, shears etc. please specify exact type!	200		<b>2.706,00</b>
	<b>Grab adapter SW 10</b> for hydraulic grabs, with cross bar, please specify exact type!	210		<b>3.196,00</b>
	<b>Universal adapter SW 10</b> <b>W=545mm</b> for individual drilling patterns or welding Base plate 545x715x30mm.	172	LH279156	<b>2.087,00</b>
	<b>Universal adapter SW 10</b> <b>W=605mm</b> for individual drilling patterns or welding Base plate 605x715x30mm.	185	LH269765	<b>2.116,00</b>
	<b>Universal adapter SW 10</b> <b>W=650mm</b> for individual drilling patterns or welding Base plate 650x715x30mm.	190	LH269774	<b>2.174,00</b>



## SW 10V Adapter

Screw-adapter SW 10V with valve configuration (please specify attachment type)

	Description	Weight [kg]	Price [€]
	<b>Screwed adapter SW 10V</b> for hydraulic hammers valves: 2x KV3, plus installation and hoses	200	<b>4.102,00</b>
	<b>Screwed adapter SW 10V</b> for cutting units/compactors, valves: 2x KV3, 1x KV1, plus installation and hoses	200	<b>4.425,00</b>
	<b>Screwed adapter SW 10V</b> for sorting grabs/shears, valves: 2x KV3, 2x KV1, plus installation and hoses	200	<b>4.515,00</b>
	<b>Screwed adapter SW 10V</b> for rotating compactors, valves: 2x KV3, 3x KV1, plus installation and hoses	200	<b>4.725,00</b>
	<b>Grab adapter SW 10V</b> for suspended grabs, with cross bar, valves: 2x KV1, 2x KV3, plus installation and hoses	225	<b>4.965,00</b>



### SQ 70-2H LSC Quickcoupler hydraulic, symmetrical for PW158-PW198

Hydraulic symmetrical quickcoupler, based on S-standard, with LSC safety assistance system as standard. one 10 t load hook, installation kit and installation not included.

Type	Excavator	Option	Weight [kg]	PN	Price [€]
SQ 70-2H LSC	PW158-PW168	Load Hook 10t	271	LH295346	<b>10.394,00</b>
SQ 70-2H LSC	PC170-PW198	Load Hook 10t	271	LH295342	<b>10.394,00</b>
LSC install. kit electr.				LH249489	<b>1.069,00</b>



### SQ 70/55H LSC Quickcoupler hydraulic, symmetrical for PC170-PW198

Hydraulic symmetrical quickcoupler, based on S-standard, width 550mm, with LSC safety assistance system as standard. one 10 t load hook, installation kit and installation not included.

Type	Excavator	Option	Weight [kg]	PN	Price [€]
SQ 70/55H LSC	PW180/PC170	Load Hook 10t	328	LH295344	<b>11.016,00</b>
LSC install. kit electr.				LH249489	<b>1.069,00</b>



### SQ 70-2V LSC Quickcoupler fully hydraulic, symmetrical for PW158-PW198

Fully hydraulic symmetrical quickcoupler, based on S-standard, with LSC safety assistance system as standard. 2 valves KV4, 1 valve KV3 and 2 valves KV1, one 10 t load hook, incl. valve block's internal depressurization unit (BiD), installation kit and installation not included. Also available as hydraulic or mechanical version.

Type	Excavator	Option	Weight [kg]	PN	Price [€]
SQ 70-2V LSC	PW158-PW168	Hook 10t	298	LH295347	<b>14.195,00</b>
SQ 70-2V LSC	PW158-PW168	2x Hook 10t	306	LH295349	<b>14.642,00</b>
SQ 70-2V LSC 1LH	PC170-PW198	Load Hook 10t	302	LH295343	<b>14.195,00</b>
SQ 70-2V LSC	PC170-PW198	2x Hook 10t	312	LH295350	<b>14.642,00</b>
LSC install. kit electr.				LH249489	<b>1.069,00</b>



### SQ 70/55V LSC Quickcoupler fully hydraulic, symmetrical for PC170-PW198






Fully hydraulic symmetrical quickcoupler, based on S-standard, width 550mm, with LSC safety assistance system as standard. 2 valves KV4, 1 valve KV3 and 2 valves KV1, one 10 t load hook, incl. valve block's internal depressurization unit (BiD), installation kit and installation not included. Also available as hydraulic or mechanical version.



Type	Excavator	Option	Weight [kg]	PN	Price [€]
SQ 70/55V LSC	PC170-PW198	Load Hook 10t	344	LH295345	<b>15.090,00</b>
SQ 70/55V LSC	PC170-PW198	2x Hook 10t	354	LH295351	<b>15.552,00</b>
LSC install. kit electr.				LH249489	<b>1.069,00</b>

### SQ 70 Adapter






Adapters SQ 70 for bucket modification and for screwing or welding on other attachments

Description	Weight [kg]	PN	Price [€]
 <b>Adapter Frame SQ 70 for bucket modification</b> for use with SQ 70H	91	283681	<b>1.056,00</b>
 <b>Adapter Frame SQ 70 for bucket modification</b> incl. SQ valve dirt protection and tacking device. For use with SQ 70V	96	273091	<b>1.292,00</b>
 <b>Weld-on adapter SQ 70</b> for welding on various attachm. For use with SQ 70H/70V	210	283677	<b>1.627,00</b>
 <b>Screwed adapter SQ 70 for hammers, grabs, compactors etc.</b> exact type required! For use with SQ 70H/70V	215		<b>2.229,00</b>
 <b>Universal adapter SQ 70</b> for individual drilling patterns, base plate 570x750x35mm machined and planned. For use with SQ 70H/70V	210	283672	<b>1.662,00</b>








## SQ 70V Adapter

Screw-adapter SQ 70 with valve configuration for various attachments (Please specify attachment type)

	Description	Weight [kg]	Price [€]
	<b>Screwed adapter SQ 70V for hydraulic hammers</b> valves: 2x KV4, plus installation and hoses	235	<b>4.397,00</b>
	<b>Screwed adapter SQ 70V for cutting units/compactors</b> valves: 2x KV4, 1x KV3, plus installation and hoses	235	<b>4.586,00</b>
	<b>Screwed adapter SQ 70V for sorting grabs/shears</b> valves: 2x KV4, 2x KV1, plus installation and hoses	235	<b>5.011,00</b>
	<b>Screwed adapter SQ 70V for rotating compactors</b> valves: 2x KV4, 2x KV1, 1x KV3, plus installation and hoses	235	<b>5.247,00</b>
	<b>Grab adapter SQ 70V for suspended grabs, with cross bar</b>	250	<b>5.482,00</b>

## SQ 70/55 Adapter






Adapters SQ 70/55 for bucket modification and for screwing or welding on other attachments

	Description	Weight [kg]	PN	Price [€]
	<b>Adapter Frame SQ 70/55 for bucket modification</b> for use with SQ 70/55H	101	LH283681	<b>1.119,00</b>
	<b>Adapter Frame SQ 70/55 for bucket modification</b> incl. SQ valve dirt protection and tacking device, for use with SQ 70/55V	104	LH273091	<b>1.369,00</b>
	<b>Weld-on adapter SQ 70/55</b> for use with SQ70/55 H/V for welding on various attachm.	221	LH283677	<b>1.724,00</b>
	<b>Screwed adapter SQ 70/55 for hammers, grabs, compactors etc.</b> SQ 70/55H	215		<b>2.362,00</b>
	<b>Universal adapter SQ 70/55</b> for use with SQ70/55 H/V , for individual drilling patterns, base plate 570x750x35mm machined and planned.	225	LH283672	<b>1.762,00</b>



## SQ 70/55V Adapter

Screw-adapter SQ 70/55V with valve configuration for various attachments (Please specify attachment type)

	Description	Weight [kg]	Price [€]
	<b>Screwed adapter SQ 70/55V for hydraulic hammers</b> valves: 2x KV4, plus installation and hoses	260	4.660,00
	<b>Screwed adapter SQ 70/55V for cutting units/compactors</b> , valves: 2x KV4, 1x KV3, plus installation and hoses	260	4.861,00
	<b>Screwed adapter SQ 70/55V for sorting grabs/shears</b> valves: 2x KV4, 2x KV1, plus installation and hoses	260	5.311,00
	<b>Screwed adapter SQ 70/55V for rotating compactors</b> valves: 2x KV4, 2x KV1, 1x KV3, plus installation and hoses	260	5.562,00
	<b>Grab adapter SQ 70/55V for suspended grabs, with cross bar</b> valves: 2x KV1, 2x KV4, plus installation and hoses	275	5.810,00



### HTL 20 GP General purpose bucket

with direct suspension for PW158/PW160/PW180/PC170

Cutting edge 250x30mm (500 HB), sandwich constructed base out of 400 HB steel, with tooth system Kprime P020SC



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
500	Kprime	P020SC	2	0,30	365	LH280812	<b>3.769,00</b>
600	Kprime	P020SC	3	0,38	380	LH280813	<b>3.943,00</b>
700	Kprime	P020SC	3	0,47	457	LH280814	<b>4.128,00</b>
800	Kprime	P020SC	3	0,56	500	LH280815	<b>4.350,00</b>
900	Kprime	P020SC	4	0,66	535	LH280816	<b>4.575,00</b>
1000	Kprime	P020SC	4	0,75	600	LH280817	<b>4.747,00</b>
1100	Kprime	P020SC	4	0,85	640	LH280818	<b>5.118,00</b>
1200	Kprime	P020SC	5	0,94	680	LH280819	<b>5.316,00</b>
1300	Kprime	P020SC	5	1,04	743	LH280820	<b>5.670,00</b>
1400	Kprime	P020SC	5	1,13	770	LH280821	<b>5.804,00</b>

### HTL 20 GP QC General purpose bucket

with Lehmatic adapter SW 10

Cutting edge 250x30mm (500 HB), sandwich constructed base out of 400 HB steel, with tooth system Kprime P020SC.

Surcharge for HS10V dirt protection: 241,- EUR

Surcharge for SQ70 adapter incl. dirt protection: 180,- EUR



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
500	Kprime	P020SC	2	0,30	365	LH280822	<b>3.769,00</b>
600	Kprime	P020SC	3	0,38	380	LH280824	<b>3.943,00</b>
700	Kprime	P020SC	3	0,47	457	LH280825	<b>4.128,00</b>
800	Kprime	P020SC	3	0,56	500	LH280826	<b>4.350,00</b>
900	Kprime	P020SC	4	0,66	535	LH280827	<b>4.575,00</b>
1000	Kprime	P020SC	4	0,75	600	LH280829	<b>4.747,00</b>
1100	Kprime	P020SC	4	0,85	640	LH280830	<b>5.118,00</b>
1200	Kprime	P020SC	5	0,94	680	LH280831	<b>5.316,00</b>
1300	Kprime	P020SC	5	1,04	743	LH280832	<b>5.670,00</b>
1400	Kprime	P020SC	5	1,13	770	LH280833	<b>5.804,00</b>





### HG 20 S Ditch bucket, rigid version

optionally with direct suspension for PW158/PW160/PW180/PC170 or quickcoupler suspension SW 10. Round bucket shape, base out of 400 HB steel, cutting edge 200x25mm out of 500 HB steel, with lateral water drain bores and rear cutting edge.  
Surcharge for HS10V protection: 241,- EUR  
Surcharge for SQ70 adapter incl. dirt protection: 180,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1800	Direct Susp.	-	-	0,60	480	LH231041	4.041,00
1800	SW 10	-	-	0,60	480	LH226680	4.041,00
2000	Direct Susp.	-	-	0,66	540	LH253771	4.312,00
2000	SW 10	-	-	0,66	540	LH253770	4.312,00



### HG 20 SH Tilting ditch bucket, compact round design

optionally with direct suspension for PW158/PW160/PW180/PC170 or quickcoupler suspension SW 10. 2 x 45° tilting angle, 2 hydraulic cylinders with protected piston rods, with counter-balance valve, base out of 400 HB steel, cutting edge 200x25mm out of Lehbort 5000 (500 HB), with lateral water drain bores and rear cutting edge, with hydraulic hoses up to tilting head.  
Surcharge for HS10V adapter: 2.667,- EUR  
Surcharge for SQ70V adapter: 2.823,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1800	Direct Susp.	-	-	0,60	698	on demand	0,00
1800	SW 10	-	-	0,60	698	LH232137	9.014,00
2000	Direct Susp.	-	-	0,66	740	LH253773	9.173,00
2000	SW 10	-	-	0,66	740	LH232000	9.173,00



### HP 20 Grading bucket

especially for use with rotators/tilt-rotators, with Lehmatic adapter SW10  
45° conical side walls, cutting edge 250x30mm out of 500 HB steel, base out of 400 HB steel, wear resistant plates out of 400 HB  
Surcharge for HS10V protection: 241,- EUR  
Surcharge for SQ70 adapter incl. dirt protection: 180,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1600			-	0,820	533	on demand	0,00



### HU 20 R Universal bucket

**backhoe bucket shape with round side part with quickcoupler suspension SW 10**

base out of 400 HB steel, cutting edge 250x30mm out of 500 HB steel.

Surcharge for HS 10V dirt protection: 241,- EUR

Surcharge for SQ70 adapter incl. dirt protection: 180,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1400			-	0,800	515	LH232770	<b>4.940,00</b>
1500			-	0,870	560	LH217481	<b>5.194,00</b>



### HU 20 RH Universal tilting bucket

**backhoe bucket shape with round side part with quickcoupler suspension SW 10**

2 x 45° tilting range, 2 hydraulic cylinders with protected piston rods and pressurizing valve, base out of 400 HB steel, cutting edge 250x30mm out of Lehbort 5000 (500 HB), robust version, with hydraulic hoses up to tilting head.

Surcharge for HS10V adapter: 2.667,- EUR

Surcharge for SQ70V adapter: 2.823,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1400	SW 10	-	-	0,800	725	LH232140	<b>10.340,00</b>
1500	SW 10	-	-	0,870	735	LH235251	<b>10.617,00</b>



### HU 20 RM Universal tilting bucket

**backhoe bucket shape with round side part with quickcoupler suspension SW 10**

2 x 45° tilting range, with hydraulic tilt motor, base out of 400 HB steel, cutting edge 250x30mm out of Lehbort 5000 (500 HB), robust version.

Surcharge for HS10V adapter: 2.667,- EUR

Surcharge for SQ70V adapter: 2.823,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1400	SW 10	-	-	0,800	858	LH242516	<b>14.882,00</b>
1500	SW 10	-	-	0,870	880	LH242517	<b>15.005,00</b>



**HSL 20 Sorting bucket with rectangular bars  
with Lehmatic adapter SW 10**

Base made of solid rectangular bars 40x25mm, 60mm spacing, cutting edge 250x30mm (500 HB), side edges (400 HB), with teeth Kprime P020SC

Surcharge for HS10V dirt protection: 241,- EUR

Surcharge for SQ70 adapter incl. dirt protection: 180,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1200	Kprime	P020SC	5	0,940	710	LH282495	<b>7.468,00</b>



**HSL 20 Sorting bucket round bars  
with Symlock adapter SW 10**

Base with round bars D40 made of 400HB steel, 60mm hole width, cutting edge 250x30mm (500 HB), side edges (400 HB), with teeth Kprime P020SC.

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1200		P020SC	5	0,940	710	LH	



**HRZ 18 bionic Ripper tooth**

for demolition and rock use - with Lehmatic adapter SW 10

Option	Tooth point	Angle	Tooth-radius [mm]	Weight [kg]	PN	Price [€]
SW 10	K030RC	35	950	274	LH227750	<b>4.457,00</b>



### HSG 20 Demolition and sorting grab

compact design, grab shells out of Hardox 400, interchangeable cutting edges out of Hardox 500, incl. counter-balance valve, rotating angle 360° endless, incl. screwed Lehmatic adapter SW 10. Grab shells closed or with rectangular bars on demand.  
 Surcharge for HS10V adapter: 1.810,- EUR  
 Surcharge for SQ70V adapter: 2.238,- EUR



Opening clearance [mm]	Width [mm]	Capacity SAE [m <sup>3</sup> ]	Grab force [kN]	Weight [kg]	PN	Price [€]
1830	900	0,400	41	1215	LH264714	<b>25.177,00</b>

### HSG 20V Demolition and sorting grab

**With integrated SW 10V adapter, ready for use**, approx. 10% weight saving and lower overall height, grab shells out of Hardox 400, interchangeable cutting edges out of Hardox 500, incl. counter-balance valve, rotating angle 360° endless, grab shells closed or with rectangular bars on demand.



Opening clearance [mm]	Width [mm]	Capacity SAE [m <sup>3</sup> ]	Grab force [kN]	Weight [kg]	PN	Price [€]
1830	900	0,400	41	1215	LH271766	<b>27.505,00</b>



## Attachments for PC210/PC228

**MS 21 Quickcoupler mechanical****for PC210/PC228**

Quickcoupler with mechanical locking, incl. socket wrench, optionally with 10t load hook

Type	Excavator	Option	Weight [kg]	PN	Price [€]
MS 21	PC210-PC240	-	270	LH104618	<b>7.184,00</b>
MS 21	PC210-PC240	Load hook 10t	280	LH105219	<b>7.631,00</b>

**HS 21 DL Quickcoupler hydraulic****for PC210/PC228**

Quickcoupler with hydraulic locking, with 10t load hook.

**With safety locking mechanism Double Lock**

Type	Excavator	Option	Weight [kg]	PN	Price [€]
HS 21 DL	PC210-PC240	Load hook 10t	280	LH281636	<b>9.795,00</b>

**HS 21V DL Quickcoupler fully hydraulic****for PC210/PC228**

Fully hydraulic Quickcoupler with 2 valves KV4, 1 valve KV3, 2 valves KV1, two 10 t load hooks, valve block's internal depressurizing circuit (BiD) incl., hoses from valve block to flange, excl. hydr. installation kit and installation.

**With safety locking mechanism Double Lock**

Type	Excavator	Option	Weight [kg]	PN	Price [€]
HS 21 DL	PC210-PC240	2x Load hook 10t	280	LH284281	<b>17.844,00</b>



### MS 21 - Tilt Quickcoupler Tilt

#### for PC210/PC228

Mechanical quickcoupler with Powertilt motor (PT), with direct suspension. Including 10t load hook.

Excl. optional switch valve, excl. installation on excavator.



Type	Excavator	Option	Tilt-Angle	Weight [kg]	PN	Price [€]
MS 21 - PT 240	PC210/PC228	Hook 10t	2 x 60°	570-590	LH255517	<b>18.130,00</b>
Tilt switch valve		24 V			LH207711	<b>976,00</b>

### HS 21 DL - Tilt Quickcoupler Tilt

#### for PC210/PC228

Hydraulic quickcoupler with Powertilt motor (PT), with direct suspension. Including 10t load hook.

Excl. optional switch valve, excl. installation on excavator.

**With safety locking mechanism Double Lock**



Type	Excavator	Option	Tilt-Angle	Weight [kg]	PN	Price [€]
HS 21 DL - PT 240	PC210/PC228	Hook 10t	2 x 60°	590-630	LH286715	<b>19.964,00</b>
Tilt switch valve		24 V			LH207711	<b>976,00</b>

### HS 21V DL - Tilt Quickcoupler Tilt

#### for PC210/PC228

Fully hydraulic quickcoupler with Powertilt motor (PT), with direct suspension. Including 10t load hook. Excl. optional switch valve, excl. installation on excavator.

**With safety locking mechanism Double Lock**



Abb. ähnlich

Type	Excavator	Option	Tilt-Angle	Weight [kg]	PN	Price [€]
HS 21V DL - PT 240	PC210/PC228	2x Hook 10t	2 x 60°	790-850	LH286870	<b>29.466,00</b>
Tilt switch valve		24 V			LH207711	<b>976,00</b>



## Attachments for PC210/PC228






**SW 21/25 Adapter**

Adapters SW 21/25 for bucket modification and for screwing or welding on other attachments.

	Description	Weight [kg]	PN	Price [€]
	<b>Adapter plate SW 21/25 -standard-</b> for bucket modification, Base plate: 600x530x30mm	147	LH100577	<b>1.664,00</b>
	<b>Adapter plate SW 21/25 HD -reinforced-</b> for bucket modification, Base plate: 700x550x40mm	188	LH257849	<b>2.237,00</b>
	<b>Weld-on adapter SW 21/25</b> for hammers, shears etc. Base plate: 752x665x40mm	250	LH238536	<b>2.959,00</b>
	<b>Screwed adapter SW 21/25 -standard-</b> for hammers, shears etc.	250		<b>3.386,00</b>
	<b>Screwed adapter SW 21/25 HD -reinforced-</b> for hammers, shears etc.	300		<b>4.403,00</b>
	<b>Grab adapter SW 21/25</b> for hydraulic grabs, with cross bar	205		<b>3.717,00</b>
	<b>Universal adapter SW 21/25 W=665mm</b> for individual drilling patterns or welding Base plate 665x752x40mm, Bottom side machined and planned.	300	LH279159	<b>2.988,00</b>
	<b>Universal adapter SW 21/25 W=735mm</b> for individual drilling patterns or welding Base plate 735x752x40mm, Bottom side machined and planned.	310	LH269783	<b>3.024,00</b>
	<b>Universal adapter SW 21/25 B=755mm</b> for individual drilling patterns or welding Base plate 755x752x40mm, Bottom side machined and planned.	320	LH269805	<b>3.082,00</b>

### SW 21V/25V Adapter

Screw-adapter SW 21V/25V with valve configuration for various attachments (Please specify attachment type)

	Description	Weight [kg]	Price [€]
	<b>Screwed adapter SW 21V/25V</b> for hydraulic hammers, valves: 2x KV4, plus installation and hoses	316	<b>4.794,00</b>
	<b>Screwed adapter SW 21V/25V</b> for sorting grabs/shears, valves: 2x KV4, 2x KV1, plus installation and hoses	316	<b>5.336,00</b>
	<b>Screwed adapter HS 21V/25V</b> for cutting units/compactors, valves: 2x KV4, 1x KV3, plus installation and hoses	316	<b>5.336,00</b>
	<b>Screwed adapter SW 21V/25V</b> for rotating compactors, valves: 2x KV4, 2x KV1, 1x KV3, plus installation and hoses	316	<b>5.459,00</b>
	<b>Grab adapter SW 21V/25V</b> for suspended grabs, with cross bar, valves: 2x KV1, 2x KV4, plus installation and hoses	250	<b>5.324,00</b>





## Attachments for PC210/PC228



### SQ 70-2H LSC Quickcoupler hydraulic, symmetrical for PC210-PC240

symmetrical quickcoupler, based on S-standard, with LSC safety assistance system as standard. one 10 t load hook, installation kit and installation not included.

Type	Excavator	Option	Weight [kg]	PN	Price [€]
SQ 70-2H LSC	PC210-PC240	Load Hook 10t	288	LH295341	<b>10.394,00</b>
LSC install. kit electr.				LH249489	<b>1.069,00</b>



### SQ 70/55H LSC Quickcoupler hydraulic, symmetrical for PC210-PC240

symmetrical quickcoupler, based on S-standard, width 550mm, with LSC safety assistance system as standard. one 10 t load hook, installation kit and installation not included.

Type	Excavator	Option	Weight [kg]	PN	Price [€]
SQ 70/55H LSC	PC210-PC240	Load Hook 10t	330	LH295338	<b>11.016,00</b>
LSC install. kit electr.				LH249489	<b>1.069,00</b>



### SQ 70-2V LSC Quickcoupler fully hydraulic, symmetrical for PC210/PC240

Fully hydraulic symmetrical quickcoupler, based on S-standard, with LSC safety assistance system as standard. 2 valves KV4, 1 valve KV3 and 2 valves KV1, one 10 t load hook, incl. valve block's internal depressurization unit (BiD), installation kit and installation not included. Also available as hydraulic or mechanical version.

Type	Excavator	Option	Weight [kg]	PN	Price [€]
SQ 70-2V LSC	PC210-PC240	Load Hook 10t	305	LH294053	<b>14.195,00</b>
SQ 70-2V LSC	PC210-PC240	2x Hook 10t	315	LH294352	<b>14.642,00</b>
LSC install. kit electr.				LH249489	<b>1.069,00</b>



### SQ 70/55V LSC Quickcoupler fully hydraulic, symmetrical for PC210/PC240






Fully hydraulic symmetrical quickcoupler, based on S-standard, width 550mm, with LSC safety assistance system as standard. 2 valves KV4, 1 valve KV3 and 2 valves KV1, one 10 t load hook, incl. valve block's internal depressurization unit (BiD), installation kit and installation not included. Also available as hydraulic or mechanical version.



Type	Excavator	Option	Weight [kg]	PN	Price [€]
SQ 70/55V LSC	PC210-PC240	Load Hook 10t	344	LH295337	<b>15.090,00</b>
SQ 70/55V LSC	PC210-PC240	2x Hook 10t	354	LH295353	<b>15.552,00</b>
LSC install. kit electr.				LH249489	<b>1.069,00</b>

### SQ 70 Adapter

Adapters SQ 70 for bucket modification and for screwing or welding on other attachments






Description	Weight [kg]	PN	Price [€]
 <b>Adapter Frame SQ 70 for bucket modification</b> for use with SQ 70H	91	283681	<b>1.056,00</b>
 <b>Adapter Frame SQ 70 for bucket modification</b> incl. SQ valve dirt protection and tacking device. For use with SQ 70V	96	273091	<b>1.292,00</b>
 <b>Weld-on adapter SQ 70</b> for welding on various attachm. For use with SQ 70H/70V	210	283677	<b>1.627,00</b>
 <b>Screwed adapter SQ 70 for hammers, grabs, compactors etc.</b> exact type required! For use with SQ 70H/70V	215		<b>2.229,00</b>
 <b>Universal adapter SQ 70</b> for individual drilling patterns, base plate 570x750x35mm machined and planned. For use with SQ 70H/70V	210	283672	<b>1.662,00</b>



## Attachments for PC210/PC228






**SQ 70V Adapter**

Screw-adapter SQ 70 with valve configuration for various attachments (Please specify attachment type)

	Description	Weight [kg]	Price [€]
	<b>Screwed adapter SQ 70V for hydraulic hammers</b> valves: 2x KV4, plus installation and hoses	235	<b>4.397,00</b>
	<b>Screwed adapter SQ 70V for cutting units/compactors</b> valves: 2x KV4, 1x KV3, plus installation and hoses	235	<b>4.586,00</b>
	<b>Screwed adapter SQ 70V for sorting grabs/shears</b> valves: 2x KV4, 2x KV1, plus installation and hoses	235	<b>5.011,00</b>
	<b>Screwed adapter SQ 70V for rotating compactors</b> valves: 2x KV4, 2x KV1, 1x KV3, plus installation and hoses	235	<b>5.247,00</b>
	<b>Grab adapter SQ 70V for suspended grabs, with cross bar</b>	250	<b>5.482,00</b>

### SQ 70/55 Adapter

Adapters SQ 70/55 for bucket modification and for screwing or welding on other attachments






	Description	Weight [kg]	PN	Price [€]
	<b>Adapter Frame SQ 70/55 for bucket modification</b> for use with SQ 70/55H	101	LH283681	<b>1.119,00</b>
	<b>Adapter Frame SQ 70/55 for bucket modification</b> incl. SQ valve dirt protection and tacking device, for use with SQ 70/55V	104	LH273091	<b>1.369,00</b>
	<b>Weld-on adapter SQ 70/55</b> for use with SQ70/55 H/V for welding on various attachm.	221	LH283677	<b>1.724,00</b>
	<b>Screwed adapter SQ 70/55 for hammers, grabs, compactors etc.</b> SQ 70/55H	215		<b>2.362,00</b>
	<b>Universal adapter SQ 70/55</b> for use with SQ70/55 H/V , for individual drilling patterns, base plate 570x750x35mm machined and planned.	225	LH283672	<b>1.762,00</b>



## Attachments for PC210/PC228

**SQ 70/55V Adapter**

Screw-adapter SQ 70/55V with valve configuration for various attachments (Please specify attachment type)

	Description	Weight [kg]	Price [€]
	<b>Screwed adapter SQ 70/55V for hydraulic hammers</b> valves: 2x KV4, plus installation and hoses	260	4.660,00
	<b>Screwed adapter SQ 70/55V for cutting units/compactors</b> , valves: 2x KV4, 1x KV3, plus installation and hoses	260	4.861,00
	<b>Screwed adapter SQ 70/55V for sorting grabs/shears</b> valves: 2x KV4, 2x KV1, plus installation and hoses	260	5.311,00
	<b>Screwed adapter SQ 70/55V for rotating compactors</b> valves: 2x KV4, 2x KV1, 1x KV3, plus installation and hoses	260	5.562,00
	<b>Grab adapter SQ 70/55V for suspended grabs, with cross bar</b> valves: 2x KV1, 2x KV4, plus installation and hoses	275	5.810,00



### HTL 25 GP General purpose bucket

#### with direct suspension for PC210/PC228

Cutting edge 300x35mm (500 HB), sandwich base out of 400 HB steel, side wear protection (400 HB), with tooth system Kprime P025SC

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
600	Kprime	P025SC	3	0,43	558	LH280834	<b>5.142,00</b>
700	Kprime	P025SC	3	0,53	590	LH280835	<b>5.184,00</b>
800	Kprime	P025SC	3	0,63	659	LH280836	<b>5.623,00</b>
900	Kprime	P025SC	4	0,73	690	LH280837	<b>5.831,00</b>
1000	Kprime	P025SC	4	0,84	750	LH280838	<b>6.017,00</b>
1100	Kprime	P025SC	4	0,94	785	LH280839	<b>6.347,00</b>
1200	Kprime	P025SC	4	1,05	865	LH280840	<b>6.743,00</b>
1300	Kprime	P025SC	5	1,16	895	LH280841	<b>6.943,00</b>
1400	Kprime	P025SC	5	1,26	968	LH280842	<b>7.336,00</b>
1500	Kprime	P025SC	5	1,37	1050	LH280843	<b>7.497,00</b>



### HTL 25 GP QC General purpose bucket

#### with Lehmatic adapter SW 21

Cutting edge 300x35mm (500 HB), sandwich base out of 400 HB steel, side wear protection (400 HB), with tooth system Kprime P025SC.

Surcharge for HS21V protection: 241,- EUR

Surcharge for SQ70V adapter incl. dirt protection: 180,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
600	Kprime	P025SC	3	0,43	558	LH280844	<b>5.142,00</b>
700	Kprime	P025SC	3	0,53	590	LH280845	<b>5.184,00</b>
800	Kprime	P025SC	3	0,63	659	LH280846	<b>5.623,00</b>
900	Kprime	P025SC	3	0,73	690	LH280847	<b>5.831,00</b>
1000	Kprime	P025SC	4	0,84	750	LH280848	<b>6.017,00</b>
1100	Kprime	P025SC	4	0,94	785	LH280849	<b>6.347,00</b>
1200	Kprime	P025SC	4	1,05	865	LH280850	<b>6.743,00</b>
1300	Kprime	P025SC	4	1,16	895	LH280851	<b>6.943,00</b>
1400	Kprime	P025SC	5	1,26	968	LH280852	<b>7.336,00</b>
1500	Kprime	P025SC	5	1,37	1050	LH280853	<b>7.497,00</b>



## Attachments for PC210/PC228

**HTL 25 HD Heavy-Duty bucket****with direct suspension for PC210/PC228**

for demolition and rock, Cutting edge 300x40mm (500 HB), base and side cutting edges of 400 HB steel, wear resistant plates on base (500 HB), side wear protection (400 HB), with tooth system Kprime P025RC

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
600	Kprime	P025RC	2	0,43	590	LH280854	<b>5.976,00</b>
700	Kprime	P025RC	3	0,53	630	LH280855	<b>6.042,00</b>
800	Kprime	P025RC	3	0,63	690	LH280857	<b>6.546,00</b>
900	Kprime	P025RC	3	0,73	750	LH280858	<b>6.743,00</b>
1000	Kprime	P025RC	4	0,84	795	LH280859	<b>6.958,00</b>
1100	Kprime	P025RC	4	0,94	840	LH280860	<b>7.391,00</b>
1200	Kprime	P025RC	4	1,05	900	LH280861	<b>7.829,00</b>
1300	Kprime	P025RC	4	1,16	950	LH280862	<b>8.065,00</b>
1400	Kprime	P025RC	5	1,26	1020	LH280863	<b>8.530,00</b>
1500	Kprime	P025RC	5	1,37	1080	LH280864	<b>8.716,00</b>

**HTL 25 HD QC Heavy-Duty bucket****with Lehmatic adapter SW 21**

for demolition and rock, Cutting edge 300x40mm (500 HB), base and side cutting edges of 400 HB steel, wear resistant plates on base (500 HB), side wear protection (400 HB), with tooth system Kprime P025RC.

Surcharge for HS21V protection: 241,- EUR

Surcharge for SQ70 adapter incl. dirt protection: 180,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
600	Kprime	P025RC	2	0,43	590	LH280871	<b>5.976,00</b>
700	Kprime	P025RC	3	0,53	630	LH280873	<b>6.042,00</b>
800	Kprime	P025RC	3	0,63	690	LH280875	<b>6.546,00</b>
900	Kprime	P025RC	3	0,73	750	LH280876	<b>6.743,00</b>
1000	Kprime	P025RC	4	0,84	795	LH280877	<b>6.958,00</b>
1100	Kprime	P025RC	4	0,94	840	LH280878	<b>7.391,00</b>
1200	Kprime	P025RC	4	1,05	900	LH280879	<b>7.829,00</b>
1300	Kprime	P025RC	4	1,16	950	LH280880	<b>8.065,00</b>
1400	Kprime	P025RC	5	1,26	1020	LH280881	<b>8.530,00</b>
1500	Kprime	P025RC	5	1,37	1080	LH280882	<b>8.716,00</b>



### HG 25 S Ditch bucket, rigid version

optionally with direct suspension for PC210/PC220 or quickcoupler suspension SW 21. Round bucket shape, base out of 400 HB steel, cutting edge 200x25mm out of 500 HB steel, with lateral water drain bores and rear cutting edge.

Surcharge for HS21V dirt protection: 241,- EUR

Surcharge for SQ70 adapter incl. dirt protection: 180,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
2000	Direct Susp.	-	-	0,86	620	LH253824	<b>5.843,00</b>
2000	SW 21/25	-	-	0,86	620	LH253822	<b>5.843,00</b>
2200	Direct Susp.	-	-	0,95	670	LH253825	<b>2.974,00</b>
2200	SW 21/25	-	-	0,95	670	LH253823	<b>6.094,00</b>



### HG 25 SH Tilting ditch bucket, compact round design

optionally with direct suspension for PC210/PC228 or quickcoupler suspension SW 21

2 x 45° tilting angle, 2 hydraulic cylinders with protected piston rods, with counter-balance valve, base out of 400 HB steel, cutting edge 200x25mm out of 500 HB steel, with lateral water drain bores and rear cutting edge, with hydraulic hoses up to tilting head.

Surcharge for HS21V adapter: 2.860,- EUR

Surcharge for SQ70V adapter: 2.369,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
2000	Direct Susp.	-	-	0,86	945	LH253828	<b>10.411,00</b>
2000	SW 21/25	-	-	0,86	945	LH232006	<b>10.411,00</b>
2200	Direct Susp.	-	-	0,95	997	LH253829	<b>10.607,00</b>
2200	SW 21/25	-	-	0,95	997	LH253827	<b>10.607,00</b>



### HU 25 R Universal bucket

backhoe bucket shape with round side part with quickcoupler suspension SW 21

base out of 400 HB steel, cutting edge 300x35mm out of 500 HB steel, wear resistant plates on base (500 HB)

Surcharge for HS 21V dirt protection: 241,- EUR

Surcharge for SQ70 adapter incl. dirt protection: 180,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1600			-	1,200	850	LH213239	<b>6.567,00</b>
1800			-	1,370	960	LH237392	<b>6.943,00</b>





## Attachments for PC210/PC228

**HU 25 RH Universal tilting bucket**

**backhoe bucket shape with round side part with quickcoupler suspension SW 21**

2 x 45° tilting range, 2 hydraulic cylinders with protected piston rods and counter-balance valve, base out of 400 HB steel, cutting edge 300x35mm out of Leborit 5000 (500 HB), wear resistant plates on base (500 HB), with hydraulic hoses up to tilting head.

Surcharge for HS21V adapter: 2.860,- EUR  
Surcharge for SQ70V adapter: 2.369,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1600	SW 21/25	-	-	1,200	1250	LH232134	<b>13.381,00</b>
1800	SW 21/25	-	-	1,370	1317	LH232135	<b>13.911,00</b>

**HU 25 RM Universal tilting bucket**

**backhoe bucket shape with round side part with quickcoupler suspension SW 21**

2 x 45° tilting range, with hydraulic tilt motor Type 250, base of 400 HB steel, cutting edge 300x35mm of Leborit 5000 (500 HB), wear resistant plates on base (500 HB), robust version.

Surcharge for HS21V adapter: 2.860,- EUR  
Surcharge for SQ70V adapter: 2.369,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1600	SW 21/25	-	-	1,200	1205	LH238653	<b>16.258,00</b>
1800	SW 21/25	-	-	1,370	1336	LH242527	<b>16.732,00</b>

**HSL 25 Sorting bucket with rectangular bars**

**with Lehmatic adapter SW 21**

Base made of solid rectangular bars 50x30mm, spacing 60mm, cutting edge 300x40mm (500 HB), side wear protection (400 HB), with teeth Kprime P025SC

Surcharge for HS21V protection: 241,- EUR  
Surcharge for SQ70 adapter incl. dirt protection: 180,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1300	Kprime	P025SC	5	1,160	955	LH282496	<b>9.072,00</b>



### HSL 25 Sorting bucket round bars

#### with Symlock adapter SW21

Base with round bars D40 made of 400HB steel, 60mm hole width, cutting edge 300x40mm (500 HB), side edges (400 HB), with teeth Kprime P025SC.



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1300		P025SC	5	1,160	955		

### MRZ 28 bionic Ripper tooth

for demolition and rock use, with Lehmatic adapter SW 21/25



Option	Tooth point	Angle	Tooth-radius [mm]	Weight [kg]	PN	Price [€]
SW 21	9W2452	35	1150	420	LH225637	<b>6.425,00</b>

### HSG 25 Demolition and sorting grab

compact design, grab shells out of Hardox 400, interchangeable cutting edges out of Hardox 500, incl. counter-balance valve, rotating angle 360° endless, incl. screwed Lehmatic adapter SW 21. Grab shells closed or with rectangular bars on demand.

Surcharge for HS21V adapter: 1.950,- EUR

Surcharge for SQ70V adapter: 1.624,- EUR



Opening clearance [mm]	Width [mm]	Capacity SAE [m <sup>3</sup> ]	Grab force [kN]	Weight [kg]	PN	Price [€]
2000	1000	0,530	53	1555	LH264715	<b>29.070,00</b>

### HSG 25V Demolition and sorting grab

With integrated SW 21V adapter, ready for use, approx. 10% weight saving and lower overall height, grab shells out of Hardox 400, interchangeable cutting edges out of Hardox 500, incl. counter-balance valve, rotating angle 360° endless, grab shells closed or with rectangular bars on demand.



Opening clearance [mm]	Width [mm]	Capacity SAE [m <sup>3</sup> ]	Grab force [kN]	Weight [kg]	PN	Price [€]
2000	1000	0,530	53	1555	LH271767	<b>31.683,00</b>



## Attachments for PC230/PC240

**MS 21 Quickcoupler mechanical****for PC230/PC240**

Quickcoupler with mechanical locking, incl. socket wrench, optionally with 10t load hook

Type	Excavator	Option	Weight [kg]	PN	Price [€]
MS 21	PC210-PC240	-	270	LH104618	<b>7.184,00</b>
MS 21	PC210-PC240	Load hook 10t	280	LH105219	<b>7.631,00</b>

**HS 21 DL Quickcoupler hydraulic****for PC230/PC240**

Quickcoupler with hydraulic locking, with 10t load hook.

**With safety locking mechanism Double Lock**

Type	Excavator	Option	Weight [kg]	PN	Price [€]
HS 21 DL	PC210-PC240	Load hook 10t	280	LH281636	<b>9.795,00</b>

**HS 21V DL Quickcoupler fully hydraulic****for PC230/PC240**

Fully hydraulic Quickcoupler with 2 valves KV4, 1 valve KV3, 2 valves KV1, two 10 t load hooks, valve block's internal depressurizing circuit (BiD) incl., hoses from valve block to flange, excl. hydr. installation kit and installation.

**With safety locking mechanism Double Lock**

Type	Excavator	Option	Weight [kg]	PN	Price [€]
HS 21 DL	PC210-PC240	2x Load hook 10t	280	LH284281	<b>17.844,00</b>



### MS 21 - Tilt Quickcoupler Tilt

#### for PC230/PC240

Mechanical quickcoupler with Powertilt motor (PT), with direct suspension. Including 10t load hook.

Excl. optional switch valve, excl. installation on excavator.



Type	Excavator	Option	Tilt-Angle	Weight [kg]	PN	Price [€]
MS 21 - PT 240	PC210-PC230	Hook 10t	2 x 60°	570-590	LH255517	<b>18.130,00</b>
MS 21 - PT 300	PC240	Hook 10t	2 x 60°	570-590	LH287564	<b>23.238,00</b>
Tilt switch valve		24 V			LH207711	<b>976,00</b>

### HS 21 DL - Tilt Quickcoupler Tilt

#### for PC230/PC240

Hydraulic quickcoupler with Powertilt motor (PT), with direct suspension. Including 10t load hook.

Excl. optional switch valve, excl. installation on excavator.

**With safety locking mechanism Double Lock**



Type	Excavator	Option	Tilt-Angle	Weight [kg]	PN	Price [€]
HS 21 DL - PT 240	PC210-PC230	Hook 10t	2 x 60°	590-630	LH286715	<b>19.964,00</b>
HS 21 DL - PT 300	PC240	Hook 10t	2 x 60°	570-590	LH286838	<b>25.528,00</b>
Tilt switch valve		24 V			LH207711	<b>976,00</b>

### HS 21V DL - Tilt Quickcoupler Tilt

#### for PC230/PC240

Fully hydraulic quickcoupler with Powertilt motor (PT), with direct suspension. Including 10t load hook. Excl. optional switch valve, excl. installation on excavator.

**With safety locking mechanism Double Lock**



Abb. ähnlich

Type	Excavator	Option	Tilt-Angle	Weight [kg]	PN	Price [€]
HS 21V DL - PT 240	PC210-PC230	2x Hook 10t	2 x 60°	790-850	LH286870	<b>29.466,00</b>
HS 21V DL - PT 300	PC240	2x Hook 10t	2 x 60°	580-600	LH286876	<b>32.181,00</b>
Tilt switch valve		24 V			LH207711	<b>976,00</b>



## Attachments for PC230/PC240






**SW 21/25 Adapter**

Adapters SW 21/25 for bucket modification and for screwing or welding on other attachments.

	Description	Weight [kg]	PN	Price [€]
	<b>Adapter plate SW 21/25 -standard-</b> for bucket modification, Base plate: 600x530x30mm	147	LH100577	<b>1.664,00</b>
	<b>Adapter plate SW 21/25 HD -reinforced-</b> for bucket modification, Base plate: 700x550x40mm	188	LH257849	<b>2.237,00</b>
	<b>Weld-on adapter SW 21/25</b> for hammers, shears etc. Base plate: 752x665x40mm	250	LH238536	<b>2.959,00</b>
	<b>Screwed adapter SW 21/25 -standard-</b> for hammers, shears etc.	250		<b>3.386,00</b>
	<b>Screwed adapter SW 21/25 HD -reinforced-</b> for hammers, shears etc.	300		<b>4.403,00</b>
	<b>Grab adapter SW 21/25</b> for hydraulic grabs, with cross bar	205		<b>3.717,00</b>
	<b>Universal adapter SW 21/25 W=665mm</b> for individual drilling patterns or welding Base plate 665x752x40mm, Bottom side machined and planned.	300	LH279159	<b>2.988,00</b>
	<b>Universal adapter SW 21/25 W=735mm</b> for individual drilling patterns or welding Base plate 735x752x40mm, Bottom side machined and planned.	310	LH269783	<b>3.024,00</b>
	<b>Universal adapter SW 21/25 B=755mm</b> for individual drilling patterns or welding Base plate 755x752x40mm, Bottom side machined and planned.	320	LH269805	<b>3.082,00</b>

### SW 21V/25V Adapter

Screw-adapter SW 21V/25V with valve configuration for various attachments (Please specify attachment type)

	Description	Weight [kg]	Price [€]
	<b>Screwed adapter SW 21V/25V</b> for hydraulic hammers, valves: 2x KV4, plus installation and hoses	316	<b>4.794,00</b>
	<b>Screwed adapter SW 21V/25V</b> for sorting grabs/shears, valves: 2x KV4, 2x KV1, plus installation and hoses	316	<b>5.336,00</b>
	<b>Screwed adapter HS 21V/25V</b> for cutting units/compactors, valves: 2x KV4, 1x KV3, plus installation and hoses	316	<b>5.336,00</b>
	<b>Screwed adapter SW 21V/25V</b> for rotating compactors, valves: 2x KV4, 2x KV1, 1x KV3, plus installation and hoses	316	<b>5.459,00</b>
	<b>Grab adapter SW 21V/25V</b> for suspended grabs, with cross bar, valves: 2x KV1, 2x KV4, plus installation and hoses	250	<b>5.324,00</b>



## Attachments for PC230/PC240



### SQ 70-2H LSC Quickcoupler hydraulic, symmetrical for PC210-PC240

symmetrical quickcoupler, based on S-standard, with LSC safety assistance system as standard. one 10 t load hook, installation kit and installation not included.

Type	Excavator	Option	Weight [kg]	PN	Price [€]
SQ 70-2H LSC	PC210-PC240	Load Hook 10t	288	LH295341	<b>10.394,00</b>
LSC install. kit electr.				LH249489	<b>1.069,00</b>



### SQ 70/55H LSC Quickcoupler hydraulic, symmetrical for PC210-PC240

symmetrical quickcoupler, based on S-standard, width 550mm, with LSC safety assistance system as standard. one 10 t load hook, installation kit and installation not included.

Type	Excavator	Option	Weight [kg]	PN	Price [€]
SQ 70/55H LSC	PC210-PC240	Load Hook 10t	330	LH295338	<b>11.016,00</b>
LSC install. kit electr.				LH249489	<b>1.069,00</b>



### SQ 70-2V LSC Quickcoupler fully hydraulic, symmetrical for PC210-PC240

Fully hydraulic symmetrical quickcoupler, based on S-standard, with LSC safety assistance system as standard. 2 valves KV4, 1 valve KV3 and 2 valves KV1, one 10 t load hook, incl. valve block's internal depressurization unit (BiD), installation kit and installation not included.

Type	Excavator	Option	Weight [kg]	PN	Price [€]
SQ 70-2V LSC	PC210-PC240	Load Hook 10t	305	LH294053	<b>14.195,00</b>
SQ 70-2V LSC	PC210-PC240	2x Hook 10t	315	LH294352	<b>14.642,00</b>
LSC install. kit electr.				LH249489	<b>1.069,00</b>

### SQ 70/55V LSC Quickcoupler fully hydraulic, symmetrical for PC210/PC240






Fully hydraulic symmetrical quickcoupler, based on S-standard, width 550mm, with LSC safety assistance system as standard. 2 valves KV4, 1 valve KV3 and 2 valves KV1, one 10 t load hook, incl. valve block's internal depressurization unit (BiD), installation kit and installation not included. Also available as hydraulic or mechanical version.



Type	Excavator	Option	Weight [kg]	PN	Price [€]
SQ 70/55V LSC	PC210-PC240	Load Hook 10t	344	LH295337	<b>15.090,00</b>
SQ 70/55V LSC	PC210-PC240	2x Hook 10t	354	LH295353	<b>15.552,00</b>
LSC install. kit electr.				LH249489	<b>1.069,00</b>

### SQ 70 Adapter

Adapters SQ 70 for bucket modification and for screwing or welding on other attachments

Description	Weight [kg]	PN	Price [€]
 <b>Adapter Frame SQ 70 for bucket modification</b> for use with SQ 70H	91	283681	<b>1.056,00</b>
 <b>Adapter Frame SQ 70 for bucket modification</b> incl. SQ valve dirt protection and tacking device. For use with SQ 70V	96	273091	<b>1.292,00</b>
 <b>Weld-on adapter SQ 70</b> for welding on various attachm. For use with SQ 70H/70V	210	283677	<b>1.627,00</b>
 <b>Screwed adapter SQ 70 for hammers, grabs, compactors etc.</b> exact type required! For use with SQ 70H/70V	215		<b>2.229,00</b>
 <b>Universal adapter SQ 70</b> for individual drilling patterns, base plate 570x750x35mm machined and planned. For use with SQ 70H/70V	210	283672	<b>1.662,00</b>










## Attachments for PC230/PC240






**SQ 70V Adapter**

Screw-adapter SQ 70 with valve configuration for various attachments (Please specify attachment type)

	Description	Weight [kg]	Price [€]
	<b>Screwed adapter SQ 70V for hydraulic hammers</b> valves: 2x KV4, plus installation and hoses	235	<b>4.397,00</b>
	<b>Screwed adapter SQ 70V for cutting units/compactors</b> valves: 2x KV4, 1x KV3, plus installation and hoses	235	<b>4.586,00</b>
	<b>Screwed adapter SQ 70V for sorting grabs/shears</b> valves: 2x KV4, 2x KV1, plus installation and hoses	235	<b>5.011,00</b>
	<b>Screwed adapter SQ 70V for rotating compactors</b> valves: 2x KV4, 2x KV1, 1x KV3, plus installation and hoses	235	<b>5.247,00</b>
	<b>Grab adapter SQ 70V for suspended grabs, with cross bar</b>	250	<b>5.482,00</b>

### SQ 70/55 Adapter

Adapters SQ 70/55 for bucket modification and for screwing or welding on other attachments






	Description	Weight [kg]	PN	Price [€]
	<b>Adapter Frame SQ 70/55 for bucket modification</b> for use with SQ 70/55H	101	LH283681	<b>1.119,00</b>
	<b>Adapter Frame SQ 70/55 for bucket modification</b> incl. SQ valve dirt protection and tacking device, for use with SQ 70/55V	104	LH273091	<b>1.369,00</b>
	<b>Weld-on adapter SQ 70/55</b> for use with SQ70/55 H/V for welding on various attachm.	221	LH283677	<b>1.724,00</b>
	<b>Screwed adapter SQ 70/55 for hammers, grabs, compactors etc.</b> SQ 70/55H	215		<b>2.362,00</b>
	<b>Universal adapter SQ 70/55</b> for use with SQ70/55 H/V , for individual drilling patterns, base plate 570x750x35mm machined and planned.	225	LH283672	<b>1.762,00</b>



## Attachments for PC230/PC240

**SQ 70/55V Adapter**

Screw-adapter SQ 70/55V with valve configuration for various attachments (Please specify attachment type)

	Description	Weight [kg]	Price [€]
	<b>Screwed adapter SQ 70/55V for hydraulic hammers</b> valves: 2x KV4, plus installation and hoses	260	4.660,00
	<b>Screwed adapter SQ 70/55V for cutting units/compactors</b> , valves: 2x KV4, 1x KV3, plus installation and hoses	260	4.861,00
	<b>Screwed adapter SQ 70/55V for sorting grabs/shears</b> valves: 2x KV4, 2x KV1, plus installation and hoses	260	5.311,00
	<b>Screwed adapter SQ 70/55V for rotating compactors</b> valves: 2x KV4, 2x KV1, 1x KV3, plus installation and hoses	260	5.562,00
	<b>Grab adapter SQ 70/55V for suspended grabs, with cross bar</b> valves: 2x KV1, 2x KV4, plus installation and hoses	275	5.810,00



### HTL 30 GP General purpose bucket

#### with direct suspension for PC230/PC240

Cutting edge 300x40mm (500 HB), sandwich constructed base out of 400 HB steel, side wear protection (400 HB), with tooth system Kprime P025SC



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
600	Kprime	P025SC	2	0,48	620	LH280883	<b>5.950,00</b>
800	Kprime	P025SC	3	0,7	700	LH280884	<b>6.599,00</b>
1000	Kprime	P025SC	4	0,93	780	LH280885	<b>6.957,00</b>
1200	Kprime	P025SC	4	1,17	890	LH280886	<b>7.869,00</b>
1400	Kprime	P025SC	5	1,41	1025	LH280888	<b>8.700,00</b>
1500	Kprime	P025SC	5	1,53	1100	LH280889	<b>9.149,00</b>
1600	Kprime	P025SC	5	1,65	1206	LH280890	<b>9.560,00</b>
1800	Kprime	P025SC	6	1,89	1290	LH280891	<b>9.787,00</b>

### HTL 30 GP QC General purpose bucket

#### with Lehmatic adapter SW 21

cutting edge 300x40mm (500 HB), sandwich constructed base out of 400 HB steel, side wear protection (400 HB), with tooth System Kprime P025SC.

Surcharge for HS21V adapter: 241,- EUR

Surcharge for SQ70 adapter incl. dirt protection: 180,- EUR



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
600	Kprime	P025SC	2	0,48	620	LH280892	<b>5.950,00</b>
800	Kprime	P025SC	3	0,70	700	LH280893	<b>6.599,00</b>
1000	Kprime	P025SC	4	0,93	780	LH280894	<b>6.957,00</b>
1200	Kprime	P025SC	4	1,17	890	LH280895	<b>7.869,00</b>
1400	Kprime	P025SC	5	1,41	1025	LH280896	<b>8.700,00</b>
1500	Kprime	P025SC	5	1,53	1100	LH280897	<b>9.149,00</b>
1600	Kprime	P025SC	6	1,65	1206	LH280898	<b>9.560,00</b>
1800	Kprime	P025SC	6	1,89	1290	LH280899	<b>9.787,00</b>



## Attachments for PC230/PC240

**HTL 30 HD Heavy-Duty bucket****with direct suspension for PC230/PC240**

for demolition and rock, cutting edge 300x40mm (500 HB), base, side cutting edge and side wear protection out of 400 HB steel, wear resistant plates on base (500 HB), with tooth system Kprime P025RC

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
600	Kprime	P025RC	2	0,48	670	LH280900	<b>6.743,00</b>
800	Kprime	P025RC	3	0,70	750	LH280901	<b>7.209,00</b>
1000	Kprime	P025RC	4	0,93	840	LH280902	<b>7.738,00</b>
1200	Kprime	P025RC	4	1,17	960	LH280903	<b>8.662,00</b>
1400	Kprime	P025RC	5	1,41	1050	LH280904	<b>10.050,00</b>
1500	Kprime	P025RC	5	1,53	1120	LH280905	<b>10.474,00</b>
1600	Kprime	P025RC	5	1,65	1170	LH280906	<b>10.910,00</b>

**HTL 30 HD QC Heavy-Duty bucket****with Lehmatic adapter SW 21**

for demolition and rock, cutting edge 300x40mm (500 HB), base, side cutting edge and side wear protection out of 400 HB steel, wear protection plates on base (500 HB), with tooth system Kprime P025RC.

Surcharge for HS21V adapter: 241,- EUR

Surcharge for SQ70 adapter incl. dirt protection: 180,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
600	Kprime	P025RC	3	0,48	670	LH280907	<b>6.743,00</b>
800	Kprime	P025RC	3	0,70	750	LH280909	<b>7.209,00</b>
1000	Kprime	P025RC	4	0,93	840	LH280910	<b>7.738,00</b>
1200	Kprime	P025RC	4	1,17	960	LH280911	<b>8.662,00</b>
1400	Kprime	P025RC	5	1,41	1050	LH280912	<b>10.050,00</b>
1500	Kprime	P025RC	5	1,53	1120	LH280913	<b>10.474,00</b>
1600	Kprime	P025RC	5	1,65	1170	LH280914	<b>10.910,00</b>



### HG 30 S Ditch bucket, rigid version

optionally with direct suspension for PC240 or quickcoupler suspension SW 21. Round bucket shape, base out of 400 HB steel, cutting edge 250x30mm out of 500 HB steel, with lateral water drain bores and rear cutting edge.

Surcharge for HS 21V dirt protection: 241,- EUR

Surcharge for SQ70 adapter incl. dirt protection: 180,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
2000	Direct Susp.	-	-	1,25	990	LH253857	<b>6.441,00</b>
2000	SW 21/25	-	-	1,25	990	LH253855	<b>6.441,00</b>
2200	Direct Susp.	-	-	1,37	1075	LH253858	<b>6.604,00</b>
2200	SW 21/25	-	-	1,37	1075	LH253856	<b>6.604,00</b>



### HG 30 SH Tilting ditch bucket, compact round design

optionally with direct suspension for PC240 or quickcoupler suspension SW 21

2 x 45° tilting angle, 2 hydraulic cylinders with protected piston rods, with counter-balance valve, base out of 400 HB steel, cutting edge 250x30mm out of 500 HB steel, with lateral water drain bores and rear cutting edge, with hydraulic hoses up to tilting head.

Surcharge for HS21V adapter: 2.860,- EUR

Surcharge for SQ70 adapter: 2.369,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
2000	Direct Susp.	-	-	1,25	1340	LH253861	<b>11.623,00</b>
2000	SW 21/25	-	-	1,25	1340	LH253859	<b>11.623,00</b>
2200	Direct Susp.	-	-	1,37	1450	LH253862	<b>11.868,00</b>
2200	SW 21/25	-	-	1,37	1450	LH253860	<b>11.868,00</b>



### HU 30 R rigid Universal bucket

backhoe bucket shape with round side part with quickcoupler suspension SW 10

base out of 400 HB steel, cutting edge 300x35mm out of 500 HB steel, wear resistant plates on base (500 HB)

Surcharge for HS21V dirt protection: 241,- EUR

Surcharge for SQ70 adapter incl. dirt protection: 180,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1600			-	1,370	915	LH246843	<b>7.723,00</b>
1800			-	1,550	1025		<b>0,00</b>



## Attachments for PC230/PC240

**HU 30 RH Universal tilting bucket**

**backhoe bucket shape with round side part with quickcoupler suspension SW 21**

2 x 45° tilting range, 2 hydraulic cylinders with protected piston rods and counter-balance valve, base out of 400 HB steel, cutting edge 300x35mm out of Lehborit 5000 (500 HB), wear resistant plates on base (500 HB), with hydraulic hoses up to tilting head.

Surcharge for HS 21V adapter: 2.860,- EUR

Surcharge for SQ70 adapter: 2.369,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1600	SW 21/25	-	-	1,370	1349	LH234662	<b>14.306,00</b>
1800	SW 21/25	-	-	1,550	1431	LH232350	<b>14.971,00</b>

**HU 30 RM Universal tilting bucket**

**backhoe bucket shape with round side part with quickcoupler suspension SW 21**

2 x 45° tilting range, with hydraulic tilt Motor, base out of 400 HB steel, cutting edge 300x35mm out of Lehborit 5000 (500 HB), wear resistant plates on base (500 HB).

Surcharge for HS21V adapter: 2.860,- EUR

Surcharge for SQ70V adapter: 2.369,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1600	SW 21/25	-	-	1,370	1500	LH238617	<b>23.381,00</b>
1800	SW 21/25	-	-	1,550	1600	LH242533	<b>23.615,00</b>

**HSL 30 Sorting bucket with rectangular bars**

**with Lehmatic adapter SW 21**

Base made of solid rectangular bars 60x40mm, 60mm spacing, cutting edge 300x40mm (500 HB), side edges (400 HB), with teeth Kprime P025C.

Surcharge for HS21V protection: 241,- EUR

Surcharge for SQ70 adapter incl. dirt protection: 180,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1400	Kprime	P025SC	5	1,410	1280	LH282497	<b>11.086,00</b>
1500	Kprime	P025SC	5	1,530	1337	LH282498	<b>11.321,00</b>



24 - 28 t



### HSL 30 Sorting bucket round bars

with Symlock adapter SW21

Base with round bars D40 made of 400HB steel, 60mm hole width, cutting edge 300x40mm (500 HB), side edges (400 HB), with teeth Kprime P025SC.

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1400		P025SC	5	1,410	1280		



### MRZ 28 bionic Ripper tooth

for demolition and rock use, with Lehmatic adapter SW 21/25

Option	Tooth point	Angle	Tooth-radius [mm]	Weight [kg]	PN	Price [€]
SW 21	9W2452	35	1150	420	LH225637	6.425,00



### HSG 28 Demolition and sorting grab

compact design, grab shells out of Hardox 400, interchangeable cutting edges out of Hardox 500, incl. counter-balance valve, rotating angle 360° endless, incl. screwed Lehmatic adapter SW 21. Grab shells closed or with rectangular bars on demand.

Surcharge for HS21V adapter: 1.950,- EUR

Surcharge for SQ70V adapter: 1.624,- EUR

Opening clearance [mm]	Width [mm]	Capacity SAE [m <sup>3</sup> ]	Grab force [kN]	Weight [kg]	PN	Price [€]
2190	1100	0,640	61	1800	LH264716	31.381,00



### HSG 28V Demolition and sorting grab

With integrated SW 21V adapter, ready for use, approx. 10% weight saving and lower overall height, grab shells out of Hardox 400, interchangeable cutting edges out of Hardox 500, incl. counter-balance valve, rotating angle 360° endless, grab shells closed or with rectangular bars on demand.

Opening clearance [mm]	Width [mm]	Capacity SAE [m <sup>3</sup> ]	Grab force [kN]	Weight [kg]	PN	Price [€]
2190	1100	0,640	61	1800	LH271768	33.998,00





## Attachments for PC290 (PC390/PC490 HRD boom)



### MS 25 Quickcoupler mechanical

#### for PC290/PC390 HRD boom

Quickcoupler with mechanical locking, incl. socket wrench, optionally with 18t load hook

Type	Excavator	Option	Weight [kg]	PN	Price [€]
MS 25	PC290/PC390	-	330	LH107900	<b>8.662,00</b>
MS 25	PC290	Load hook 18t	340	LH107901	<b>9.109,00</b>



### HS 25 DL Quickcoupler hydraulic

#### for PC290/PC390 HRD boom

Quickcoupler with hydraulic locking, with 18t load hook.

**With safety locking mechanism Double Lock**

Type	Excavator	Option	Weight [kg]	PN	Price [€]
HS 25 DL	PC290/PC390	Load hook 18t	340	LH283388	<b>11.471,00</b>



### HS 25V DL Quickcoupler fully hydraulic

#### for PC290/PC390 HRD boom

Fully hydraulic Quickcoupler with 2 valves KV4, 1 valve KV3, 2 valves KV1, two 18 t load hooks, valve block's internal depressurizing circuit (BiD) incl., hoses from valve block to flange, excl. hydr. installation kit and installation.

**With safety locking mechanism Double Lock**

Type	Excavator	Option	Weight [kg]	PN	Price [€]
HS 25V DL	PC290/PC390	2x Load hook 18t	340	LH283887	<b>20.645,00</b>



## SW 21/25 Adapter

Adapters SW 21/25 for bucket modification and for screwing or welding on other attachments.






	Description	Weight [kg]	PN	Price [€]
	<b>Adapter plate SW 21/25 -standard-</b> for bucket modification, Base plate: 600x530x30mm	147	LH100577	<b>1.664,00</b>
	<b>Adapter plate SW 21/25 HD -reinforced-</b> for bucket modification, Base plate: 700x550x40mm	188	LH257849	<b>2.237,00</b>
	<b>Weld-on adapter SW 21/25</b> for hammers, shears etc. Base plate: 752x665x40mm	250	LH238536	<b>2.959,00</b>
	<b>Screwed adapter SW 21/25 -standard-</b> for hammers, shears etc.	250		<b>3.386,00</b>
	<b>Screwed adapter SW 21/25 HD -reinforced-</b> for hammers, shears etc.	300		<b>4.403,00</b>
	<b>Grab adapter SW 21/25</b> for hydraulic grabs, with cross bar	205		<b>3.717,00</b>
	<b>Universal adapter SW 21/25 W=665mm</b> for individual drilling patterns or welding Base plate 665x752x40mm, Bottom side machined and planned.	300	LH279159	<b>2.988,00</b>
	<b>Universal adapter SW 21/25 W=735mm</b> for individual drilling patterns or welding Base plate 735x752x40mm, Bottom side machined and planned.	310	LH269783	<b>3.024,00</b>
	<b>Universal adapter SW 21/25 B=755mm</b> for individual drilling patterns or welding Base plate 755x752x40mm, Bottom side machined and planned.	320	LH269805	<b>3.082,00</b>



## Attachments for PC290 (PC390/PC490 HRD boom)

**SW 21V/25V Adapter**

Screw-adapter SW 21V/25V with valve configuration for various attachments (Please specify attachment type)

	Description	Weight [kg]	Price [€]
	<b>Screwed adapter SW 21V/25V</b> for hydraulic hammers, valves: 2x KV4, plus installation and hoses	316	<b>4.794,00</b>
	<b>Screwed adapter SW 21V/25V</b> for sorting grabs/shears, valves: 2x KV4, 2x KV1, plus installation and hoses	316	<b>5.336,00</b>
	<b>Screwed adapter HS 21V/25V</b> for cutting units/compactors, valves: 2x KV4, 1x KV3, plus installation and hoses	316	<b>5.336,00</b>
	<b>Screwed adapter SW 21V/25V</b> for rotating compactors, valves: 2x KV4, 2x KV1, 1x KV3, plus installation and hoses	316	<b>5.459,00</b>
	<b>Grab adapter SW 21V/25V</b> for suspended grabs, with cross bar, valves: 2x KV1, 2x KV4, plus installation and hoses	250	<b>5.324,00</b>



### SQ 70/55H LSC Quickcoupler hydraulic, symmetrical for PC290

symmetrical quickcoupler, based on S-standard, width 550mm, with LSC safety assistance system as standard. one 10 t load hook, installation kit and installation not included.

Type	Excavator	Option	Weight [kg]	PN	Price [€]
SQ 70/55H LSC	PC290	Load Hook 10t	330	LH295339	<b>11.016,00</b>



### SQ 70/55V LSC Quickcoupler fully hydraulic, symmetrical for PC290

Fully hydraulic symmetrical quickcoupler, based on S-standard, width 550mm, with LSC safety assistance system as standard. 2 valves KV4, 1 valve KV3 and 2 valves KV1, one 10 t load hook, incl. valve block's internal depressurization unit (BiD), installation kit and installation not included.

Type	Excavator	Option	Weight [kg]	PN	Price [€]
SQ 70/55V LSC	PC290	Load Hook 10t	346	LH295340	<b>15.090,00</b>
SQ 70/55V LSC	PC290	2x Hook 10t	356	LH295354	<b>15.552,00</b>
LSC install. kit electr.				LH249489	<b>1.069,00</b>



### SQ 80H LSC Quickcoupler hydraulic, symmetrical for PC290/PC390 HRD boom

Hydraulic symmetrical quickcoupler, based on S-standard, with LSC safety assistance system as standard. one 18 t load hook, installation kit and installation not included.

Type	Excavator	Option	Weight [kg]	PN	Price [€]
SQ 80H LSC	PC290/PC390	1x Hook 18t	382	LH279851	<b>13.850,00</b>
LSC install. kit electr.				LH249489	<b>1.069,00</b>



## Attachments for PC290 (PC390/PC490 HRD boom)



### SQ 80V LSC Quickcoupler fully hydraulic, symmetrical for PC290/PC390 HRD boom






Fully hydraulic symmetrical quickcoupler, based on S standard. With 2 valves KV4, 1 valve KV3 and 2 valves KV1, one 18 t load hook, series with Lehmatic Safety Control (LSC) as standard, valve block's internal depressurizing circuit (BiD) incl., installation kit and installation not included. Also available as hydraulic version.

Type	Excavator	Option	Weight [kg]	PN	Price [€]
SQ 80V LSC	PC290/PC390	1x Hook 18t	396	LH279443	<b>16.960,00</b>
SQ 80V LSC	PC290/PC390	2x Hook 18t	406	LH282634	<b>17.407,00</b>
LSC install. kit electr.				LH249489	<b>1.069,00</b>



## SQ 70/55 Adapter

Adapters SQ 70/55 for bucket modification and for screwing or welding on other attachments






	Description	Weight [kg]	PN	Price [€]
	<b>Adapter Frame SQ 70/55 for bucket modification</b> for use with SQ 70/55H	101	LH283681	<b>1.119,00</b>
	<b>Adapter Frame SQ 70/55 for bucket modification</b> incl. SQ valve dirt protection and tacking device, for use with SQ 70/55V	104	LH273091	<b>1.369,00</b>
	<b>Weld-on adapter SQ 70/55</b> for use with SQ70/55 H/V for welding on various attachm.	221	LH283677	<b>1.724,00</b>
	<b>Screwed adapter SQ 70/55 for hammers, grabs, compactors etc.</b> SQ 70/55H	215		<b>2.362,00</b>
	<b>Universal adapter SQ 70/55</b> for use with SQ70/55 H/V , for individual drilling patterns, base plate 570x750x35mm machined and planned.	225	LH283672	<b>1.762,00</b>








## Attachments for PC290

**SQ 70/55V Adapter**

Screw-adapter SQ 70/55V with valve configuration for various attachments (Please specify attachment type)

	Description	Weight [kg]	Price [€]
	<b>Screwed adapter SQ 70/55V for hydraulic hammers</b> valves: 2x KV4, plus installation and hoses	260	<b>4.660,00</b>
	<b>Screwed adapter SQ 70/55V for cutting units/compactors</b> , valves: 2x KV4, 1x KV3, plus installation and hoses	260	<b>4.861,00</b>
	<b>Screwed adapter SQ 70/55V for sorting grabs/shears</b> valves: 2x KV4, 2x KV1, plus installation and hoses	260	<b>5.311,00</b>
	<b>Screwed adapter SQ 70/55V for rotating compactors</b> valves: 2x KV4, 2x KV1, 1x KV3, plus installation and hoses	260	<b>5.562,00</b>
	<b>Grab adapter SQ 70/55V for suspended grabs, with cross bar</b> valves: 2x KV1, 2x KV4, plus installation and hoses	275	<b>5.810,00</b>

## SQ 80H Adapter

	Description	Weight [kg]	PN	Price [€]
	<b>Adapter Frame SQ 80 for bucket modification</b> for use with SQH80	141	LH283680	<b>1.214,00</b>
	<b>Adapter Frame SQ 80 for bucket modification</b> incl. SQ valve dirt protection and tacking device, for use with SQH80 & SQE80	165	LH277716	<b>1.544,00</b>
	<b>Weld-on adapter SQ 80</b> for use with SQ80V for welding on various attachm.	433		<b>1.980,00</b>
	<b>Screwed adapter SQ 80</b> for use with SQH80 for hammers, grabs, compactors etc. exact type required!	356		<b>2.393,00</b>
	<b>Universal adapter SQ 80</b> for use with SQ 80H/80V. For individual drilling patterns, base plate 740x860x40mm. For use with SQ 80H/80V	345	283674	<b>2.016,00</b>









## Attachments for PC290 (PC390/PC490 HRD boom)

### SQ 80V Adapter

Screw-adapter SQ 80 with valve configuration for various attachments (Please specify attachment type)

	Description	Weight [kg]	Price [€]
	<b>Screwed adapter SQ 80V</b> for hydraulic hammers, valves: 2x KV4, plus installation and hoses	385	4.657,00
	<b>Screwed adapter SQ 80V</b> for cutting units/compactors, valves: 2x KV4, 1x KV3, plus installation and hoses	385	4.951,00
	<b>Screwed adapter SQ 80V</b> for sorting grabs/shears, valves: 2x KV4, 2x KV1, plus installation and hoses	385	5.600,00
	<b>Screwed adapter SQ 80V</b> for rotating compactors, valves: 2x KV4, 2x KV1, 1x KV3, plus installation and hoses	385	5.835,00



### HTL 35 GP General purpose bucket

with direct suspension for PC290

**NEW design with tube reinforcement**

Cutting edge 300x45mm (500 HB), sandwich constructed base with 400 HB steel, side wear protection (400 HB), with tooth system Kprime P030SC



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
800	Kprime	P030SC	3	0,85	790	LH280916	<b>8.264,00</b>
1000	Kprime	P030SC	3	1,13	1010	LH280917	<b>9.175,00</b>
1200	Kprime	P030SC	4	1,42	1160	LH280918	<b>9.946,00</b>
1400	Kprime	P030SC	4	1,75	1290	LH280919	<b>10.554,00</b>
1500	Kprime	P030SC	5	1,87	1480	LH280920	<b>11.341,00</b>
1600	Kprime	P030SC	5	2,02	1550	LH280921	<b>11.860,00</b>

### HTL 35 GP QC General purpose bucket

with Lehmatic adapter SW 25

Cutting edge 300x45mm (500 HB), sandwich constructed base with 400 HB steel, side wear protection (400 HB), with tooth system Kprime P030SC.

Surcharge for HS25V protection: 241,- EUR

Surcharge for SQ80 adapter incl. dirt protection: 180,- EUR



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
800	Kprime	P030SC	3	0,85	875	LH280947	<b>8.264,00</b>
1000	Kprime	P030SC	3	1,13	1010	LH280948	<b>9.175,00</b>
1200	Kprime	P030SC	4	1,42	1230	LH280949	<b>9.946,00</b>
1400	Kprime	P030SC	4	1,75	1330	LH280950	<b>10.554,00</b>
1500	Kprime	P030SC	5	1,87	1420	LH280951	<b>11.341,00</b>
1600	Kprime	P030SC	5	2,02	1480	LH280952	<b>11.860,00</b>
1800	Kprime	P030SC	5	2,32	1590	LH280953	<b>13.234,00</b>
2000	Kprime	P030SC	6	2,54	1690	LH280954	<b>14.607,00</b>



Attachments for PC290



**HTL 35 HD Heavy-Duty bucket**

with direct suspension for PC290  
**NEW design with tube reinforcement**

for demolition and rock, cutting edge 300x50mm (500 HB), base, side cutting edge and side wear protection out of 400 HB steel, wear resistant plates on base (500 HB), with tooth system Kprime P030RC

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
800	Kprime	P030RC	3	0,85	920	LH280922	<b>9.916,00</b>
1000	Kprime	P030RC	3	1,13	1060	LH280923	<b>10.776,00</b>
1200	Kprime	P030RC	4	1,42	1220	LH280924	<b>12.269,00</b>
1400	Kprime	P030RC	4	1,75	1350	LH280925	<b>12.960,00</b>
1500	Kprime	P030RC	5	1,87	1430	LH280926	<b>13.618,00</b>
1600	Kprime	P030RC	5	2,02	1480	LH280927	<b>14.678,00</b>



**HTL 35 HD QC Heavy-Duty bucket**

with Lehmatic adapter SW 25

for demolition and rock, cutting edge 300x50mm (500 HB), base, side cutting edge and side wear protection out of 400 HB steel, wear protection plates on base (500 HB), with tooth system Kprime P030RC.

Surcharge for HS25V protection: 241,- EUR

Surcharge for SQ80 adapter incl. dirt protection: 180,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
800	Kprime	P030RC	3	0,85	960	LH280928	<b>9.916,00</b>
1000	Kprime	P030RC	3	1,13	1020	LH280929	<b>10.776,00</b>
1200	Kprime	P030RC	4	1,42	1250	LH280930	<b>12.269,00</b>
1400	Kprime	P030RC	4	1,75	1370	LH280931	<b>12.960,00</b>
1500	Kprime	P030RC	5	1,87	1460	LH280932	<b>13.618,00</b>
1600	Kprime	P030RC	5	2,02	1520	LH280933	<b>14.678,00</b>
1800	Kprime	P030RC	5	2,32	1630	LH280962	<b>15.733,00</b>



### HG 35 S Ditch bucket, rigid version

optionally with direct suspension for PC290

or quickcoupler suspension SW 25. Round bucket shape, base out of 400 HB steel, cutting edge 250x30mm out of 500 HB steel, with lateral water drain bores and rear cutting edge.

Surcharge for HS25V protection: 241,- EUR

Surcharge for SQ80 adapter incl. dirt protection: 180,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
2000	Direct Susp.	-	-	1,40	1140	LH253902	<b>9.130,00</b>
2000	SW 21/25	-	-	1,40	1140	LH253898	<b>9.130,00</b>
2200	Direct Susp.	-	-	1,56	1270	LH253903	<b>9.485,00</b>
2200	SW 21/25	-	-	1,56	1270	LH253900	<b>9.485,00</b>



### HG 35 SH Tilting ditch bucket, compact round design

optionally with direct suspension for PC290

or quickcoupler suspension SW 25

2 x 45° tilting angle, 2 hydraulic cylinders with protected piston rods, with counter-balance valve, base out of 400 HB steel, cutting edge 300x40mm out of Lehborit 5000 (500 HB), with lateral water drain bores and rear cutting edge, with hydraulic hoses up to tilting head.

Surcharge for HS25V adapter: 2.860- EUR

Surcharge for SQ80V adapter: 2.723,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
2000	Direct Susp.	-	-	1,40	1740	LH253906	<b>15.432,00</b>
2000	SW 21/25	-	-	1,40	1740	LH270164	
2200	Direct Susp.	-	-	1,56	1840	LH253907	<b>15.439,00</b>
2200	SW 21/25	-	-	1,56	1840	LH253905	<b>15.439,00</b>



## Attachments for PC290

**HU 35 RH Universal tilting bucket**

**backhoe bucket shape with round side part with quickcoupler suspension SW 25**

2 x 45° tilting range, 2 hydraulic cylinders with protected piston rods and counter-balance valve, base out of 400 HB steel, cutting edge 300x40mm out of Leborit 5000 (500 HB), with hydraulic hoses up to tilting head, with wear resistant plates on base (500 HB).

Surcharge for HS25V adapter: 2.860,- EUR  
Surcharge for SQ80V adapter: 2.723,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1800	SW 21/25	-	-	1,850	1835	LH270163	<b>18.053,00</b>

**HU 35 RM Universal tilting bucket**

**backhoe bucket shape with round side part with quickcoupler suspension SW 25**

2 x 45° tilting range, with hydraulic tilt motor, base out of 400 HB steel, cutting edge 300x40mm out of Leborit 5000 (500 HB), wear resistant plates on base (500 HB).

Surcharge for HS25V adapter: 2.860,- EUR  
Surcharge for SQ80V adapter: 2.723,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1600	SW 21/25	-	-	1,65	2150	LH242545	<b>38.315,00</b>
1800	SW 21/25	-	-	1,85	2240	LH242423	<b>38.844,00</b>

**HSL 35 Sorting bucket with rectangular bars**

**with Lehmatic adapter SW 25**

Base made of solid rectangular bars 70x50mm, 60mm spacing, cutting edge 300x50mm (500 HB), side edges (400 HB), with teeth Kprime P030SC .

Surcharge for HS25V protection: 241,- EUR  
Surcharge for SQ80 adapter incl. dirt protection: 180,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1500	Kprime	P030SC	5	1,870	1980	LH282499	<b>16.034,00</b>



### HSL 35 Sorting bucket round bars

#### with Symlock adapter SW25

Base with round bars D60 made of 400HB steel, 60mm hole width, cutting edge 300x50mm (500 HB), side edges (400 HB), with teeth Kprime P030SC.

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1500		P030SC	5	1,870	1980		<b>16.034,00</b>



### HRZ 38 bionic Ripper tooth

for demolition and rock use - with Lehmatic adapter SW 21/25

Option	Tooth point	Angle	Tooth-radius [mm]	Weight [kg]	PN	Price [€]
	9W2452	35	1250	485	LH228069	<b>7.724,00</b>



### HSG 35 Demolition and sorting grab

compact design, grab shells out of Hardox 400, interchangeable cutting edges out of Hardox 500, incl. counter-balance valve, rotating angle 360° endless, incl. screwed Lehmatic adapter SW 25. Grab shells closed or with rectangular bars on demand.

Surcharge for HS 25V adapter: 1.950,- EUR

Surcharge for SQ80 adapter: 2.214,- EUR

Opening clearance [mm]	Width [mm]	Capacity SAE [m <sup>3</sup> ]	Grab force [kN]	Weight [kg]	PN	Price [€]
2425	1200	0,900	70	2270	LH264717	<b>39.494,00</b>



## Attachments for PC360/HB365/PC390 HRD excav. boom

**MS 25 Quickcoupler mechanical**

for PC360/HB365/PC390 excav. boom

Quickcoupler with mechanical locking, incl. socket wrench, optionally with 18t load hook

Type	Excavator	Option	Weight [kg]	PN	Price [€]
MS 25	PC360-PC390	-	330	LH104622	<b>8.662,00</b>
MS 25	PC360-PC390	Load hook 18t	340	LH206848	<b>9.258,00</b>

**HS 25 DL Quickcoupler hydraulic**

for PC360/HB365/PC390 excav. boom

Quickcoupler with hydraulic locking, with 18t load hook.

**With safety locking mechanism Double Lock**

Type	Excavator	Option	Weight [kg]	PN	Price [€]
HS 25 DL	PC360-PC390	Load hook 18t	340	LH281752	<b>11.620,00</b>

**HS 25V DL Quickcoupler fully hydraulic**

for PC360/HB365/PC390 excav. boom

Fully hydraulic Quickcoupler with 2 valves KV4, 1 valve KV3, 2 valves KV1, two 18 t load hooks, valve block's internal depressurizing circuit (BiD) incl., hoses from valve block to flange, excl. hydr. installation kit and installation.

**NEW: With safety locking mechanism Double Lock**

Type	Excavator	Option	Weight [kg]	PN	Price [€]
HS 25 DL	PC360-PC390	2x Load hook 18t	340	LH284387	<b>20.645,00</b>

### SW 21/25 Adapter

Adapters SW 21/25 for bucket modification and for screwing or welding on other attachments.

	Description	Weight [kg]	PN	Price [€]
	<b>Adapter plate SW 21/25 -standard-</b> for bucket modification, Base plate: 600x530x30mm	147	LH100577	<b>1.664,00</b>
	<b>Adapter plate SW 21/25 HD -reinforced-</b> for bucket modification, Base plate: 700x550x40mm	188	LH257849	<b>2.237,00</b>
	<b>Weld-on adapter SW 21/25</b> for hammers, shears etc. Base plate: 752x665x40mm	250	LH238536	<b>2.959,00</b>
	<b>Screwed adapter SW 21/25 -standard-</b> for hammers, shears etc.	250		<b>3.386,00</b>
	<b>Screwed adapter SW 21/25 HD -reinforced-</b> for hammers, shears etc.	300		<b>4.403,00</b>
	<b>Grab adapter SW 21/25</b> for hydraulic grabs, with cross bar	205		<b>3.717,00</b>
	<b>Universal adapter SW 21/25 W=665mm</b> for individual drilling patterns or welding Base plate 665x752x40mm, Bottom side machined and planned.	300	LH279159	<b>2.988,00</b>
	<b>Universal adapter SW 21/25 W=735mm</b> for individual drilling patterns or welding Base plate 735x752x40mm, Bottom side machined and planned.	310	LH269783	<b>3.024,00</b>
	<b>Universal adapter SW 21/25 B=755mm</b> for individual drilling patterns or welding Base plate 755x752x40mm, Bottom side machined and planned.	320	LH269805	<b>3.082,00</b>










## Attachments for PC360/HB365/PC390 HRD excav. boom

**SW 21V/25V Adapter**

Screw-adapter SW 21V/25V with valve configuration for various attachments (Please specify attachment type)

	Description	Weight [kg]	Price [€]
	<b>Screwed adapter SW 21V/25V</b> for hydraulic hammers, valves: 2x KV4, plus installation and hoses	316	<b>4.794,00</b>
	<b>Screwed adapter SW 21V/25V</b> for sorting grabs/shears, valves: 2x KV4, 2x KV1, plus installation and hoses	316	<b>5.336,00</b>
	<b>Screwed adapter HS 21V/25V</b> for cutting units/compactors, valves: 2x KV4, 1x KV3, plus installation and hoses	316	<b>5.336,00</b>
	<b>Screwed adapter SW 21V/25V</b> for rotating compactors, valves: 2x KV4, 2x KV1, 1x KV3, plus installation and hoses	316	<b>5.459,00</b>
	<b>Grab adapter SW 21V/25V</b> for suspended grabs, with cross bar, valves: 2x KV1, 2x KV4, plus installation and hoses	250	<b>5.324,00</b>



### SQ 80H LSC Quickcoupler hydraulic, symmetrical

#### for PC360/HB365/PC390 excav. boom

Hydraulic symmetrical quickcoupler, based on S-standard, with LSC safety assistance system as standard. one 18 t load hook, installation kit and installation not included.



Type	Excavator	Option	Weight [kg]	PN	Price [€]
SQ 80H LSC	PC360-PC390	1x Hook 18t	396	LH283339	<b>13.850,00</b>
LSC install. kit electr.				LH249489	<b>1.069,00</b>

### SQ 80V LSC Quickcoupler fully hydraulic, symmetrical

#### for PC360/HB365/PC390 excav. boom

Fully hydraulic symmetrical quickcoupler, based on S standard. Fully hydraulic symmetrical Quickcoupler, with 2 valves KV4, 1 valve KV3 and 2 valves KV1, one 18 t load hook, with Lehmatic Safety Control (LSC) as standard, valve block's internal depressurizing circuit (BiD) incl., installation kit and installation not included.

Also available as hydraulic version.








Type	Excavator	Option	Weight [kg]	PN	Price [€]
SQ 80V LSC	PC360-PC390	1x Hook 18t	418	LH282657	<b>16.960,00</b>
SQ 80V LSC	PC360-PC390	2x Hook 18t	430	LH282658	<b>17.556,00</b>
LSC install. kit electr.				LH249489	<b>1.069,00</b>



## Attachments for PC360/HB365/PC390 HRD excav. boom





## SQ 80H Adapter

	Description	Weight [kg]	PN	Price [€]
	<b>Adapter Frame SQ 80 for bucket modification</b> for use with SQH80	141	LH283680	<b>1.214,00</b>
	<b>Adapter Frame SQ 80 for bucket modification</b> incl. SQ valve dirt protection and tacking device, for use with SQH80 & SQE80	165	LH277716	<b>1.544,00</b>
	<b>Weld-on adapter SQ 80</b> for use with SQ80V for welding on various attachm.	433		<b>1.980,00</b>
	<b>Screwed adapter SQ 80</b> for use with SQH80 for hammers, grabs, compactors etc. exact type required!	356		<b>2.393,00</b>
	<b>Universal adapter SQ 80</b> for use with SQ 80H/80V. For individual drilling patterns, base plate 740x860x40mm. For use with SQ 80H/80V	345	283674	<b>2.016,00</b>



### SQ 80V Adapter

Screw-adapter SQ 80 with valve configuration for various attachments (Please specify attachment type)

	Description	Weight [kg]	Price [€]
	<b>Screwed adapter SQ 80V</b> for hydraulic hammers, valves: 2x KV4, plus installation and hoses	385	<b>4.657,00</b>
	<b>Screwed adapter SQ 80V</b> for cutting units/compactors, valves: 2x KV4, 1x KV3, plus installation and hoses	385	<b>4.951,00</b>
	<b>Screwed adapter SQ 80V</b> for sorting grabs/shears, valves: 2x KV4, 2x KV1, plus installation and hoses	385	<b>5.600,00</b>
	<b>Screwed adapter SQ 80V</b> for rotating compactors, valves: 2x KV4, 2x KV1, 1x KV3, plus installation and hoses	385	<b>5.835,00</b>



## Attachments for PC360/HB365

**HTL 35 GP General purpose bucket**

with direct suspension for PC360/HB365

**NEW design with tube reinforcement**

Cutting edge 300x50mm (500 HB), sandwich constructed base with 400 HB steel, side wear protection (400 HB), with tooth system Kprime P030SC

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
800	Kprime	P030SC	3	0,85	890	LH280938	<b>8.264,00</b>
1000	Kprime	P030SC	3	1,13	1010	LH280939	<b>9.175,00</b>
1200	Kprime	P030SC	4	1,42	1160	LH280940	<b>9.946,00</b>
1400	Kprime	P030SC	4	1,75	1290	LH280941	<b>10.554,00</b>
1500	Kprime	P030SC	5	1,87	1430	LH280942	<b>11.341,00</b>
1600	Kprime	P030SC	5	2,02	1646	LH294613	<b>11.860,00</b>
1800	Kprime	P030SC	5	2,32	1720	LH294612	<b>13.234,00</b>
2000	Kprime	P030SC	6	2,54	1780	LH280945	<b>14.607,00</b>

**HTL 35 GP QC General purpose bucket**

with Lehmatic adapter SW 25

Cutting edge 300x50mm (500 HB), sandwich constructed base with 400 HB steel, side wear protection (400 HB), with tooth system Kprime P030SC.

Surcharge for HS25V adapter: 241,- EUR

Surcharge for SQ80 adapter incl. dirt protection: 180,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
800	Kprime	P030SC	3	0,85	875	LH280947	<b>8.264,00</b>
1000	Kprime	P030SC	3	1,13	1010	LH280948	<b>9.175,00</b>
1200	Kprime	P030SC	4	1,42	1230	LH280949	<b>9.946,00</b>
1400	Kprime	P030SC	4	1,75	1330	LH280950	<b>10.554,00</b>
1500	Kprime	P030SC	5	1,87	1420	LH280951	<b>11.341,00</b>
1600	Kprime	P030SC	5	2,02	1480	LH280952	<b>11.860,00</b>
1800	Kprime	P030SC	5	2,32	1590	LH280953	<b>13.234,00</b>
2000	Kprime	P030SC	6	2,54	1690	LH280954	<b>14.607,00</b>



### HTL 35 HD Heavy-Duty bucket

with direct suspension for PC360/HB365

**NEW design with tube reinforcement**

for demolition and rock, cutting edge 300x50mm (500 HB), base, side cutting edge and side wear protection out of 400 HB steel, wear resistant plates on base (500 HB), with tooth system Kprime P030RC



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
800	Kprime	P030RC	3	0,85	980	LH280955	<b>9.916,00</b>
1000	Kprime	P030RC	3	1,13	1060	LH280956	<b>10.776,00</b>
1200	Kprime	P030RC	4	1,42	1340	LH280957	<b>12.269,00</b>
1400	Kprime	P030RC	4	1,75	1410	LH294611	<b>12.960,00</b>
1500	Kprime	P030RC	5	1,87	1500	LH294610	<b>13.618,00</b>
1600	Kprime	P030RC	5	2,02	1570	LH294609	<b>14.678,00</b>
1800	Kprime	P030RC	5	2,32	1780	LH280961	<b>15.733,00</b>

### HTL 35 HD QC Heavy-Duty bucket

with Lehmatic adapter SW 25

for demolition and rock, cutting edge 300x50mm (500 HB), base, side cutting edge and side wear protection out of 400 HB steel, wear protection plates on base (500 HB), with tooth system Kprime P030RC.

Surcharge for HS25V protection: 241,- EUR

Surcharge for SQ80 adapter incl. dirt protection: 180,- EUR



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
800	Kprime	P030RC	3	0,85	960	LH280928	<b>9.916,00</b>
1000	Kprime	P030RC	3	1,13	1020	LH280929	<b>10.776,00</b>
1200	Kprime	P030RC	4	1,42	1250	LH280930	<b>12.269,00</b>
1400	Kprime	P030RC	4	1,75	1370	LH280931	<b>12.960,00</b>
1500	Kprime	P030RC	5	1,87	1460	LH280932	<b>13.618,00</b>
1600	Kprime	P030RC	5	2,02	1520	LH280933	<b>14.678,00</b>
1800	Kprime	P030RC	5	2,32	1630	LH280962	<b>15.733,00</b>



## Attachments for PC360/HB365

**HTL 35 SH Severe-Heavy-Duty Bucket**

with direct suspension for PC360/HB365

**NEW design with tube reinforcement**

for demolition and rock, trapezoidal cutting edge 300x50mm (Hardox HiTuf), base, side cutting edge and side wear protection out of 400 HB steel, wear resistant plates on base (500 HB), plus additional wear protection, with tooth system Kprime P040RC

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1400	Kprime	P040RC	4	1,75	1670	LH282220	<b>19.095,00</b>
1600	Kprime	P040RC	5	2,02	1850	LH282221	<b>21.607,00</b>

**HTL 35 SH QC Severe-Heavy-Duty Bucket**

with Lehmatic adapter SW 25

for demolition and rock, trapezoidal cutting edge 300x50mm (Hardox HiTuf), base, side cutting edge and side wear protection out of 400 HB steel, wear resistant plates on base (500 HB), plus additional wear protection, with tooth system Kprime P040RC.

Surcharge for HS25V protection: 241,- EUR

Surcharge for SQ80 adapter incl. dirt protection: 180,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1400	Kprime	P040RC	4	1,75	1640	LH282222	<b>19.095,00</b>
1600	Kprime	P040RC	5	2,02	1810	LH282223	<b>21.607,00</b>

**HSL 35 Sorting bucket with rectangular bars**

with Lehmatic adapter SW 25

Base made of solid rectangular bars 70x50mm, 60mm spacing, cutting edge 300x50mm (500 HB), side edges (400 HB), with teeth Kprime P030SC .

Surcharge for HS25V protection: 241,- EUR

Surcharge for SQ80 adapter incl. dirt protection: 180,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1500	Kprime	P030SC	5	1,870	1980	LH282499	<b>16.034,00</b>



### HSL 35 Sorting bucket round bars

#### with Symlock adapter SW25

Base with round bars D60 made of 400HB steel, 60mm hole width, cutting edge 300x50mm (500 HB), side edges (400 HB), with teeth Kprime P030SC.



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1500		P030SC	5	1,870	1980		<b>16.034,00</b>

### HRZ 38 bionic Ripper tooth

for demolition and rock use - with Lehmatic adapter SW 21/25



Option	Tooth point	Angle	Tooth-radius [mm]	Weight [kg]	PN	Price [€]
	9W2452	35	1250	485	LH228069	<b>7.724,00</b>

### HSG 35 Demolition and sorting grab

compact design, grab shells out of Hardox 400, interchangeable cutting edges out of Hardox 500, incl. counter-balance valve, rotating angle 360° endless, incl. screwed Lehmatic adapter SW 25. Grab shells closed or with rectangular bars on demand.

Surcharge for HS 25V adapter: 1.950,- EUR

Surcharge for SQ80 adapter: 2.214,- EUR



Opening clearance [mm]	Width [mm]	Capacity SAE [m <sup>3</sup> ]	Grab force [kN]	Weight [kg]	PN	Price [€]
2425	1200	0,900	70	2270	LH264717	<b>39.494,00</b>





## Attachments for PC490LC/PC490HRD excav. boom

**HS 40/55 LSC Quickcoupler hydraulic****for PC490LC/PC490HRD excav. boom**

Quickcoupler with hydraulic locking, optionally with 18t load hook.  
As standard with LSC (Lehmatic Safety Control)

Type	Excavator	Option	Weight [kg]	PN	Price [€]
HS 40 /55 LSC	PC490	Load hook 18t	640	LH257076	<b>18.129,00</b>
Install. kit hydr. 24V		incl. QC valve		LH249493	<b>967,00</b>
LSC install. kit electr.				LH249489	<b>1.069,00</b>

**HS 40V LSC Quickcoupler fully hydraulic****for PC490LC/PC490HRD excav. boom**

Fully hydraulic Quickcoupler with 2 valves KV6, 1 valve KV3, 2 valves KV1, two 18 t load hooks, Safety sensors LSC inside of QC incl., valve blocks internal depressurizing circuit (BiD) incl., installation on excavator not included.

Type	Excavator	Option	Weight [kg]	PN	Price [€]
HS 40V LSC	PC490	2x Hook 18t	780	LH252628	<b>32.382,00</b>
Install. kit hydr. 24V		incl. QC valve		LH249493	<b>967,00</b>
LSC install. kit electr.				LH249489	<b>1.069,00</b>





**SQ 90V LSC Quickcoupler fully hydraulic, symmetrical****for PC490LC/PC490HRD excav. boom**

Fully hydraulic symmetrical quickcoupler, based on S standard. Fully hydraulic symmetrical Quickcoupler, with 2 valves KV6, 1 valve KV3 and 2 valves KV1, optionally another KV3 valve for water and a KV1 for grease, one 18 t load hook, with Lehmatic Safety Control (LSC) as standard, valve block's internal depressurizing circuit (BiD) incl., installation kit and installation not included.  
Also available as hydraulic version.

Type	Excavator	Option	Weight [kg]	PN	Price [€]
<b>SQ 90V LSC</b>	PC490	1x Hook 18t	750-800	LH288106	<b>27.160,00</b>
LSC install. kit electr.				LH249489	<b>1.069,00</b>







### SW 40 Adapter

Adapters SW 40 for bucket modification and for welding on other attachments.

Description	Weight [kg]	PN	Price [€]
 <b>Adapter plate SW 40 / 55 -standard-</b> for bucket modification, Base plate 885x750x40mm	390	LH101870	<b>5.038,00</b>
 <b>Adapter plate SW 40 / 70 HD -reinforced-</b> for bucket modification, base plate 960x755x50mm	520	LH254049	<b>6.549,00</b>
 <b>Weld-on adapter SW 40 / 55 and SW 40 / 70</b> for hammers, shears etc.	820	LH206336	<b>6.999,00</b>
 <b>Screwed adapter SW 40 / 55 and SW 40 / 70</b> for hammers, shears etc.	710		

### SW 40V/70V Adapter

Screw-adapter SW 40V/70V with valve configuration for various attachments (Please specify attachment type)






Description	Weight [kg]	PN	Price [€]
 <b>Screwed adapter SW 40V</b> for hydraulic hammers, valves: 2x KV6, plus installation and hoses	ca. 670		<b>11.873,00</b>
 <b>Screwed adapter SW 40V</b> for cutting units/compactors, valves: 2x KV6, 1x KV3, plus installation and hoses	ca. 670		<b>12.114,00</b>
 <b>Screwed adapter SW 40V</b> for sorting grabs/shears, valves: 2x KV6, 2x KV1, plus installation and hoses	ca. 670		<b>12.353,00</b>
 <b>Screwed adapter SW 70V</b> for hydraulic hammers, valves: 2x KV6, plus installation and hoses	ca. 670		<b>13.060,00</b>
 <b>Screwed adapter SW 70V</b> for cutting units/compactors, valves: 2x KV6, 1x KV3, plus installation and hoses	ca. 670		<b>13.324,00</b>
 <b>Screwed adapter SW 70V</b> for sorting grabs/shears, valves: 2x KV6, 2x KV1, plus installation and hoses	ca. 670		<b>13.590,00</b>



## Attachments for PC490LC/PC490HRD excav. boom

**SQ 90V Adapter**

SQ 90 adapter for bucket modification and screw-on adapter with valve configuration for various attachments

	Description	Weight [kg]	Price [€]
	<b>Adapter Frame SQ 90 for bucket modification</b> incl. SQ valve dirt protection and tacking device, for use with SQ90V	222	<b>3.180,00</b>
	<b>Weld-on adapter SQ 90</b> for welding on various attachm. For use with SQ 90V	433	<b>3.720,00</b>
	<b>Screwed adapter SQ 90V</b> for hydraulic hammers, valves: 2x KV6, plus installation and hoses	530-555	<b>8.490,00</b>
	<b>Screwed adapter SQ 90V</b> for cutting units/compactors, valves: 2x KV6, 1x KV3, plus installation and hoses	530-555	<b>8.790,00</b>
	<b>Screwed adapter SQ 90V</b> for sorting grabs/shears, valves: 2x KV6, 2x KV1, plus installation and hoses	530-555	<b>9.080,00</b>



### HTL 40 GP General purpose bucket

with direct suspension for PC490

**NEW design with tube reinforcement**

Cutting edge 400x60mm (400 HB), sandwich-constructed base out of 400 HB steel, side wear protection (400 HB), with tooth system Kprime P040SC



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
800	Kprime	P040SC	3	1,07	1190	LH281948	<b>12.296,00</b>
1000	Kprime	P040SC	3	1,34	1370	LH281949	<b>13.108,00</b>
1200	Kprime	P040SC	4	1,69	1540	LH281950	<b>14.148,00</b>
1500	Kprime	P040SC	4	2,22	1780	LH281951	<b>15.656,00</b>
1600	Kprime	P040SC	5	2,40	2010	LH281952	<b>16.936,00</b>
1800	Kprime	P040SC	5	2,76	2190	LH281953	<b>18.380,00</b>
2000	Kprime	P040SC	6	3,10	2380	LH281954	<b>19.822,00</b>

### HTL 40 GP QC General purpose bucket

with Lehmatic adapter SW 40

Cutting edge 400x60mm (400 HB), sandwich-constructed base out of 400 HB steel, side wear protection (400 HB), with tooth system Kprime P040SC.

Surcharge for HS40V protection: 241,- EUR



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
800	Kprime	P040SC	3	1,07	1190	LH281957	<b>12.296,00</b>
1000	Kprime	P040SC	3	1,34	1370	LH281958	<b>13.108,00</b>
1200	Kprime	P040SC	4	1,69	1540	LH281959	<b>14.148,00</b>
1500	Kprime	P040SC	4	2,22	1780	LH281960	<b>15.656,00</b>
1600	Kprime	P040SC	5	2,40	2010	LH281961	<b>16.936,00</b>
1800	Kprime	P040SC	5	2,76	2190	LH281962	<b>18.380,00</b>
2000	Kprime	P040SC	6	3,10	2380	LH281964	<b>19.822,00</b>



Attachments for PC490LC/PC490HRD excav. boom



**HTL 40 HD Heavy-Duty bucket**

with direct suspension for PC490

**NEW design with tube reinforcement**

for demolition and rock, cutting edge 400x60mm (400 HB), base, side cutting edge and side wear protection out of 400 HB steel, wear resistant plates on base (500 HB), with tooth system Kprime P050RC

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
800	Kprime	P050RC	2	1,07	1330	LH281983	<b>15.304,00</b>
1000	Kprime	P050RC	3	1,34	1490	LH281984	<b>16.877,00</b>
1200	Kprime	P050RC	3	1,69	1704	LH281985	<b>17.836,00</b>
1500	Kprime	P050RC	4	2,22	1994	LH281986	<b>20.945,00</b>
1600	Kprime	P050RC	4	2,40	2107	LH281987	<b>22.491,00</b>
1800	Kprime	P050RC	5	2,76	2247	LH294613	<b>25.376,00</b>
2000	Kprime	P050RC	5	3,10	2487	LH281989	<b>25.671,00</b>



**HTL 40 HD QC Heavy-Duty bucket**

with Lehmatic adapter SW 40

for demolition and rock, cutting edge 400x60mm (400 HB), base, side cutting edge and side wear protection out of 400 HB steel, wear resistant plates on base (500 HB), with tooth system Kprime P050RC. Surcharge for HS40V protection: 248,- EUR

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
800	Kprime	P050RC	2	1,07	1330	LH281993	<b>15.304,00</b>
1000	Kprime	P050RC	3	1,34	1490	LH281994	<b>16.877,00</b>
1200	Kprime	P050RC	3	1,69	1704	LH281995	<b>17.836,00</b>
1500	Kprime	P050RC	4	2,22	1994	LH281996	<b>20.945,00</b>
1600	Kprime	P050RC	4	2,40	2107	LH281997	<b>22.491,00</b>
1800	Kprime	P050RC	5	2,76	2247	LH281998	<b>25.376,00</b>
2000	Kprime	P050RC	5	3,10	2487	LH281999	<b>25.671,00</b>



### HTL 40 SH Severe-Heavy-Duty Bucket

with direct suspension for PC490

**NEW design with tube reinforcement**

for demolition and rock, trapezoidal cutting edge T400x70mm (Hardox HiTuf), base, side cutting edge and side wear protection out of 400 HB steel, wear resistant plates on base (500 HB), plus additional wear protection, optionally with tooth system Kprime P050RC



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1400	Kprime	P050RC	4	2,04	2230	LH282003	<b>27.120,00</b>
1600	Kprime	P050RC	4	2,40	2395	LH282004	<b>30.348,00</b>
1800	Kprime	P050RC	5	2,76	2972	LH282005	<b>32.370,00</b>

### HTL 40 SH QC Severe-Heavy-Duty Bucket

with Lehmatic adapter SW 40

for demolition and rock, trapezoidal cutting edge T400x70mm (Hardox HiTuf), base, side cutting edge and side wear protection out of 400 HB steel, wear protection plates on base (500 HB), plus additional wear protection, optionally with tooth system Kprime P050RC.

Surcharge for HS40V protection: 248,- EUR



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1400	Kprime	P050RC	4	2,04	2230	LH282006	<b>27.120,00</b>
1600	Kprime	P050RC	4	2,40	2395	LH282007	<b>30.348,00</b>
1800	Kprime	P050RC	5	2,76	2972	LH282008	<b>32.370,00</b>



## Attachments for PC490LC/PC490HRD excav. boom

**HSL 40** Sorting bucket round bars

## with Symlock adapter SW40

Base with round bars D70 made of 400HB steel, 60mm hole width, cutting edge 400x60mm (500 HB), side edges (400 HB), with teeth Kprime P050RC.

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1800		P040SC	5	2,800	2600		<b>21.984,00</b>

**HRZ 50** bionic Ripper toothwith direct suspension for PC490  
or quickcoupler suspension SW 40

for demolition and rock use, with tooth system Hensley HLT4T4502HX

Option	Tooth point	Angle	Tooth-radius [mm]	Weight [kg]	PN	Price [€]
Direct Susp.	HLT4T4502	35	1350	1065	LH253998	<b>12.762,00</b>
SW 40	HLT4T4502	35	1350	1065	LH107151	<b>12.762,00</b>

**HSG 50** Demolition and sorting grab

compact design, grab shells out of Hardox 400, interchangeable cutting edges out of Hardox 500, incl. counter-balance valve, rotating angle 360° endless, incl. screwed Lehmatic adapter SW 40. Grab shells closed or with rectangular bars on demand.

Surcharge for HS 40V adapter: 4.314,- EUR

Opening clearance [mm]	Width [mm]	Capacity SAE [m <sup>3</sup> ]	Grab force [kN]	Weight [kg]	PN	Price [€]
2425	1400	1,100	80	2995	LH264718	<b>44.826,00</b>



### HS 40/70 LSC Quickcoupler hydraulic

#### for PC700 (bracket 608mm/678mm)

Quickcoupler with hydraulic locking, optionally with one 18t load hook. As standard with LSC (Lehmatic Safety Control)



Type	Excavator	Option	Weight [kg]	PN	Price [€]
HS 40 /70 LSC	PC700	bracket 608mm	720	LH270935	<b>20.830,00</b>
HS 40 /70 LSC	PC700	bracket 678mm	730	LH270933	<b>20.830,00</b>
Install. kit hydr. 24V		incl. QC valve		LH249493	<b>967,00</b>
LSC install. kit electr.				LH249489	<b>1.069,00</b>

### HS 70V LSC Quickcoupler fully hydraulic

#### for PC700 (bracket 608mm/678mm)

Fully hydraulic Quickcoupler with 2 valves KV6, 1 valve KV3, 2 valves KV1, two 18 t load hooks, Safety sensors LSC inside of QC incl., valve blocks internal depressurizing circuit (BID) incl., installation on excavator not included.



Type	Excavator	Option	Weight [kg]	PN	Price [€]
HS 70V LSC	PC700	bracket 608mm	830	on demand	<b>35.083,00</b>
HS 70V LSC	PC700	bracket 678mm	840	on demand	<b>35.083,00</b>
Install. kit hydr. 24V		incl. QC valve		LH249493	<b>967,00</b>
LSC install. kit electr.				LH249489	<b>1.069,00</b>

### SQ 90V LSC Quickcoupler fully hydraulic, symmetrical

#### for PC700

Fully hydraulic symmetrical quickcoupler, based on S standard. Fully hydraulic symmetrical Quickcoupler, with 2 valves KV6, 1 valve KV3 and 2 valves KV1, optionally another KV3 valve for water and a KV1 for grease, one 18 t load hook, with Lehmatic Safety Control (LSC) as standard, valve block's internal depressurizing circuit (BiD) incl., installation kit and installation not included.



Type	Excavator	Option	Weight [kg]	PN	Price [€]
<b>SQ 90V LSC</b>	PC700	bracket 608mm	750-800	on demand	<b>27.160,00</b>
<b>SQ 90V LSC</b>	PC700	bracket 678mm	750-800	LH295476	<b>27.160,00</b>
LSC install. kit electr.				LH249489	<b>1.069,00</b>









## Attachments for PC700







**SW 40 Adapter**

Adapters SW 40 for bucket modification and for welding on other attachments.

	Description	Weight [kg]	PN	Price [€]
	<b>Adapter plate SW 40 / 55 -standard-</b> for bucket modification, Base plate 885x750x40mm	390	LH101870	<b>5.038,00</b>
	<b>Adapter plate SW 40 / 70 HD -reinforced-</b> for bucket modification, base plate 960x755x50mm	520	LH254049	<b>6.549,00</b>
	<b>Weld-on adapter SW 40 / 55 and SW 40 / 70</b> for hammers, shears etc.	820	LH206336	<b>6.999,00</b>
	<b>Screwed adapter SW 40 / 55 and SW 40 / 70</b> for hammers, shears etc.	710		

**SW 40V/70V Adapter**









Screw-adapter SW 40V/70V with valve configuration for various attachments (Please specify attachment type)

	Description	Weight [kg]	PN	Price [€]
	<b>Screwed adapter SW 40V</b> for hydraulic hammers, valves: 2x KV6, plus installation and hoses	ca. 670		<b>11.873,00</b>
	<b>Screwed adapter SW 40V</b> for cutting units/compactors, valves: 2x KV6, 1x KV3, plus installation and hoses	ca. 670		<b>12.114,00</b>
	<b>Screwed adapter SW 40V</b> for sorting grabs/shears, valves: 2x KV6, 2x KV1, plus installation and hoses	ca. 670		<b>12.353,00</b>
	<b>Screwed adapter SW 70V</b> for hydraulic hammers, valves: 2x KV6, plus installation and hoses	ca. 670		<b>13.060,00</b>
	<b>Screwed adapter SW 70V</b> for cutting units/compactors, valves: 2x KV6, 1x KV3, plus installation and hoses	ca. 670		<b>13.324,00</b>
	<b>Screwed adapter SW 70V</b> for sorting grabs/shears, valves: 2x KV6, 2x KV1, plus installation and hoses	ca. 670		<b>13.590,00</b>



## SQ 90V Adapter

SQ 90 adapter for bucket modification and screw-on adapter with valve configuration for various attachments

	Description	Weight [kg]	Price [€]
	<b>Adapter Frame SQ 90 for bucket modification</b> incl. SQ valve dirt protection and tacking device, for use with SQ90V	222	<b>3.180,00</b>
	<b>Weld-on adapter SQ 90</b> for welding on various attachm. For use with SQ 90V	433	<b>3.720,00</b>
 	<b>Screwed adapter SQ 90V</b> for hydraulic hammers, valves: 2x KV6, plus installation and hoses	530-555	<b>8.490,00</b>
 	<b>Screwed adapter SQ 90V</b> for cutting units/compactors, valves: 2x KV6, 1x KV3, plus installation and hoses	530-555	<b>8.790,00</b>
 	<b>Screwed adapter SQ 90V</b> for sorting grabs/shears, valves: 2x KV6, 2x KV1, plus installation and hoses	530-555	<b>9.080,00</b>



Attachments for PC700



**HTL 50 HD Heavy-Duty bucket**

Direct suspension, bracket size 608mm

**NEW design with tube reinforcement**

trapezoid cutting edge T500x70mm (400 HB), base and side cutting edges out of 400 HB steel, wear resistant plates on base (400 HB, 500 HB edges), with Kprime adapter 1070P050 and tooth P070RC.

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1600	Kprime	P070RC	4	3,00	3.050	LH282032	<b>31.839,00</b>
1800	Kprime	P070RC	4	3,50	3.300	LH282033	<b>35.151,00</b>
2000	Kprime	P070RC	5	3,90	3.450	LH282034	<b>36.749,00</b>



**HTL 50 HD Heavy-Duty bucket**

Direct suspension, bracket size 678mm

**NEW design with tube reinforcement**

trapezoid cutting edge T500x70mm (400 HB), base and side cutting edges out of 400 HB steel, wear resistant plates on base (400 HB, 500 HB edges), with Kprime adapter 1070P070 and tooth P070RC.

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1600	Kprime	P070RC	4	3,00	3.050	LH282037	<b>31.839,00</b>
1800	Kprime	P070RC	4	3,50	3.300	LH282038	<b>35.151,00</b>
2000	Kprime	P070RC	5	3,90	3.450	LH282039	<b>36.749,00</b>
2200	Kprime	P070RC	5	4,40	3.850	LH282040	<b>41.009,00</b>



**HTL 50 HD QC Heavy-Duty bucket**

Quickcoupler suspension SW 40

trapezoid cutting edge T500x70mm (400 HB), base and side cutting edges out of 400 HB steel, wear resistant plates on base (400 HB, 500 HB edges), with Kprime adapter P070RC and tooth P070RC.

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1600	Kprime	P070RC	4	2,90	2.950	LH282044	<b>30.794,00</b>
1800	Kprime	P070RC	5	3,30	3.200	LH282045	<b>34.085,00</b>
2000	Kprime	P070RC	5	3,70	3.350	LH282046	<b>35.683,00</b>
2200	Kprime	P070RC	5	4,20	3.750	LH282047	<b>39.944,00</b>



### HTL 50 SH Severe-Heavy-Duty Bucket

Direct suspension, bracket size 608mm

**NEW design with tube reinforcement**

trapezoid cutting edge T500x80mm (Hardox HiTuf), base and side cutting edges out of 400 HB steel, wear resistant plates on base (400 HB, 500 HB edges), additional wear protection for cutting edges and base by shrouds, buttons and wear plates. With Kprime adapter 1080P085 and tooth P085RC.



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1600	Kprime	P085RC	4	3,00	3.850	LH282051	<b>45.931,00</b>
1800	Kprime	P085RC	4	3,50	4.050	LH282052	<b>48.316,00</b>
2000	Kprime	P085RC	4	3,90	4.300	LH282053	<b>52.673,00</b>

### HTL 50 SH Severe-Heavy-Duty Bucket

Direct suspension, bracket size 678mm

**NEW design with tube reinforcement**

trapezoid cutting edge T500x80mm (Hardox HiTuf), base and side cutting edges out of 400 HB steel, wear resistant plates on base (400 HB, 500 HB edges), additional wear protection for cutting edges and base by shrouds, buttons and wear plates. With Kmax tooth holder 1080P085 and tooth P085RC.



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1600	Kprime	P085RC	4	3,00	3.850	LH282056	<b>45.931,00</b>
1800	Kprime	P085RC	4	3,50	4.050	LH282057	<b>48.316,00</b>
2000	Kprime	P085RC	4	3,90	4.300	LH282058	<b>52.673,00</b>

### HTL 50 SH QC Severe-Heavy-Duty Bucket

Quickcoupler suspension SW 40

trapezoid cutting edge T500x80mm (Hardox HiTuf), base and side cutting edges out of 400 HB steel, wear resistant plates on base (400 HB, 500 HB edges), additional wear protection for cutting edges and base by shrouds, buttons and wear plates. with Kprime adapter 1080P085 and tooth P085RC.



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
1600	Kprime	P085RC	4	2,90	3.700	LH282060	<b>44.142,00</b>
1800	Kprime	P085RC	4	3,30	3.900	LH282061	<b>46.526,00</b>
2000	Kprime	P085RC	4	3,70	4.150	LH282062	<b>50.836,00</b>



## Attachments for PC700

**HRZ 70 bionic Ripper tooth****Quickcoupler suspension SW 40****for demolition and rock use, Komatsu adapter and tooth point HL4T4501**

Option	Tooth point	Angle	Tooth-radius [mm]	Weight [kg]	PN	Price [€]
	HL4T4501H-X	35	1571	1.790	LH225410	<b>22.308,00</b>



## HS 100 LSC Quickcoupler hydraulic

### for PC950




Quickcoupler with hydraulic locking, optionally with 18t load hook.  
As standard with LSC (Lehmatic Safety Control)



Type	Excavator	Option	Weight [kg]	PN	Price [€]
HS 100 LSC	PC950	-	1700	on demand	<b>44.580,00</b>
HS 100 LSC	PC950	Load hook 18t	1750	on demand	<b>45.649,00</b>

## SW 80/100 Adapter

Adapters SW 80/100 for bucket modification and for welding on other attachments.

Description	Weight [kg]	PN	Price [€]
 <b>Adapter frame SW 80/100</b> for bucket modification	810	LH117999	<b>12.407,00</b>
 <b>Adapter plate SW 80/100</b> for bucket modification	1420	LH117965	<b>14.524,00</b>
 <b>Screwed adapter SW 80/100</b> for hammers, shears etc.	1350		<b>17.057,00</b>



Attachments for PC950



**HTL 70 HD Heavy-Duty bucket**

**Direct suspension, bracket size 790mm  
NEW design with tube reinforcement**

trapezoid cutting edge T600x90mm (Hardox HiTuf), base and side cutting edges out of 400 HB steel, wear resistant plates on base (400 HB, 500 HB edges), with Kprime adapter 5090P120 and tooth P120RC.

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
2200	Kprime	P120RC	4	5,10	5.200	on demand	<b>59.530,00</b>
2400	Kprime	P120RC	4	5,60	5.600	on demand	<b>64.940,00</b>



**HTL 70 HD QC High Capacity bucket**

**Quickcoupler suspension SW 100 (arm 3,7m)**

trapezoid cutting edge T600x90mm (Hardox HiTuf), base and side cutting edges out of 400 HB steel, wear resistant plates on base (400 HB, 500 HB edges), with Kprime adapter 5090P120 and tooth P120RC.

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
2200	Kprime	P120RC	4	5,10	4.900	on demand	<b>56.890,00</b>
2400	Kprime	P120RC	4	5,60	5.300	on demand	<b>62.060,00</b>



**HTL 70 SH Severe-Heavy-Duty Bucket**

**Direct suspension, bracket size 790mm (arm 3,7m)  
NEW design with tube reinforcement**

trapezoid cutting edge T600x90mm (Hardox HiTuf), base and side cutting edges out of 400 HB steel, wear resistant plates on base (400 HB, 500 HB edges), additional wear protection for cutting edges and base by shrouds, buttons and wear plates. With Kprime Adapter 5090P120 and tooth P120RC.

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
2200	Kprime	P120RC	4	5,10	5.550	on demand	<b>65.480,00</b>
2400	Kprime	P120RC	4	5,60	6.000	on demand	<b>70.890,00</b>



### HTL 70 SH QC Severe-Heavy-Duty Bucket

#### Quickcoupler suspension SW 100 (arm 3,7m)

trapezoid cutting edge T600x90mm (Hardox HiTuf), base and side cutting edges out of 400 HB steel, wear resistant plates on base (400 HB, 500 HB edges), additional wear protection for cutting edges and base by shrouds, buttons and wear plates. With Kprime adapter 5090P120 and tooth P120RC.



Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
2200	Kprime	P120RC	4	5,10	5.250	on demand	<b>62.580,00</b>
2400	Kprime	P120RC	4	5,60	6.000	on demand	<b>68.530,00</b>



### HRZ 130 bionic Ripper tooth

for demolition and rock use - with Lehmatic adapter SW 100, Hensley adapter and HL9W4551HX tooth point

Option	Tooth point	Angle	Tooth-radius [mm]	Weight [kg]	PN	Price [€]
Susp. SW 100	HL9W4551-HX	35	1850	2.690	LH225683	<b>41.876,00</b>





Attachments for PC1250






**HS 100 LSC Quickcoupler hydraulic for PC1250**

Quickcoupler with hydraulic locking, optionally with 18t load hook. As standard with LSC (Lehmatic Safety Control)

Type	Excavator	Option	Weight [kg]	PN	Price [€]
HS 100 LSC	PC1250	-	1750	on demand	<b>44.580,00</b>
HS 100 LSC	PC1250	Load hook 18t	1750	on demand	<b>45.649,00</b>
LSC install. kit electr.				LH249489	<b>1.069,00</b>

**SW 80/100 Adapter**

Adapters SW 80/100 for bucket modification and for welding on other attachments.

	Description	Weight [kg]	PN	Price [€]
	<b>Adapter frame SW 80/100</b> for bucket modification	810	LH117999	<b>12.407,00</b>
	<b>Adapter plate SW 80/100</b> for bucket modification	1420	LH117965	<b>14.524,00</b>
	<b>Screwed adapter SW 80/100</b> for hammers, shears etc.	1350		<b>17.057,00</b>



### HTL 80 HD Heavy-Duty bucket

**Direct suspension, bracket size 840mm (arm 3,6m)**

**NEW design with tube reinforcement**

trapezoid cutting edge T600x90mm (Hardox HiTuf), base and side cutting edges out of 400 HB steel, wear resistant plates on base (400 HB, 500 HB edges), with Kprime adapter 5090P120 and tooth P120RC.

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
2100	Kprime	P120RC	4	5,40	6.400	LH282105	<b>69.535,00</b>



### HTL 80 HD Heavy-Duty bucket

**Direct suspension, bracket size 950mm (arm 2,9m)**

**NEW design with tube reinforcement**

trapezoid cutting edge T600x90mm (Hardox HiTuf), base and side cutting edges out of 400 HB steel, wear resistant plates on base (400 HB, 500 HB edges), with Kprime adapter 5090P120 and tooth P120RC.

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
2400	Kprime	P120RC	5	7,00	6.950	LH282106	<b>75.511,00</b>



### HTL 80 HD QC Heavy-Duty bucket

**Quickcoupler suspension SW 100 (arm 3,6m)**

trapezoid cutting edge T600x90mm (Hardox HiTuf), base and side cutting edges out of 400 HB steel, wear resistant plates on base (400 HB, 500 HB edges), with Kprime adapter 5090P120 and tooth P120RC.

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
2100	Kprime	P120RC	4	5,30	6.800	LH282107	<b>75.330,00</b>

## Attachments for PC1250

**HTL 80 HD QC Heavy-Duty bucket****Quickcoupler suspension SW 100 (arm 2,9m)**

trapezoid cutting edge T600x90mm (Hardox HiTuf), base and side cutting edges out of 400 HB steel, wear resistant plates on base (400 HB, 500 HB edges), with Kprime adapter 5090P120 and tooth P120RC.

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
2400	Kprime	P120RC	5	6,8	7.200	LH282108	<b>79.761,00</b>

**HTL 80 SH Severe-Heavy-Duty Bucket****Direct suspension, bracket size 840mm (arm 3,6m)****NEW design with tube reinforcement**

trapezoid cutting edge T600x90mm (Hardox HiTuf), base and side cutting edges out of 400 HB steel, wear resistant plates on base (400 HB, 500 HB edges), additional wear protection for cutting edges and base by shrouds, buttons and wear plates. With Kprime Adapter 5090P120 and tooth P120RC.

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
2100	Kprime	P120RC	4	5,40	6.750	LH282109	<b>75.650,00</b>

**HTL 80 SH Severe-Heavy-Duty Bucket****Direct suspension, bracket size 950mm (arm 2,9m)****NEW design with tube reinforcement**

trapezoid cutting edge T600x90mm (Hardox HiTuf), base and side cutting edges out of 400 HB steel, wear resistant plates on base (400 HB, 500 HB edges), additional wear protection for cutting edges and base by shrouds, buttons and wear plates. With Kprime adapter 5090P120 and tooth P120RC.

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
2400	Kprime	P120RC	5	7,00	7.300	LH282110	<b>81.858,00</b>



### HTL 80 SH QC Severe-Heavy-Duty Bucket

#### Quickcoupler suspension SW 100 (arm 3,6m)

trapezoid cutting edge T600x90mm (Hardox HiTuf), base and side cutting edges out of 400 HB steel, wear resistant plates on base (400 HB, 500 HB edges), additional wear protection for cutting edges and base by shrouds, buttons and wear plates. With Kprime adapter 5090P120 and tooth P120RC.

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
2100	Kprime	P120RC	4	5,30	7.150	LH282111	<b>81.678,00</b>



### HTL 80 SH QC Severe-Heavy-Duty Bucket

#### Quickcoupler suspension SW 100 (arm 2,9m)

trapezoid cutting edge T600x90mm (Hardox HiTuf), base and side cutting edges out of 400 HB steel, wear resistant plates on base (400 HB, 500 HB edges), additional wear protection for cutting edges and base by shrouds, buttons and wear plates. With Kprime adapter 5090P120 and tooth P120RC.

Width [mm]	Option	Tooth point	Teeth	Capacity SAE [m <sup>3</sup> ]	Weight [kg]	PN	Price [€]
2400	Kprime	P120RC	5	6,50	7.550	LH282112	<b>86.279,00</b>



### HRZ 130 bionic Ripper tooth

for demolition and rock use - with Lehmatic adapter SW 100, Hensley adapter and HL9W4551HX tooth point

Option	Tooth point	Angle	Tooth-radius [mm]	Weight [kg]	PN	Price [€]
Susp. SW 100	HL9W4551-HX	35	1850	2.690	LH225683	<b>41.876,00</b>



## **Lehnhoff Hartstahl GmbH**

Rungsstraße 10-15  
D-76534 Baden-Baden

Mailbox 11 01 65  
D-76487 Baden-Baden  
Tel. +49 (0)7223 / 966 - 0  
Fax +49 (0)7223 / 966 - 109  
E-Mail: info@lehnhoff.de

Spare parts:  
Tel. +49 (0)7223 / 966 - 202  
Fax +49 (0)7223 / 966 - 209  
E-Mail: ersatzteile@lehnhoff.de

**[www.lehnhoff.de](http://www.lehnhoff.de)**

### **Follow us on:**

 [facebook.com/LehnhoffHartstahl](https://facebook.com/LehnhoffHartstahl)

 [youtube.com/c/lehnhoff24](https://youtube.com/c/lehnhoff24)

 [twitter.com/lehnhoff24](https://twitter.com/lehnhoff24)

 [instagram.com/lehnhoff\\_official/](https://instagram.com/lehnhoff_official/)

 [linkedin.com/company/1039348](https://linkedin.com/company/1039348)

